

# Package ‘DA’

January 20, 2025

**Version** 1.2.0

**Date** 2021-07-11

**Title** Discriminant Analysis for Evolutionary Inference

**Description** Discriminant Analysis (DA) for evolutionary inference (Qin, X. et al, 2020, <[doi:10.22541/au.159256808.83862168](https://doi.org/10.22541/au.159256808.83862168)>), especially for population genetic structure and community structure inference. This package incorporates the commonly used linear and non-linear, local and global supervised learning approaches (discriminant analysis), including Linear Discriminant Analysis of Kernel Principal Components (LDAKPC), Local (Fisher) Linear Discriminant Analysis (LFDA), Local (Fisher) Discriminant Analysis of Kernel Principal Components (LFDAKPC) and Kernel Local (Fisher) Discriminant Analysis (KLFDA). These discriminant analyses can be used to do ecological and evolutionary inference, including demography inference, species identification, and population/community structure inference.

**biocViews** BiomedicalInformatics, ChIPSeq, Clustering, Coverage, DNAMethylation, DifferentialExpression, DifferentialMethylation, Software, DifferentialSplicing, Epigenetics, FunctionalGenomics, GeneExpression, GeneSetEnrichment, Genetics, ImmunoOncology, MultipleComparison, Normalization, Pathways, QualityControl, RNASeq, Regression, SAGE, Sequencing, Software, SystemsBiology, TimeCourse, Transcription, Transcriptomics

**Depends** R (>= 3.5)

**License** GPL-3

**SystemRequirements** GNU make

**URL** <https://xinghuq.github.io/DA/index.html>

**BugReports** <https://github.com/xinghuq/DA/issues>

**Imports** adegenet, lfda, MASS, kernlab, klaR, plotly, rARPACK, grDevices, stats, utils

**VignetteBuilder** knitr

**NeedsCompilation** no

**RoxygenNote** 6.1.1

**Suggests** knitr, testthat, rmarkdown

**Author** Xinghu Qin [aut, cre, cph] (<<https://orcid.org/0000-0003-2351-3610>>)

**Maintainer** Xinghu Qin <qinxinghu@gmail.com>

**Repository** CRAN

**Date/Publication** 2021-07-12 08:40:02 UTC

## Contents

KLFDA . . . . .	2
KLFDA.M . . . . .	5
KLFDA_mk . . . . .	6
kmatrixGauss . . . . .	8
LDAKPC . . . . .	8
LFDA . . . . .	10
LFDAKPC . . . . .	12
Mabayes . . . . .	13
predict . . . . .	14

## Index

16

KLFDA

*Kernel Local Fisher Discriminant Analysis (KLFDA)*

## Description

Kernel Local Fisher Discriminant Analysis (KLFDA). This function implements the Kernel Local Fisher Discriminant Analysis with an unified Kernel function. Different from KLFDA function, which adopts the Multinomial Kernel as an example, this function empolys the kernel function that allows you to choose various types of kernels. See the kernel function from "kernelMatriax" (kernlab).

## Usage

```
KLFDA(x, y, kernel = kernlab::polydot(degree = 1, scale = 1, offset = 1),
r = 20, tol, prior, CV = FALSE, usekernel = TRUE,
fL = 0.5, metric = c("weighted", "orthonormalized", "plain"),
knn = 6, reg = 0.001, ...)
```

## Arguments

x	The input training data
y	The training labels
kernel	The kernel function used to calculate kernel matrix. Choose the corresponding kernel you want, see details.
r	The number of reduced features you want to keep.

<code>tol</code>	The tolerance used to reject the uni-variance. This is important when the variance between classes is small, and setting the large tolerance will avoid the data distortion.
<code>prior</code>	The weight of each class, or the proportion of each class.
<code>CV</code>	Whether to do cross validation.
<code>usekernel</code>	whether to use kernel classifier, if TRUE, pass to Naive Bayes classifier.
<code>fL</code>	If usekernel is TRUE, pass to the kernel function.
<code>metric</code>	type of metric in the embedding space (default: 'weighted') 'weighted' - weighted eigenvectors 'orthonormalized' - orthonormalized 'plain' - raw eigenvectors
<code>knn</code>	The number of nearest neighbours
<code>reg</code>	The regularization parameter
<code>...</code>	additional arguments for the classifier

### Details

This function employs three different classifiers, the basic linear classifier, the Mabayes (Bayes rule and the Mahalanobis distance), and Niave Bayes classifier. The argument "kernel" in the klfda function is the kernel function used to calculate the kernel matrix. If usekernel is TRUE, the corresponding kernel parameters will pass to the Naive Bayes kernel classifier. The kernel parameter can be set to any function, of class kernel, which computes the inner product in feature space between two vector arguments. kernlab provides the most popular kernel functions which can be initialized by using the following functions:

- `rbdot` Radial Basis kernel function
- `polydot` Polynomial kernel function
- `vanilladot` Linear kernel function
- `tanhdot` Hyperbolic tangent kernel function
- `laplacedot` Laplacian kernel function
- `besseldot` Bessel kernel function
- `anovadot` ANOVA RBF kernel function
- `splinedot` the Spline kernel
- (see example.)

`kernelFast` is mainly used in situations where columns of the kernel matrix are computed per invocation. In these cases, evaluating the norm of each row-entry over and over again would cause significant computational overhead.

### Value

The results give the classified classes and the posterior possibility of each class using different classifier.

<code>class</code>	The class labels from linear classifier
<code>posterior</code>	The posterior possibility of each class from linear classifier

bayes_judgement	Discrimintion results using the Mabayes classifier
bayes_assignment	Discrimintion results using the Naive bayes classifier
Z	The reduced features

**Author(s)**

qinxinghu@gmail.com

**References**

- Sugiyama, M (2007). Dimensionality reduction of multimodal labeled data by local Fisher discriminant analysis. *Journal of Machine Learning Research*, vol.8, 1027-1061.
- Sugiyama, M (2006). Local Fisher discriminant analysis for supervised dimensionality reduction. In W. W. Cohen and A. Moore (Eds.), *Proceedings of 23rd International Conference on Machine Learning (ICML2006)*, 905-912.
- Original Matlab Implementation: <http://www.ms.k.u-tokyo.ac.jp/software.html#LFDA>
- Tang, Y., & Li, W. (2019). lfda: Local Fisher Discriminant Analysis in R. *Journal of Open Source Software*, 4(39), 1572.
- Moore, A. W. (2004). Naive Bayes Classifiers. In School of Computer Science. Carnegie Mellon University.
- Pierre Enel (2020). Kernel Fisher Discriminant Analysis (<https://www.github.com/p-enel/MatlabKFDA>), GitHub. Retrieved March 30, 2020.
- Karatzoglou, A., Smola, A., Hornik, K., & Zeileis, A. (2004). kernlab-an S4 package for kernel methods in R. *Journal of statistical software*, 11(9), 1-20.

**See Also**

`predict.KLFDA`, `KLFDA`

**Examples**

```
require(kernlab)
btest=KLFDA(as.matrix(iris[,1:4]),as.matrix(as.data.frame(iris[,5])),
kernel=kernlab::rbfdot(sigma = 0.1),
r=3,prior=NULL,tol=1e-90,
reg=0.01,metric = 'plain')
pred=predict.KLFDA(btest,testData=as.matrix(iris[1:10,1:4]),prior=NULL)
```

---

KLFDA*Kernel local Fisher discriminant analysis*

---

**Description**

This function performs Kernel Local Fisher Discriminant Analysis. The function provided here allows users to carry out the KLFDA using a pairwise matrix. We used the gaussian matrix as example. Users can compute different kernel matrix or distance matrix as the input for this function.

**Usage**

```
KLFDA(kdata, y, r,
metric = c("weighted", "orthonormalized", "plain"),
tol=1e-5,knn = 6, reg = 0.001)
```

**Arguments**

kdata	The input dataset (kernel matrix). The input data can be a genotype matrix, data frame, species occurrence matrix, or principal components. The dataset have to convert to a kernel matrix before feed into this function.
y	The group labels
r	Number of reduced features
metric	Type of metric in the embedding space (default: 'weighted') 'weighted' - weighted eigenvectors 'orthonormalized' - orthonormalized 'plain' - raw eigenvectors
knn	The number of nearest neighbours
tol	Tolerance to avoid singular values
reg	The regularization parameter

**Details**

Kernel Local Fisher Discriminant Analysis for any kernel matrix. It was proposed in Sugiyama, M (2006, 2007) as a non-linear improvement for discriminant analysis. This function is adopted from Tang et al. 2019.

**Value**

Z	The reduced features
Tr	The transformation matrix

**References**

- Tang, Y., & Li, W. (2019). lfda: Local Fisher Discriminant Analysis in R. *Journal of Open Source Software*, 4(39), 1572.
- Sugiyama, M (2007). Dimensionality reduction of multimodal labeled data by local Fisher discriminant analysis. *Journal of Machine Learning Research*, vol.8, 1027-1061.

Sugiyama, M (2006). Local Fisher discriminant analysis for supervised dimensionality reduction. In W. W. Cohen and A. Moore (Eds.), Proceedings of 23rd International Conference on Machine Learning (ICML2006), 905-912.

## See Also

KLFDA

## Examples

```
kmat <- kmatrixGauss(iris[, -5], sigma=1)
zklfda=KLFDA_mk(kmat, iris[, 5], r=3, metric = "plain", tol=1e-5 )
print(zklfda$Z)
```

KLFDA\_mk

*Kernel Local Fisher Discriminant Analysis (KLFDA) with Multinomial kernel*

## Description

Kernel Local Fisher Discriminant Analysis (KLFDA). This function implements the Kernel Local Fisher Discriminant Analysis with a Multinomial kernel.

## Usage

```
KLFDA_mk(X, Y, r, order, regParam,
usekernel = TRUE, fL = 0.5,
priors, tol, reg, metric,
plotFigures = FALSE, verbose, ...)
```

## Arguments

X	The input training data
Y	The training labels
r	The number of reduced features
order	The order passing to Multinomial Kernel
regParam	The regularization parameter for kernel matrix
usekernel	Whether to used kernel classifier
fL	pass to kernel classifier if usekenel is TRUE
priors	The weight of each class
tol	The tolerance for rejecting uni-variance
reg	The regularization parameter
metric	Type of metric in the embedding space (default: 'weighted') 'weighted' - weighted eigenvectors 'orthonormalized' - orthonormalized 'plain' - raw eigenvectors
plotFigures	whether to plot the reduced features, 3D plot
verbose	silence the processing
...	additional arguments for the classifier

## Details

This function uses Multinomial Kernel, users can replace the Multinomial Kernel based on your own purpose. The final discrimination employs three classifiers, the basic linear classifier, the Mabayes (Bayes rule and the Mahalanobis distance), and Niave Bayes classifier.

## Value

class	The class labels from linear classifier
posterior	The posterior possibility of each class from linear classifier
bayes_judgement	Discrimintion results using the Mabayes classifier
bayes_assignment	Discrimintion results using the Naive bayes classifier
Z	The reduced features

## Author(s)

qinxinghu@gmail.com

## References

- Sugiyama, M (2007). Dimensionality reduction of multimodal labeled data by local Fisher discriminant analysis. *Journal of Machine Learning Research*, vol.8, 1027-1061.
- Sugiyama, M (2006). Local Fisher discriminant analysis for supervised dimensionality reduction. In W. W. Cohen and A. Moore (Eds.), *Proceedings of 23rd International Conference on Machine Learning (ICML2006)*, 905-912.
- Original Matlab Implementation: <http://www.ms.k.u-tokyo.ac.jp/software.html#LFDA>
- Tang, Y., & Li, W. (2019). lfda: Local Fisher Discriminant Analysis inR. *Journal of Open Source Software*, 4(39), 1572.
- Moore, A. W. (2004). Naive Bayes Classifiers. In School of Computer Science. Carnegie Mellon University.
- Pierre Enel (2020). Kernel Fisher Discriminant Analysis (<https://www.github.com/p-enel/MatlabKFDA>), GitHub. Retrieved March 30, 2020.
- Karatzoglou, A., Smola, A., Hornik, K., & Zeileis, A. (2004). kernlab-an S4 package for kernel methods in R. *Journal of statistical software*, 11(9), 1-20.

## See Also

`predict.KLFDA_mk`, `klfda_1`

## Examples

```
btest=KLFDA_mk(X=as.matrix(iris[,1:4]),
Y=as.matrix(as.data.frame(iris[,5])),r=3,order=2,regParam=0.25,
usekernel=TRUE,fL=0.5,
priors=NULL,tol=1e-90,reg=0.01,metric = 'plain',plotFigures=FALSE,
```

```
verbose=TRUE)
#pred=predict.KLFDA_mk(btest,as.matrix(iris[1:10,1:4]))
```

kmatrixGauss

*Estimating Gaussian Kernel matrix***Description**

This function estimates Gaussian kernel computation for klfda, which maps the original data space to non-linear and higher dimensions. See the details of kmatrixGauss from lfda.

**Usage**

```
kmatrixGauss(x, sigma = 1)
```

**Arguments**

- |       |                                |
|-------|--------------------------------|
| x     | Input data matrix or dataframe |
| sigma | The Gaussian kernel parameter  |

**Details**

Return a n\*n matrix

**Value**

Return a n\*n matrix

**References**

Tang, Y., & Li, W. (2019). lfda: Local Fisher Discriminant Analysis in R. Journal of Open Source Software, 4(39), 1572.

LDAKPC

*Linear Fisher discriminant analysis of kernel principal components  
(DAKPC)***Description**

Linear Fisher discriminant analysis of kernel principal components (DAKPC). This function employs the LDA and kpca. This function is called Kernel Fisher Discriminant Analysis (KFDA) in other package (kfda). "KFDA" is the misleading name and "KFDA" has crucial error in package kfda. This function rectifies the current existing error for kfda.

**Usage**

```
LDAKPC(x, y, n.pc, usekernel = FALSE,
fL = 0, kernel.name = "rbfdot",
kpar = list(0.001), kernel = "gaussian",
threshold = 1e-05, ...)
```

**Arguments**

x	Input traing data
y	Input labels
n.pc	number of pcs that will be kept in analysis
usekernel	Whether to use kernel function, if TRUE, it will pass to the kernel.names
fL	if using kernel, pass to kernel function
kernel.name	if usekernel is TURE, this will take the kernel name and use the parameters set as you defined
kpar	the list of hyper-parameters (kernel parameters). This is a list which contains the parameters to be used with the kernel function. Valid parameters for existing kernels are : sigma inverse kernel width for the Radial Basis kernel function "rbfdot" and the Laplacian kernel "laplacedot". degree, scale, offset for the Polynomial kernel "polydot" scale, offset for the Hyperbolic tangent kernel function "tanhdot" sigma, order, degree for the Bessel kernel "besseldorf". sigma, degree for the ANOVA kernel "anovadot". Hyper-parameters for user defined kernels can be passed through the kpar parameter as well.
kernel	kernel name if all the above are not used
threshold	the threshold for kpc: value of the eigenvalue under which principal components are ignored (only valid when features = 0). (default : 0.0001)
...	additional arguments for the classifier

**Value**

kPCA	Results of kernel principal component analysis. Kernel Principal Components Analysis is a nonlinear form of principal component analysis
kpc	Kernel principal components. The scores of the components
LDAKPC	Linear discriminant anslysis of kernel principal components
LDs	The discriminant function. The scores of the components
label	The corresponding class of the data
n.pc	Number of Pcs kept in analysis

**Author(s)**

qinxinghu@gmail.com

## References

- Karatzoglou, A., Smola, A., Hornik, K., & Zeileis, A. (2004). kernlab-an S4 package for kernel methods in R. *Journal of statistical software*, 11(9), 1-20.
- Mika, S., Ratsch, G., Weston, J., Scholkopf, B., & Mullers, K. R. (1999, August). Fisher discriminant analysis with kernels. In *Neural networks for signal processing IX: Proceedings of the 1999 IEEE signal processing society workshop* (cat. no. 98th8468) (pp. 41-48). Ieee.

## Examples

```
data(iris)
train=LDAKPC(iris[,1:4],y=iris[,5],n.pc=3,kernel.name = "rbfdot")
pred=predict.LDAKPC(train,testData = iris[1:10,1:4])
```

LFDA

*Local Fisher Discriminant Analysis (LFDA)*

## Description

This function implements local Fisher discriminant analysis. It gives the discriminant function with the posterior possibility of each class.

## Usage

```
LFDA(x, y, r, prior = proportions,
CV = FALSE, usekernel = TRUE, fL = 0,
tol, kernel = "gaussian",
metric = c("orthonormalized", "plain", "weighted"),
knn = 5, ...)
```

## Arguments

<code>x</code>	Input training data
<code>y</code>	Training labels
<code>r</code>	Number of reduced features that will be kept
<code>prior</code>	Prior possibility of each class
<code>CV</code>	Whether to do cross validation
<code>usekernel</code>	Whether to use the kernel discrimination in native bayes classifier
<code>fL</code>	Feed to native bayes classifier. Factor for Laplace correction, default factor is 0, i.e. no correction.
<code>tol</code>	The tolerance used in Mabayes discrimination, see Mabayes
<code>kernel</code>	If usekernel is TRUE, specifying the kernel names, see NaiveBaye.
<code>metric</code>	The type of metric in the embedding space (no default), e.g., 'weighted', weighted eigenvectors; 'orthonormalized', orthonormalized; 'plain', raw eigenvectors.
<code>knn</code>	Number of nearest neighbors
<code>...</code>	additional arguments for the classifier

## Details

The results give the classified classes and the posterior possibility of each class using different classifier.

## Value

class	The class labels
posterior	The posterior possibility of each class
bayes_judgement	Discrimintion results using the Mabayes classifier
bayes_assignment	Discrimintion results using the Naive bayes classifier
z	The reduced features

## Author(s)

qinxinghu@gmail.com

## References

- Sugiyama, M (2007). Dimensionality reduction of multimodal labeled data by local Fisher discriminant analysis. *Journal of Machine Learning Research*, vol.8, 1027-1061.
- Sugiyama, M (2006). Local Fisher discriminant analysis for supervised dimensionality reduction. In W. W. Cohen and A. Moore (Eds.), *Proceedings of 23rd International Conference on Machine Learning (ICML2006)*, 905-912.
- Tang, Y., & Li, W. (2019). Ifda: Local Fisher Discriminant Analysis inR. *Journal of Open Source Software*, 4(39), 1572.
- Moore, A. W. (2004). Naive Bayes Classifiers. In School of Computer Science. Carnegie Mellon University.
- Pierre Enel (2020). Kernel Fisher Discriminant Analysis (<https://www.github.com/p-enel/MatlabKFDA>), GitHub. Retrieved March 30, 2020.

## Examples

```
LFDAtest=LFDA(iris[,1:4],y=iris[,5],r=3,
CV=FALSE,usekernel = TRUE, fL = 0,
kernel="gaussian",metric = "plain",knn = 6,tol = 1)
LFDApred=predict.LFDA(LFDAtest,iris[1:10,1:4],prior=NULL)
```

---

LFDAKPC*Local Fisher Discriminant Analysis of Kernel principle components  
(LFDAKPC)*

---

## Description

Local Fisher Discriminant Analysis of Kernel principle components

## Usage

```
LFDAKPC(x, y, n.pc,
usekernel = FALSE, fL = 0,
kernel.name = "rbfdot",
kpar = list(0.001), kernel = "gaussian",
threshold = 1e-05, ...)
```

## Arguments

x	Input traing data
y	Input labels
n.pc	number of pcs that will be kept in analysis
usekernel	Whether to use kernel function, if TRUE, it will pass to the kernel.names
fL	if using kernel, pass to kernel function
kernel.name	if usekernel is TURE, this will take the kernel name and use the parameters set as you defined
kpar	the list of hyper-parameters (kernel parameters). This is a list which contains the parameters to be used with the kernel function. Valid parameters for existing kernels are :  sigma inverse kernel width for the Radial Basis kernel function "rbfdot" and the Laplacian kernel "laplacedot". degree, scale, offset for the Polynomial kernel "polydot" scale, offset for the Hyperbolic tangent kernel function "tanhdot" sigma, order, degree for the Bessel kernel "besseldot". sigma, degree for the ANOVA kernel "anovadot". Hyper-parameters for user defined kernels can be passed through the kpar parameter as well.
kernel	kernel name if all the above are not used
threshold	the threshold for kpc: value of the eigenvalue under which principal components are ignored (only valid when features = 0). (default : 0.0001)
...	additional arguments for the classifier

**Value**

kPCA	Results of kernel principal component analysis. Kernel Principal Components Analysis is a nonlinear form of principal component analysis
kPC	Kernel principal components. The scores of the components
LFDKPC	Local linear discriminant analysis of kernel principal components
LDs	The discriminant function. The scores of the components
label	The corresponding class of the data
n.pc	Number of PCs kept in analysis

**Author(s)**

qinxinghu@gmail.com

**References**

- Sugiyama, M (2007). Dimensionality reduction of multimodal labeled data by local Fisher discriminant analysis. *Journal of Machine Learning Research*, vol.8, 1027-1061.
- Sugiyama, M (2006). Local Fisher discriminant analysis for supervised dimensionality reduction. In W. W. Cohen and A. Moore (Eds.), *Proceedings of 23rd International Conference on Machine Learning (ICML2006)*, 905-912.
- Tang, Y., & Li, W. (2019). lfda: Local Fisher Discriminant Analysis in R. *Journal of Open Source Software*, 4(39), 1572.
- Karatzoglou, A., Smola, A., Hornik, K., & Zeileis, A. (2004). kernlab-an S4 package for kernel methods in R. *Journal of statistical software*, 11(9), 1-20.

**Examples**

```
train=LFDKPC(iris[,1:4],y=iris[,5],tol=1,n.pc=3,kernel.name = "rbfdot")
pred=predict.LFDKPC(train,prior=NULL,testData = iris[1:10,1:4])
```

Mabayes

*Membership assignment by weighted Mahalanobis distance and bayes rule*

**Description**

The function gives the discrimination of the potential classes based on Bayes rule and the Mahalanobis distance. This function adopts the function from Bingpei Wu, 2012, WMDB 1.0 with some corrections of the judgment rule.

**Usage**

```
Mabayes(TrnX, TrnG, p = rep(1, length(levels(TrnG))), TstX = NULL, var.equal = FALSE, tol)
```

**Arguments**

TrnX	Training data
TrnG	Training label
p	prior or proportion of each class
TstX	Test data
var.equal	whether the variance or the weight is equal between classes
tol	The threshold or tolerance value for the covariance and distance

**Value**

posterior and class	
	The posterior possibility and class labels

**Author(s)**

qinxinghu@gmail.com

**References**

- Bingpei Wu, 2012, WMDB 1.0: Discriminant Analysis Methods by Weight Mahalanobis Distance and bayes.
- Ito, Y., Srinivasan, C., Izumi, H. (2006, September). Discriminant analysis by a neural network with Mahalanobis distance. In International Conference on Artificial Neural Networks (pp. 350-360). Springer, Berlin, Heidelberg.
- Wolfel, M., Ekenel, H. K. (2005, September). Feature weighted Mahalanobis distance: improved robustness for Gaussian classifiers. In 2005 13th European signal processing conference (pp. 1-4). IEEE.

**Examples**

```
data(iris)
train=Mabayes(iris[,1:4],iris[,5],TstX= iris[1:10,1:4],tol = 1)
```

**predict**

*Predict method in DA for discriminant analysis*

**Description**

Predict method for DA.

**Usage**

```
## S3 method for class 'KLFDA_mk'  
predict(object,prior,testData, ...)  
## S3 method for class 'KLFDA'  
predict(object,prior,testData, ...)  
## S3 method for class 'LDAKPC'  
predict(object,prior,testData, ...)  
## S3 method for class 'LFDA'  
predict(object,prior,testData, ...)  
## S3 method for class 'LFDAKPC'  
predict(object,prior,testData, ...)
```

**Arguments**

object	One of the trained object from discriminant analysis
prior	The weights of the groups.
testData	The test data or new data
...	Arguments passed to the classifiers

**Value**

The predict function will output the predicted points and their predicted possibility

# Index

- \* **KLFDA\_mk**
  - KLFDA\_mk, [6](#)
- \* **KLFDA**
  - KLFDA, [2](#)
- \* **LDAKPC**
  - LDAKPC, [8](#)
- \* **LFDAKPC**
  - LFDAKPC, [12](#)
- \* **LFDA**
  - LFDA, [10](#)
- \* **predict**
  - predict, [14](#)

KLFDA, [2](#)  
KLFDA\_mk, [6](#)  
KLFDAM, [5](#)  
kmatrixGauss, [8](#)

LDAKPC, [8](#)  
LFDA, [10](#)  
LFDAKPC, [12](#)

Mabayes, [13](#)

predict, [14](#)