

Package ‘NNS’

July 15, 2025

Type Package

Title Nonlinear Nonparametric Statistics

Version 11.4.1

Date 2025-07-15

Maintainer Fred Viole <ovvo.financial.systems@gmail.com>

Description

NNS (Nonlinear Nonparametric Statistics) leverages partial moments – the fundamental elements of variance that asymptotically approximate the area under $f(x)$ – to provide a robust foundation for nonlinear analysis while maintaining linear equivalences. NNS delivers a comprehensive suite of advanced statistical techniques, including: Numerical integration, Numerical differentiation, Clustering, Correlation, Dependence, Causal analysis, ANOVA, Regression, Classification, Seasonality, Autoregressive modeling, Normalization, Stochastic dominance and Advanced Monte Carlo sampling. All routines based on: Viole, F. and Nawrocki, D. (2013), Nonlinear Nonparametric Statistics: Using Partial Moments (ISBN: 1490523995).

License GPL-3

BugReports <https://github.com/OVVO-Financial/NNS/issues>

Depends R (>= 3.6.0)

Imports data.table, doParallel, foreach, quantmod, Rcpp, RcppParallel,
Rfast, rgl, xts, zoo

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

LinkingTo Rcpp, RcppParallel

SystemRequirements GNU make

Config/testthat/edition 3

RoxygenNote 7.2.3

Encoding UTF-8

NeedsCompilation yes

Author Fred Viole [aut, cre],
Roberto Spadim [ctb]

Repository CRAN

Date/Publication 2025-07-15 16:10:02 UTC

Contents

Co.LPM	3
Co.UPM	4
D.LPM	5
D.UPM	6
dy.dx	7
dy.d_	8
LPM	10
LPM.ratio	11
LPM.VaR	12
NNS.ANOVA	13
NNS.ARMA	15
NNS.ARMA.optim	17
NNS.boost	20
NNS.caus	22
NNS.CDF	23
NNS.copula	25
NNS.dep	26
NNS.diff	27
NNS.distance	28
NNS.FSD	29
NNS.FSD.uni	30
NNS.gravity	31
NNS.MC	31
NNS.meboot	33
NNS.mode	36
NNS.moments	37
NNS.norm	38
NNS.nowcast	39
NNS.part	42
NNS.reg	44
NNS.rescale	48
NNS.SD.cluster	49
NNS.SD.efficient.set	51
NNS.seas	52
NNS.SSD	53
NNS.SSD.uni	54
NNS.stack	55
NNS.term.matrix	58
NNS.TSD	59
NNS.TSD.uni	60
NNS.VAR	61
PM.matrix	64
UPM	65
UPM.ratio	66
UPM.VaR	67

Co.LPM

*Co-Lower Partial Moment (Lower Left Quadrant 4)***Description**

This function generates a co-lower partial moment for between two equal length variables for any degree or target.

Usage

```
Co.LPM(degree_lpm, x, y, target_x, target_y)
```

Arguments

degree_lpm	integer; Degree for lower deviations of both variable X and Y. (degree_lpm = 0) is frequency, (degree_lpm = 1) is area.
x	a numeric vector. data.frame or list type objects are not permissible.
y	a numeric vector of equal length to x. data.frame or list type objects are not permissible.
target_x	numeric; Target for lower deviations of variable X. Typically the mean of Variable X for classical statistics equivalences, but does not have to be.
target_y	numeric; Target for lower deviations of variable Y. Typically the mean of Variable Y for classical statistics equivalences, but does not have to be.

Value

Co-LPM of two variables

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
Co.LPM(0, x, y, mean(x), mean(y))
```

Co.UPM

*Co-Upper Partial Moment (Upper Right Quadrant 1)***Description**

This function generates a co-upper partial moment between two equal length variables for any degree or target.

Usage

```
Co.UPM(degree_upm, x, y, target_x, target_y)
```

Arguments

degree_upm	integer; Degree for upper variations of both variable X and Y. (degree_upm = 0) is frequency, (degree_upm = 1) is area.
x	a numeric vector. data.frame or list type objects are not permissible.
y	a numeric vector of equal length to x. data.frame or list type objects are not permissible.
target_x	numeric; Target for upside deviations of variable X. Typically the mean of Variable X for classical statistics equivalences, but does not have to be.
target_y	numeric; Target for upside deviations of variable Y. Typically the mean of Variable Y for classical statistics equivalences, but does not have to be.

Value

Co-UPM of two variables

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
Co.UPM(0, x, y, mean(x), mean(y))
```

D.LPM

*Divergent-Lower Partial Moment (Lower Right Quadrant 3)***Description**

This function generates a divergent lower partial moment between two equal length variables for any degree or target.

Usage

```
D.LPM(degree_lpm, degree_upm, x, y, target_x, target_y)
```

Arguments

degree_lpm	integer; Degree for lower deviations of variable Y. (degree_lpm = 0) is frequency, (degree_lpm = 1) is area.
degree_upm	integer; Degree for upper deviations of variable X. (degree_upm = 0) is frequency, (degree_upm = 1) is area.
x	a numeric vector. data.frame or list type objects are not permissible.
y	a numeric vector of equal length to x. data.frame or list type objects are not permissible.
target_x	numeric; Target for upside deviations of variable X. Typically the mean of Variable X for classical statistics equivalences, but does not have to be.
target_y	numeric; Target for lower deviations of variable Y. Typically the mean of Variable Y for classical statistics equivalences, but does not have to be.

Value

Divergent LPM of two variables

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
D.LPM(0, 0, x, y, mean(x), mean(y))
```

D.UPM

*Divergent-Upper Partial Moment (Upper Left Quadrant 2)***Description**

This function generates a divergent upper partial moment between two equal length variables for any degree or target.

Usage

```
D.UPM(degree_lpm, degree_upm, x, y, target_x, target_y)
```

Arguments

degree_lpm	integer; Degree for lower deviations of variable X. (degree_lpm = 0) is frequency, (degree_lpm = 1) is area.
degree_upm	integer; Degree for upper deviations of variable Y. (degree_upm = 0) is frequency, (degree_upm = 1) is area.
x	a numeric vector. data.frame or list type objects are not permissible.
y	a numeric vector of equal length to x. data.frame or list type objects are not permissible.
target_x	numeric; Target for lower deviations of variable X. Typically the mean of Variable X for classical statistics equivalences, but does not have to be.
target_y	numeric; Target for upper deviations of variable Y. Typically the mean of Variable Y for classical statistics equivalences, but does not have to be.

Value

Divergent UPM of two variables

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
D.UPM(0, 0, x, y, mean(x), mean(y))
```

dy.dx	<i>Partial Derivative dy/dx</i>
-------	---------------------------------

Description

Returns the numerical partial derivative of y wrt x for a point of interest.

Usage

```
dy.dx(x, y, eval.point = NULL)
```

Arguments

x	a numeric vector.
y	a numeric vector.
eval.point	numeric or ("overall"); x point to be evaluated, must be provided. Defaults to (eval.point = NULL). Set to (eval.point = "overall") to find an overall partial derivative estimate (1st derivative only).

Value

Returns a data.table of eval.point along with both 1st and 2nd derivative.

Note

If a vector of derivatives is required, ensure (deriv.method = "FD").

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Vinod, H. and Viole, F. (2017) "Nonparametric Regression Using Clusters" [doi:10.1007/s10614-01797135](https://doi.org/10.1007/s10614-01797135)

Examples

```
## Not run:
x <- seq(0, 2 * pi, pi / 100) ; y <- sin(x)
dy.dx(x, y, eval.point = 1.75)

# First derivative
dy.dx(x, y, eval.point = 1.75)[ , first.derivative]

# Second derivative
```

```

dy.dx(x, y, eval.point = 1.75)[ , second.derivative]

# Vector of derivatives
dy.dx(x, y, eval.point = c(1.75, 2.5))

## End(Not run)

```

dy.d_

Partial Derivative $dy/d_{[wrt]}$

Description

Returns the numerical partial derivative of y with respect to [wrt] any regressor for a point of interest. Finite difference method is used with [NNS.reg](#) estimates as $f(x + h)$ and $f(x - h)$ values.

Usage

```
dy.d_(x, y, wrt, eval.points = "obs", mixed = FALSE, messages = TRUE)
```

Arguments

x	a numeric matrix or data frame.
y	a numeric vector with compatible dimensions to x.
wrt	integer; Selects the regressor to differentiate with respect to (vectorized).
eval.points	numeric or options: ("obs", "apd", "mean", "median", "last"); Regressor points to be evaluated. • Numeric values must be in matrix or data.frame form to be evaluated for each regressor, otherwise, a vector of points will evaluate only at the wrt regressor. See examples for use cases. • Set to (eval.points = "obs") (default) to find the average partial derivative at every observation of the variable with respect to <i>for specific tuples of given observations</i>. • Set to (eval.points = "apd") to find the average partial derivative at every observation of the variable with respect to <i>over the entire distribution of other regressors</i>. • Set to (eval.points = "mean") to find the partial derivative at the mean of value of every variable. • Set to (eval.points = "median") to find the partial derivative at the median value of every variable. • Set to (eval.points = "last") to find the partial derivative at the last observation of every value (relevant for time-series data).
mixed	logical; FALSE (default) If mixed derivative is to be evaluated, set (mixed = TRUE).
messages	logical; TRUE (default) Prints status messages.

Value

Returns column-wise matrix of wrt regressors:

- `dy.d(...)[, wrt]$First` the 1st derivative
- `dy.d(...)[, wrt]$Second` the 2nd derivative
- `dy.d(...)[, wrt]$Mixed` the mixed derivative (for two independent variables only).

Note

For binary regressors, it is suggested to use `eval.points = seq(0, 1, .05)` for a better resolution around the midpoint.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Vinod, H. and Viole, F. (2020) "Comparing Old and New Partial Derivative Estimates from Nonlinear Nonparametric Regressions" [doi:10.2139/ssrn.3681104](https://doi.org/10.2139/ssrn.3681104)

Examples

```
## Not run:
set.seed(123) ; x_1 <- runif(1000) ; x_2 <- runif(1000) ; y <- x_1 ^ 2 * x_2 ^ 2
B <- cbind(x_1, x_2)

## To find derivatives of y wrt 1st regressor for specific points of both regressors
dy.d(B, y, wrt = 1, eval.points = t(c(.5, 1)))

## To find average partial derivative of y wrt 1st regressor,
only supply 1 value in [eval.points], or a vector of [eval.points]:
dy.d(B, y, wrt = 1, eval.points = .5)

dy.d(B, y, wrt = 1, eval.points = fivenum(B[,1]))

## To find average partial derivative of y wrt 1st regressor,
for every observation of 1st regressor:
apd <- dy.d(B, y, wrt = 1, eval.points = "apd")
plot(B[,1], apd[,1]$First)

## 95% Confidence Interval to test if 0 is within
### Lower CI
LPM.VaR(.025, 0, apd[,1]$First)

### Upper CI
UPM.VaR(.025, 0, apd[,1]$First)
```

```
## End(Not run)
```

LPM

Lower Partial Moment

Description

This function generates a univariate lower partial moment for any degree or target.

Usage

```
LPM(degree, target, variable, excess_ret = FALSE)
```

Arguments

degree	integer; (degree = 0) is frequency, (degree = 1) is area.
target	numeric; Set to target = mean(variable) for classical equivalences, but does not have to be. (Vectorized)
variable	a numeric vector. data.frame or list type objects are not permissible.
excess_ret	Logical; FALSE (default)

Value

LPM of variable

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
set.seed(123)
x <- rnorm(100)
LPM(0, mean(x), x)
```

LPM.ratio	<i>Lower Partial Moment RATIO</i>
-----------	-----------------------------------

Description

This function generates a standardized univariate lower partial moment for any degree or target.

Usage

```
LPM.ratio(degree, target, variable)
```

Arguments

degree	integer; (degree = 0) is frequency, (degree = 1) is area.
target	numeric; Typically set to mean, but does not have to be. (Vectorized)
variable	a numeric vector.

Value

Standardized LPM of variable

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Viole, F. (2017) "Continuous CDFs and ANOVA with NNS" [doi:10.2139/ssrn.3007373](https://doi.org/10.2139/ssrn.3007373)

Examples

```
set.seed(123)
x <- rnorm(100)
LPM.ratio(0, mean(x), x)

## Not run:
## Empirical CDF (degree = 0)
lpm_cdf <- LPM.ratio(0, sort(x), x)
plot(sort(x), lpm_cdf)

## Continuous CDF (degree = 1)
lpm_cdf_1 <- LPM.ratio(1, sort(x), x)
plot(sort(x), lpm_cdf_1)

## Joint CDF
x <- rnorm(5000) ; y <- rnorm(5000)
```

```
plot3d(x, y, Co.LPM(0, sort(x), sort(y), x, y), col = "blue", xlab = "X", ylab = "Y",
zlab = "Probability", box = FALSE)

## End(Not run)
```

LPM.VaR

LPM VaR

Description

Generates a value at risk (VaR) quantile based on the Lower Partial Moment ratio.

Usage

```
LPM.VaR(percentile, degree, x)
```

Arguments

percentile	numeric [0, 1]; The percentile for left-tail VaR (vectorized).
degree	integer; (degree = 0) for discrete distributions, (degree = 1) for continuous distributions.
x	a numeric vector.

Value

Returns a numeric value representing the point at which "percentile" of the area of x is below.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100)

## For 5th percentile, left-tail
LPM.VaR(0.05, 0, x)

## End(Not run)
```

NNS.ANOVA

NNS ANOVA

Description

Analysis of variance (ANOVA) based on lower partial moment CDFs for multiple variables, evaluated at multiple quantiles (or means only). Returns a degree of certainty to whether the population distributions (or sample means) are identical, not a p-value.

Usage

```
NNS.ANOVA(
  control,
  treatment,
  means.only = FALSE,
  medians = FALSE,
  confidence.interval = 0.95,
  tails = "Both",
  pairwise = FALSE,
  plot = TRUE,
  robust = FALSE
)
```

Arguments

<code>control</code>	a numeric vector, matrix or data frame, or list if unequal vector lengths.
<code>treatment</code>	NULL (default) a numeric vector, matrix or data frame.
<code>means.only</code>	logical; FALSE (default) test whether difference in sample means only is zero.
<code>medians</code>	logical; FALSE (default) test whether difference in sample medians only is zero. Requires <code>means.only = TRUE</code> .
<code>confidence.interval</code>	numeric [0, 1]; The confidence interval surrounding the <code>control</code> mean, defaults to (<code>confidence.interval = 0.95</code>).
<code>tails</code>	options: ("Left", "Right", "Both"). <code>tails = "Both"</code> (Default) Selects the tail of the distribution to determine effect size.
<code>pairwise</code>	logical; FALSE (default) Returns pairwise certainty tests when set to <code>pairwise = TRUE</code> .
<code>plot</code>	logical; TRUE (default) Returns the boxplot of all variables along with grand mean identification and confidence interval thereof.
<code>robust</code>	logical; FALSE (default) Generates 100 independent random permutations to test results, and returns / plots 95 percent confidence intervals along with robust central tendency of all results for pairwise analysis only.

Value

Returns the following:

- "Control Mean" control mean.
- "Treatment Mean" treatment mean.
- "Grand Mean" mean of means.
- "Control CDF" CDF of the control from the grand mean.
- "Treatment CDF" CDF of the treatment from the grand mean.
- "Certainty" the certainty of the same population statistic.
- "Lower Bound Effect" and "Upper Bound Effect" the effect size of the treatment for the specified confidence interval.
- "Robust Certainty Estimate" and "Lower 95 CI", "Upper 95 CI" are the robust certainty estimate and its 95 percent confidence interval after permutations if robust = TRUE.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Viole, F. (2017) "Continuous CDFs and ANOVA with NNS" [doi:10.2139/ssrn.3007373](https://doi.org/10.2139/ssrn.3007373)

Examples

```
## Not run:
### Binary analysis and effect size
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
NNS.ANOVA(control = x, treatment = y)

### Two variable analysis with no control variable
A <- cbind(x, y)
NNS.ANOVA(A)

### Medians test
NNS.ANOVA(A, means.only = TRUE, medians = TRUE)

### Multiple variable analysis with no control variable
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100) ; z <- rnorm(100)
A <- cbind(x, y, z)
NNS.ANOVA(A)

### Different length vectors used in a list
x <- rnorm(30) ; y <- rnorm(40) ; z <- rnorm(50)
A <- list(x, y, z)
```

```

NNS.ANOVA(A)

## End(Not run)

```

NNS.ARMA

NNS ARMA

Description

Autoregressive model incorporating nonlinear regressions of component series.

Usage

```

NNS.ARMA(
  variable,
  h = 1,
  training.set = NULL,
  seasonal.factor = TRUE,
  weights = NULL,
  best.periods = 1,
  modulo = NULL,
  mod.only = TRUE,
  negative.values = FALSE,
  method = "nonlin",
  dynamic = FALSE,
  shrink = FALSE,
  plot = TRUE,
  seasonal.plot = TRUE,
  pred.int = NULL
)

```

Arguments

<code>variable</code>	a numeric vector.
<code>h</code>	integer; 1 (default) Number of periods to forecast.
<code>training.set</code>	numeric; NULL (default) Sets the number of variable observations (<code>variable[1 : training.set]</code>) to monitor performance of forecast over in-sample range.
<code>seasonal.factor</code>	logical or integer(s); TRUE (default) Automatically selects the best seasonal lag from the seasonality test. To use weighted average of all seasonal lags set to (<code>seasonal.factor = FALSE</code>). Otherwise, directly input known frequency integer lag to use, i.e. (<code>seasonal.factor = 12</code>) for monthly data. Multiple frequency integers can also be used, i.e. (<code>seasonal.factor = c(12, 24, 36)</code>)

<code>weights</code>	numeric or "equal"; NULL (default) sets the weights of the <code>seasonal.factor</code> vector when specified as integers. If (<code>weights = NULL</code>) each <code>seasonal.factor</code> is weighted on its NNS.seas result and number of observations it contains, else an "equal" weight is used.
<code>best.periods</code>	integer; [2] (default) used in conjunction with (<code>seasonal.factor = FALSE</code>), uses the <code>best.periods</code> number of detected seasonal lags instead of ALL lags when (<code>seasonal.factor = FALSE</code> , <code>best.periods = NULL</code>).
<code>modulo</code>	integer(s); NULL (default) Used to find the nearest multiple(s) in the reported seasonal period.
<code>mod.only</code>	logical; TRUE (default) Limits the number of seasonal periods returned to the specified modulo.
<code>negative.values</code>	logical; FALSE (default) If the variable can be negative, set to (<code>negative.values = TRUE</code>). If there are negative values within the variable, <code>negative.values</code> will automatically be detected.
<code>method</code>	options: ("lin", "nonlin", "both", "means"); "nonlin" (default) To select the regression type of the component series, select (<code>method = "both"</code>) where both linear and nonlinear estimates are generated. To use a nonlinear regression, set to (<code>method = "nonlin"</code>); to use a linear regression set to (<code>method = "lin"</code>). Means for each subset are returned with (<code>method = "means"</code>).
<code>dynamic</code>	logical; FALSE (default) To update the seasonal factor with each forecast point, set to (<code>dynamic = TRUE</code>). The default is (<code>dynamic = FALSE</code>) to retain the original seasonal factor from the inputted variable for all ensuing h.
<code>shrink</code>	logical; FALSE (default) Ensembles forecasts with <code>method = "means"</code> .
<code>plot</code>	logical; TRUE (default) Returns the plot of all periods exhibiting seasonality and the variable level reference in upper panel. Lower panel returns original data and forecast.
<code>seasonal.plot</code>	logical; TRUE (default) Adds the seasonality plot above the forecast. Will be set to FALSE if no seasonality is detected or <code>seasonal.factor</code> is set to an integer value.
<code>pred.int</code>	numeric [0, 1]; NULL (default) Plots and returns the associated prediction intervals for the final estimate. Constructed using the maximum entropy bootstrap NNS.meboot on the final estimates.

Value

Returns a vector of forecasts of length (h) if no `pred.int` specified. Else, returns a `data.table` with the forecasts as well as lower and upper prediction intervals per forecast point.

Note

For monthly data series, increased accuracy may be realized from forcing seasonal factors to multiples of 12. For example, if the best periods reported are: {37, 47, 71, 73} use (`seasonal.factor = c(36, 48, 72)`).

(`seasonal.factor = FALSE`) can be a very computationally expensive exercise due to the number of seasonal periods detected.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Viole, F. (2019) "Forecasting Using NNS" [doi:10.2139/ssrn.3382300](https://doi.org/10.2139/ssrn.3382300)

Examples

```
## Nonlinear NNS.ARMA using AirPassengers monthly data and 12 period lag
## Not run:
NNS.ARMA(AirPassengers, h = 45, training.set = 100, seasonal.factor = 12, method = "nonlin")

## Linear NNS.ARMA using AirPassengers monthly data and 12, 24, and 36 period lags
NNS.ARMA(AirPassengers, h = 45, training.set = 120, seasonal.factor = c(12, 24, 36), method = "lin")

## Nonlinear NNS.ARMA using AirPassengers monthly data and 2 best periods lag
NNS.ARMA(AirPassengers, h = 45, training.set = 120, seasonal.factor = FALSE, best.periods = 2)

## End(Not run)
```

NNS.ARMA.optim

NNS ARMA Optimizer

Description

Wrapper function for optimizing any combination of a given seasonal.factor vector in [NNS.ARMA](#). Minimum sum of squared errors (forecast-actual) is used to determine optimum across all [NNS.ARMA](#) methods.

Usage

```
NNS.ARMA.optim(
  variable,
  h = NULL,
  training.set = NULL,
  seasonal.factor,
  negative.values = FALSE,
  obj.fn = expression(mean((predicted - actual)^2)/(NNS::Co.LPM(1, predicted, actual,
    target_x = mean(predicted), target_y = mean(actual)) + NNS::Co.UPM(1, predicted,
    actual, target_x = mean(predicted), target_y = mean(actual)))),
  objective = "min",
  linear.approximation = TRUE,
  ncores = NULL,
  pred.int = 0.95,
```

```

    print.trace = TRUE,
    plot = FALSE
  )

```

Arguments

<code>variable</code>	a numeric vector.
<code>h</code>	integer; NULL (default) Number of periods to forecast out of sample. If NULL, $h = \text{length}(\text{variable}) - \text{training.set}$.
<code>training.set</code>	integer; NULL (default) Sets the number of variable observations as the training set. See Note below for recommended uses.
<code>seasonal.factor</code>	integers; Multiple frequency integers considered for NNS.ARMA model, i.e. (<code>seasonal.factor = c(12, 24, 36)</code>)
<code>negative.values</code>	logical; FALSE (default) If the variable can be negative, set to (<code>negative.values = TRUE</code>). It will automatically select (<code>negative.values = TRUE</code>) if the minimum value of the variable is negative.
<code>obj.fn</code>	expression; <code>expression(cor(predicted, actual, method = "spearman") / sum((predicted - actual)^2))</code> (default) Rank correlation / sum of squared errors is the default objective function. Any <code>expression(...)</code> using the specific terms <code>predicted</code> and <code>actual</code> can be used.
<code>objective</code>	options: ("min", "max") "max" (default) Select whether to minimize or maximize the objective function <code>obj.fn</code> .
<code>linear.approximation</code>	logical; TRUE (default) Uses the best linear output from <code>NNS.reg</code> to generate a nonlinear and mixture regression for comparison. FALSE is a more exhaustive search over the objective space.
<code>ncores</code>	integer; value specifying the number of cores to be used in the parallelized procedure. If NULL (default), the number of cores to be used is equal to the number of cores of the machine - 1.
<code>pred.int</code>	numeric [0, 1]; 0.95 (default) Returns the associated prediction intervals for the final estimate. Constructed using the maximum entropy bootstrap NNS.meboot on the final estimates.
<code>print.trace</code>	logical; TRUE (default) Prints current iteration information. Suggested as backup in case of error, best parameters to that point still known and copyable!
<code>plot</code>	logical; FALSE (default)

Value

Returns a list containing:

- `$period` a vector of optimal seasonal periods
- `$weights` the optimal weights of each seasonal period between an equal weight or NULL weighting
- `$obj.fn` the objective function value

- `$method` the method identifying which [NNS.ARMA](#) method was used.
- `$shrink` whether to use the shrink parameter in [NNS.ARMA](#).
- `$nns.regress` whether to smooth the variable via [NNS.reg](#) before forecasting.
- `$bias.shift` a numerical result of the overall bias of the optimum objective function result. To be added to the final result when using the [NNS.ARMA](#) with the derived parameters.
- `$errors` a vector of model errors from internal calibration.
- `$results` a vector of length `h`.
- `$lower.pred.int` a vector of lower prediction intervals per forecast point.
- `$upper.pred.int` a vector of upper prediction intervals per forecast point.

Note

- Typically, `(training.set = 0.8 * length(variable))` is used for optimization. Smaller samples could use `(training.set = 0.9 * length(variable))` (or larger) in order to preserve information.
- The number of combinations will grow prohibitively large, they should be kept as small as possible. `seasonal.factor` containing an element too large will result in an error. Please reduce the maximum `seasonal.factor`.
- Set `(ncores = 1)` if routine is used within a parallel architecture.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Nonlinear NNS.ARMA period optimization using 2 yearly lags on AirPassengers monthly data
## Not run:
nns.optims <- NNS.ARMA.optim(AirPassengers[1:132], training.set = 120,
seasonal.factor = seq(12, 24, 6))

## To predict out of sample using best parameters:
NNS.ARMA.optim(AirPassengers[1:132], h = 12, seasonal.factor = seq(12, 24, 6))

## Incorporate any objective function from external packages (such as \code{Metrics::mape})
NNS.ARMA.optim(AirPassengers[1:132], h = 12, seasonal.factor = seq(12, 24, 6),
obj.fn = expression(Metrics::mape(actual, predicted)), objective = "min")

## End(Not run)
```

NNS.boost

*NNS Boost***Description**

Ensemble method for classification using the NNS multivariate regression [NNS.reg](#) as the base learner instead of trees.

Usage

```
NNS.boost(
  IVs.train,
  DV.train,
  IVs.test = NULL,
  type = NULL,
  depth = NULL,
  learner.trials = 100,
  epochs = NULL,
  CV.size = NULL,
  balance = FALSE,
  ts.test = NULL,
  folds = 5,
  threshold = NULL,
  obj.fn = expression(sum((predicted - actual)^2)),
  objective = "min",
  extreme = FALSE,
  features.only = FALSE,
  feature.importance = TRUE,
  pred.int = NULL,
  status = TRUE
)
```

Arguments

IVs.train	a matrix or data frame of variables of numeric or factor data types.
DV.train	a numeric or factor vector with compatible dimensions to (IVs.train).
IVs.test	a matrix or data frame of variables of numeric or factor data types with compatible dimensions to (IVs.train). If NULL, will use (IVs.train) as default.
type	NULL (default). To perform a classification of discrete integer classes from factor target variable (DV.train) with a base category of 1, set to (type = "CLASS"), else for continuous (DV.train) set to (type = NULL).
depth	options: (integer, NULL, "max"); (depth = NULL)(default) Specifies the order parameter in the NNS.reg routine, assigning a number of splits in the regressors, analogous to tree depth.

<code>learner.trials</code>	integer; 100 (default) Sets the number of trials to obtain an accuracy threshold level. If the number of all possible feature combinations is less than selected value, the minimum of the two values will be used.
<code>epochs</code>	integer; <code>2*length(DV.train)</code> (default) Total number of feature combinations to run.
<code>CV.size</code>	numeric [0, 1]; NULL (default) Sets the cross-validation size. Defaults to a random value between 0.2 and 0.33 for a random sampling of the training set.
<code>balance</code>	logical; FALSE (default) Uses both up and down sampling to balance the classes. <code>type="CLASS"</code> required.
<code>ts.test</code>	integer; NULL (default) Sets the length of the test set for time-series data; typically <code>2*h</code> parameter value from NNS.ARMA or double known periods to forecast.
<code>folds</code>	integer; 5 (default) Sets the number of folds in the NNS.stack procedure for optimal <code>n.best</code> parameter.
<code>threshold</code>	numeric; NULL (default) Sets the <code>obj.fn</code> threshold to keep feature combinations.
<code>obj.fn</code>	expression; <code>expression(sum((predicted - actual)^2))</code> (default) Sum of squared errors is the default objective function. Any <code>expression(...)</code> using the specific terms <code>predicted</code> and <code>actual</code> can be used. Automatically selects an accuracy measure when <code>(type = "CLASS")</code> .
<code>objective</code>	options: ("min", "max") "max" (default) Select whether to minimize or maximize the objective function <code>obj.fn</code> .
<code>extreme</code>	logical; FALSE (default) Uses the maximum (minimum) threshold obtained from the <code>learner.trials</code> , rather than the upper (lower) quintile level for maximization (minimization) objective.
<code>features.only</code>	logical; FALSE (default) Returns only the final feature loadings along with the final feature frequencies.
<code>feature.importance</code>	logical; TRUE (default) Plots the frequency of features used in the final estimate.
<code>pred.int</code>	numeric [0,1]; NULL (default) Returns the associated prediction intervals for the final estimate.
<code>status</code>	logical; TRUE (default) Prints status update message in console.

Value

Returns a vector of fitted values for the dependent variable test set `$results`, prediction intervals `$pred.int`, and the final feature loadings `$feature.weights`, along with final feature frequencies `$feature.frequency`.

Note

- Like a logistic regression, the `(type = "CLASS")` setting is not necessary for target variable of two classes e.g. [0, 1]. The response variable base category should be 1 for classification problems.
- Incorporate any objective function from external packages (such as `Metrics::mape`) via `NNS.boost(..., obj.fn = expression(Metrics::mape(actual, predicted)), objective = "min")`

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. (2016) "Classification Using NNS Clustering Analysis" [doi:10.2139/ssrn.2864711](https://doi.org/10.2139/ssrn.2864711)

Examples

```
## Using 'iris' dataset where test set [IVs.test] is 'iris' rows 141:150.
## Not run:
a <- NNS.boost(iris[1:140, 1:4], iris[1:140, 5],
IVs.test = iris[141:150, 1:4],
epochs = 100, learner.trials = 100,
type = "CLASS", depth = NULL)

## Test accuracy
mean(a$results == as.numeric(iris[141:150, 5]))

## End(Not run)
```

NNS.caus	<i>NNS Causation</i>
----------	----------------------

Description

Returns the causality from observational data between two variables.

Usage

```
NNS.caus(x, y = NULL, factor.2.dummy = FALSE, tau = 0, plot = FALSE)
```

Arguments

x	a numeric vector, matrix or data frame.
y	NULL (default) or a numeric vector with compatible dimensions to x.
factor.2.dummy	logical; FALSE (default) Automatically augments variable matrix with numerical dummy variables based on the levels of factors. Includes dependent variable y.
tau	options: ("cs", "ts", integer); 0 (default) Number of lagged observations to consider (for time series data). Otherwise, set (tau = "cs") for cross-sectional data. (tau = "ts") automatically selects the lag of the time series data, while (tau = [integer]) specifies a time series lag.
plot	logical; FALSE (default) Plots the raw variables, tau normalized, and cross-normalized variables.

Value

Returns the directional causation ($x \longrightarrow y$) or ($y \longrightarrow x$) and net quantity of association. For causal matrix, directional causation is returned as ([column variable] $\longrightarrow$ [row variable]). Negative numbers represent causal direction attributed to [row variable].

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Not run:
## x causes y...
set.seed(123)
x <- rnorm(1000) ; y <- x ^ 2
NNS.caus(x, y, tau = "cs")

## Causal matrix without per factor causation
NNS.caus(iris, tau = 0)

## Causal matrix with per factor causation
NNS.caus(iris, factor.2.dummy = TRUE, tau = 0)

## End(Not run)
```

NNS.CDF

NNS CDF

Description

This function generates an empirical CDF using partial moment ratios [LPM.ratio](#), and resulting survival, hazard and cumulative hazard functions.

Usage

```
NNS.CDF(variable, degree = 0, target = NULL, type = "CDF", plot = TRUE)
```

Arguments

variable	a numeric vector or data.frame of 2 variables for joint CDF.
degree	integer; (degree = 0) (default) is frequency, (degree = 1) is area.
target	numeric; NULL (default) Must lie within support of each variable.

type	options("CDF", "survival", "hazard", "cumulative hazard"); "CDF" (default) Selects type of function to return for bi-variate analysis. Multivariate analysis is restricted to "CDF".
plot	logical; plots CDF.

Value

Returns:

- "Function" a data.table containing the observations and resulting CDF of the variable.
- "target.value" value from the target argument.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Viole, F. (2017) "Continuous CDFs and ANOVA with NNS" [doi:10.2139/ssrn.3007373](https://doi.org/10.2139/ssrn.3007373)

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100)
NNS.CDF(x)

## Empirical CDF (degree = 0)
NNS.CDF(x)

## Continuous CDF (degree = 1)
NNS.CDF(x, 1)

## Joint CDF
x <- rnorm(5000) ; y <- rnorm(5000)
A <- cbind(x,y)

NNS.CDF(A, 0)

## Joint CDF with target
NNS.CDF(A, 0, target = c(0,0))

## End(Not run)
```

Description

Determines higher dimension dependence coefficients based on co-partial moment matrices ratios.

Usage

```
NNS.copula(  
  X,  
  target = NULL,  
  continuous = TRUE,  
  plot = FALSE,  
  independence.overlay = FALSE  
)
```

Arguments

X	a numeric matrix or data frame.
target	numeric; Typically the mean of Variable X for classical statistics equivalences, but does not have to be. (Vectorized) (target = NULL) (default) will set the target as the mean of every variable.
continuous	logical; TRUE (default) Generates a continuous measure using degree 1 PM.matrix , while discrete FALSE uses degree 0 PM.matrix .
plot	logical; FALSE (default) Generates a 3d scatter plot with regression points.
independence.overlay	logical; FALSE (default) Creates and overlays independent Co.LPM and Co.UPM regions to visually reference the difference in dependence from the data.frame of variables being analyzed. Under independence, the light green and red shaded areas would be occupied by green and red data points respectively.

Value

Returns a multivariate dependence value [0,1].

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. (2016) "Beyond Correlation: Using the Elements of Variance for Conditional Means and Probabilities" [doi:10.2139/ssrn.2745308](https://doi.org/10.2139/ssrn.2745308).

Examples

```
## Not run:
set.seed(123)
x <- rnorm(1000) ; y <- rnorm(1000) ; z <- rnorm(1000)
A <- data.frame(x, y, z)
NNS.copula(A, target = colMeans(A), plot = TRUE, independence.overlay = TRUE)

### Target 0
NNS.copula(A, target = rep(0, ncol(A)), plot = TRUE, independence.overlay = TRUE)

## End(Not run)
```

NNS.dep

NNS Dependence

Description

Returns the dependence and nonlinear correlation between two variables based on higher order partial moment matrices measured by frequency or area.

Usage

```
NNS.dep(x, y = NULL, asym = FALSE, p.value = FALSE, print.map = FALSE)
```

Arguments

x	a numeric vector, matrix or data frame.
y	NULL (default) or a numeric vector with compatible dimensions to x.
asym	logical; FALSE (default) Allows for asymmetrical dependencies.
p.value	logical; FALSE (default) Generates 100 independent random permutations to test results against and plots 95 percent confidence intervals along with all results.
print.map	logical; FALSE (default) Plots quadrant means, or p-value replicates.

Value

Returns the bi-variate "Correlation" and "Dependence" or correlation / dependence matrix for matrix input.

Note

For asymmetrical (asym = TRUE) matrices, directional dependence is returned as ([column variable] —> [row variable]).

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
NNS.dep(x, y)

## Correlation / Dependence Matrix
x <- rnorm(100) ; y <- rnorm(100) ; z <- rnorm(100)
B <- cbind(x, y, z)
NNS.dep(B)

## End(Not run)
```

NNS.diff

NNS Numerical Differentiation

Description

Determines numerical derivative of a given univariate function using projected secant lines on the y-axis. These projected points infer finite steps h , in the finite step method.

Usage

```
NNS.diff(f, point, h = 0.1, tol = 1e-10, digits = 12, print.trace = FALSE)
```

Arguments

<code>f</code>	an expression or call or a formula with no lhs.
<code>point</code>	numeric; Point to be evaluated for derivative of a given function <code>f</code> .
<code>h</code>	numeric [0, ...]; Initial step for secant projection. Defaults to ($h = 0.1$).
<code>tol</code>	numeric; Sets the tolerance for the stopping condition of the inferred h . Defaults to ($tol = 1e-10$).
<code>digits</code>	numeric; Sets the number of digits specification of the output. Defaults to (<code>digits = 12</code>).
<code>print.trace</code>	logical; FALSE (default) Displays each iteration, lower y-intercept, upper y-intercept and inferred h .

Value

Returns a matrix of values, intercepts, derivatives, inferred step sizes for multiple methods of estimation.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Not run:
f <- function(x) sin(x) / x
NNS.diff(f, 4.1)

## End(Not run)
```

NNS.distance

NNS Distance

Description

Internal kernel function for NNS multivariate regression [NNS.reg](#) parallel instances.

Usage

```
NNS.distance(rpm, dist.estimate, k, class)
```

Arguments

rpm	REGRESSION.POINT.MATRIX from NNS.reg
dist.estimate	Vector to generate distances from.
k	n.best from NNS.reg
class	if classification problem.

Value

Returns sum of weighted distances.

NNS.FSD

*NNS FSD Test***Description**

Bi-directional test of first degree stochastic dominance using lower partial moments.

Usage

```
NNS.FSD(x, y, type = "discrete", plot = TRUE)
```

Arguments

x	a numeric vector.
y	a numeric vector.
type	options: ("discrete", "continuous"); "discrete" (default) selects the type of CDF.
plot	logical; TRUE (default) plots the FSD test.

Value

Returns one of the following FSD results: "X FSD Y", "Y FSD X", or "NO FSD EXISTS".

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2016) "LPM Density Functions for the Computation of the SD Efficient Set." Journal of Mathematical Finance, 6, 105-126. doi:[10.4236/jmf.2016.61012](https://doi.org/10.4236/jmf.2016.61012).

Viole, F. (2017) "A Note on Stochastic Dominance." doi:[10.2139/ssrn.3002675](https://doi.org/10.2139/ssrn.3002675).

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
NNS.FSD(x, y)

## End(Not run)
```

NNS.FSD.uni*NNS FSD Test uni-directional*

Description

Uni-directional test of first degree stochastic dominance using lower partial moments used in SD Efficient Set routine.

Usage

```
NNS.FSD.uni(x, y, type = "discrete")
```

Arguments

x	a numeric vector.
y	a numeric vector.
type	options: ("discrete", "continuous"); "discrete" (default) selects the type of CDF.

Value

Returns (1) if "X FSD Y", else (0).

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2016) "LPM Density Functions for the Computation of the SD Efficient Set." Journal of Mathematical Finance, 6, 105-126. [doi:10.4236/jmf.2016.61012](https://doi.org/10.4236/jmf.2016.61012)

Viole, F. (2017) "A Note on Stochastic Dominance." [doi:10.2139/ssrn.3002675](https://doi.org/10.2139/ssrn.3002675)

Examples

```
## Not run:  
set.seed(123)  
x <- rnorm(100) ; y <- rnorm(100)  
NNS.FSD.uni(x, y)  
  
## End(Not run)
```

NNS.gravity

NNS gravity

Description

Alternative central tendency measure more robust to outliers.

Usage

```
NNS.gravity(x, discrete = FALSE)
```

Arguments

`x` vector of data.
`discrete` logical; FALSE (default) for discrete distributions.

Value

Returns a numeric value representing the central tendency of the distribution.

Author(s)

Fred Viole, OVVO Financial Systems

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100)
NNS.gravity(x)

## End(Not run)
```

NNS.MC

NNS Monte Carlo Sampling

Description

Monte Carlo sampling from the maximum entropy bootstrap routine [NNS.meboot](#), ensuring the replicates are sampled from the full [-1,1] correlation space.

Usage

```

NNS.MC(
  x,
  reps = 30,
  lower_rho = -1,
  upper_rho = 1,
  by = 0.01,
  exp = 1,
  type = "spearman",
  drift = TRUE,
  target_drift = NULL,
  target_drift_scale = NULL,
  xmin = NULL,
  xmax = NULL,
  ...
)

```

Arguments

<code>x</code>	vector of data.
<code>reps</code>	numeric; number of replicates to generate, 30 default.
<code>lower_rho</code>	numeric [-1, 1]; .01 default will set the from argument in <code>seq(from, to, by)</code> .
<code>upper_rho</code>	numeric [-1, 1]; .01 default will set the to argument in <code>seq(from, to, by)</code> .
<code>by</code>	numeric; .01 default will set the by argument in <code>seq(-1, 1, step)</code> .
<code>exp</code>	numeric; 1 default will exponentially weight maximum rho value if <code>exp > 1</code> . Shrinks values towards <code>upper_rho</code> .
<code>type</code>	<code>options("spearman", "pearson", "NNScor", "NNSdep"); type = "spearman"</code> (default) dependence metric desired.
<code>drift</code>	logical; <code>drift = TRUE</code> (default) preserves the drift of the original series.
<code>target_drift</code>	numerical; <code>target_drift = NULL</code> (default) Specifies the desired drift when <code>drift = TRUE</code> , i.e. a risk-free rate of return.
<code>target_drift_scale</code>	numerical; instead of calculating a <code>target_drift</code> , provide a scalar to the existing drift when <code>drift = TRUE</code> .
<code>xmin</code>	numeric; the lower limit for the left tail.
<code>xmax</code>	numeric; the upper limit for the right tail.
<code>...</code>	possible additional arguments to be passed to NNS.meboot .

Value

- ensemble average observation over all replicates as a vector.
- replicates maximum entropy bootstrap replicates as a list for each rho.

References

Vinod, H.D. and Viole, F. (2020) Arbitrary Spearman's Rank Correlations in Maximum Entropy Bootstrap and Improved Monte Carlo Simulations. doi:[10.2139/ssrn.3621614](https://doi.org/10.2139/ssrn.3621614)

Examples

```
## Not run:
# To generate a set of MC sampled time-series to AirPassengers
MC_samples <- NNS.MC(AirPassengers, reps = 10, lower_rho = -1, upper_rho = 1, by = .5, xmin = 0)

## End(Not run)
```

NNS.meboot

NNS meboot

Description

Adapted maximum entropy bootstrap routine from meboot <https://cran.r-project.org/package=meboot>.

Usage

```
NNS.meboot(
  x,
  reps = 999,
  rho = NULL,
  type = "spearman",
  drift = TRUE,
  target_drift = NULL,
  target_drift_scale = NULL,
  trim = 0.1,
  xmin = NULL,
  xmax = NULL,
  reachbnd = TRUE,
  expand.sd = TRUE,
  force.clt = TRUE,
  scl.adjustment = FALSE,
  sym = FALSE,
  elaps = FALSE,
  digits = 6,
  colsubj,
  coldata,
  coltimes,
  ...
)
```

Arguments

<code>x</code>	vector of data.
<code>reps</code>	numeric; number of replicates to generate.
<code>rho</code>	numeric [-1,1] (vectorized); A rho must be provided, otherwise a blank list will be returned.
<code>type</code>	options("spearman", "pearson", "NNScor", "NNSdep"); <code>type = "spearman"</code> (default) dependence metric desired.
<code>drift</code>	logical; <code>drift = TRUE</code> (default) preserves the drift of the original series.
<code>target_drift</code>	numerical; <code>target_drift = NULL</code> (default) Specifies the desired drift when <code>drift = TRUE</code> , i.e. a risk-free rate of return.
<code>target_drift_scale</code>	numerical; instead of calculating a <code>target_drift</code> , provide a scalar to the existing drift when <code>drift = TRUE</code> .
<code>trim</code>	numeric [0,1]; The mean trimming proportion, defaults to <code>trim = 0.1</code> .
<code>xmin</code>	numeric; the lower limit for the left tail.
<code>xmax</code>	numeric; the upper limit for the right tail.
<code>reachbnd</code>	logical; If <code>TRUE</code> potentially reached bounds (<code>xmin = smallest value - trimmed mean</code> and <code>xmax = largest value + trimmed mean</code>) are given when the random draw happens to be equal to 0 and 1, respectively.
<code>expand.sd</code>	logical; If <code>TRUE</code> the standard deviation in the ensemble is expanded. See <code>expand.sd</code> in <code>meboot::meboot</code> .
<code>force.clt</code>	logical; If <code>TRUE</code> the ensemble is forced to satisfy the central limit theorem. See <code>force.clt</code> in <code>meboot::meboot</code> .
<code>scl.adjustment</code>	logical; If <code>TRUE</code> scale adjustment is performed to ensure that the population variance of the transformed series equals the variance of the data.
<code>sym</code>	logical; If <code>TRUE</code> an adjustment is performed to ensure that the ME density is symmetric.
<code>elaps</code>	logical; If <code>TRUE</code> elapsed time during computations is displayed.
<code>digits</code>	integer; 6 (default) number of digits to round output to.
<code>colsubj</code>	numeric; the column in <code>x</code> that contains the individual index. It is ignored if the input data <code>x</code> is not a <code>pdata.frame</code> object.
<code>coldata</code>	numeric; the column in <code>x</code> that contains the data of the variable to create the ensemble. It is ignored if the input data <code>x</code> is not a <code>pdata.frame</code> object.
<code>coltimes</code>	numeric; an optional argument indicating the column that contains the times at which the observations for each individual are observed. It is ignored if the input data <code>x</code> is not a <code>pdata.frame</code> object.
<code>...</code>	possible argument <code>fiv</code> to be passed to <code>expand.sd</code> .

Value

Returns the following row names in a matrix:

- `x` original data provided as input.

- replicates maximum entropy bootstrap replicates.
- ensemble average observation over all replicates.
- xx sorted order stats (xx[1] is minimum value).
- z class intervals limits.
- dv deviations of consecutive data values.
- dvtrim trimmed mean of dv.
- xmin data minimum for ensemble=xx[1]-dvtrim.
- xmax data x maximum for ensemble=xx[n]+dvtrim.
- desintxb desired interval means.
- ordxx ordered x values.
- kappa scale adjustment to the variance of ME density.
- elaps elapsed time.

Note

Vectorized rho and drift parameters will not vectorize both simultaneously. Also, do not specify `target_drift = NULL`.

References

- Vinod, H.D. and Viole, F. (2020) Arbitrary Spearman's Rank Correlations in Maximum Entropy Bootstrap and Improved Monte Carlo Simulations. [doi:10.2139/ssrn.3621614](https://doi.org/10.2139/ssrn.3621614)
- Vinod, H.D. (2013), Maximum Entropy Bootstrap Algorithm Enhancements. [doi:10.2139/ssrn.2285041](https://doi.org/10.2139/ssrn.2285041)
- Vinod, H.D. (2006), Maximum Entropy Ensembles for Time Series Inference in Economics, *Journal of Asian Economics*, **17**(6), pp. 955-978.
- Vinod, H.D. (2004), Ranking mutual funds using unconventional utility theory and stochastic dominance, *Journal of Empirical Finance*, **11**(3), pp. 353-377.

Examples

```
## Not run:
# To generate an orthogonal rank correlated time-series to AirPassengers
boots <- NNS.meboot(AirPassengers, reps = 100, rho = 0, xmin = 0)

# Verify correlation of replicates ensemble to original
cor(boots["ensemble",]$ensemble, AirPassengers, method = "spearman")

# Plot all replicates
matplot(boots["replicates",]$replicates, type = 'l')

# Plot ensemble
lines(boots["ensemble",]$ensemble, lwd = 3)

### Vectorized drift with a single rho
```

```

boots <- NNS.meboot(AirPassengers, reps = 10, rho = 0, xmin = 0, target_drift = c(1,7))
matplot(do.call(cbind, boots["replicates", ]), type = "l")
lines(1:length(AirPassengers), AirPassengers, lwd = 3, col = "red")

### Vectorized rho with a single target drift
boots <- NNS.meboot(AirPassengers, reps = 10, rho = c(0, .5, 1), xmin = 0, target_drift = 3)
matplot(do.call(cbind, boots["replicates", ]), type = "l")
lines(1:length(AirPassengers), AirPassengers, lwd = 3, col = "red")

### Vectorized rho with a single target drift scale
boots <- NNS.meboot(AirPassengers, reps = 10, rho = c(0, .5, 1), xmin = 0, target_drift_scale = 0.5)
matplot(do.call(cbind, boots["replicates", ]), type = "l")
lines(1:length(AirPassengers), AirPassengers, lwd = 3, col = "red")

## End(Not run)

```

NNS.mode

NNS mode

Description

Mode of a distribution, either continuous or discrete.

Usage

```
NNS.mode(x, discrete = FALSE, multi = TRUE)
```

Arguments

<code>x</code>	vector of data.
<code>discrete</code>	logical; FALSE (default) for discrete distributions.
<code>multi</code>	logical; TRUE (default) returns multiple mode values.

Value

Returns a numeric value representing the mode of the distribution.

Author(s)

Fred Viole, OVVO Financial Systems

Examples

```

## Not run:
set.seed(123)
x <- rnorm(100)
NNS.mode(x)

## End(Not run)

```

`NNS.moments`*NNS moments*

Description

This function returns the first 4 moments of the distribution.

Usage

```
NNS.moments(x, population = TRUE)
```

Arguments

<code>x</code>	a numeric vector.
<code>population</code>	logical; TRUE (default) Performs the population adjustment. Otherwise returns the sample statistic.

Value

Returns:

- `"$mean"` mean of the distribution.
- `"$variance"` variance of the distribution.
- `"$skewness"` skewness of the distribution.
- `"$kurtosis"` excess kurtosis of the distribution.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Not run:  
set.seed(123)  
x <- rnorm(100)  
NNS.moments(x)  
  
## End(Not run)
```

NNS.norm

*NNS Normalization***Description**

Normalizes a matrix of variables based on nonlinear scaling normalization method.

Usage

```
NNS.norm(X, linear = FALSE, chart.type = NULL, location = "topleft")
```

Arguments

X	a numeric matrix or data frame, or a list.
linear	logical; FALSE (default) Performs a linear scaling normalization, resulting in equal means for all variables.
chart.type	options: ("l", "b"); NULL (default). Set (chart.type = "l") for line, (chart.type = "b") for boxplot.
location	Sets the legend location within the plot, per the x and y co-ordinates used in base graphics legend .

Value

Returns a [data.frame](#) of normalized values.

Note

Unequal vectors provided in a list will only generate linear=TRUE normalized values.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
A <- cbind(x, y)
NNS.norm(A)

### Normalize list of unequal vector lengths
```

```

vec1 <- c(1, 2, 3, 4, 5, 6, 7)
vec2 <- c(10, 20, 30, 40, 50, 60)
vec3 <- c(0.5, 0.6, 0.7, 0.8, 0.9, 1.0, 1.1, 1.2, 1.3)

vec_list <- list(vec1, vec2, vec3)
NNS.norm(vec_list)

## End(Not run)

```

NNS.nowcast

NNS Nowcast

Description

Wrapper function for NNS nowcasting method using the nonparametric vector autoregression [NNS.VAR](#), and Federal Reserve Nowcasting variables.

Usage

```

NNS.nowcast(
  h = 1,
  additional.regressors = NULL,
  additional.sources = NULL,
  naive.weights = FALSE,
  specific.regressors = NULL,
  start.date = "2000-01-03",
  keep.data = FALSE,
  status = TRUE,
  ncores = NULL
)

```

Arguments

<code>h</code>	integer; (<code>h = 1</code>) (default) Number of periods to forecast. (<code>h = 0</code>) will return just the interpolated and extrapolated values up to the current month.
<code>additional.regressors</code>	character; NULL (default) add more regressors to the base model. The format must utilize the getSymbols format for FRED data, else specify the source.
<code>additional.sources</code>	character; NULL (default) specify the source argument per getSymbols for each <code>additional.regressors</code> specified.
<code>naive.weights</code>	logical; TRUE Equal weights applied to univariate and multivariate outputs in ensemble. FALSE (default) will apply weights based on the number of relevant variables detected.
<code>specific.regressors</code>	integer; NULL (default) Select individual regressors from the base model per Vi-ole (2020) listed in the Note below.

start.date	character; "2000-01-03" (default) Starting date for all data series download.
keep.data	logical; FALSE (default) Keeps downloaded variables in a new environment NNSdata.
status	logical; TRUE (default) Prints status update message in console.
ncores	integer; value specifying the number of cores to be used in the parallelized sub-routine NNS.ARMA.optim . If NULL (default), the number of cores to be used is equal to the number of cores of the machine - 1.

Value

Returns the following matrices of forecasted variables:

- "interpolated_and_extrapolated" Returns a data.frame of the linear interpolated and [NNS.ARMA](#) extrapolated values to replace NA values in the original variables argument. This is required for working with variables containing different frequencies, e.g. where NA would be reported for intra-quarterly data when indexed with monthly periods.
- "relevant_variables" Returns the relevant variables from the dimension reduction step.
- "univariate" Returns the univariate [NNS.ARMA](#) forecasts.
- "multivariate" Returns the multi-variate [NNS.reg](#) forecasts.
- "ensemble" Returns the ensemble of both "univariate" and "multivariate" forecasts.

Note

Specific regressors include:

1. PAYEMS – Payroll Employment
2. JTSJOL – Job Openings
3. CPIAUCSL – Consumer Price Index
4. DGORDER – Durable Goods Orders
5. RSAFS – Retail Sales
6. UNRATE – Unemployment Rate
7. HOUST – Housing Starts
8. INDPRO – Industrial Production
9. DSPIC96 – Personal Income
10. BOPTEXP – Exports
11. BOPTIMP – Imports
12. TTLCONS – Construction Spending
13. IR – Import Price Index
14. CPILFESL – Core Consumer Price Index
15. PCEPILFE – Core PCE Price Index
16. PCEPI – PCE Price Index
17. PERMIT – Building Permits
18. TCU – Capacity Utilization Rate

19. BUSINV – Business Inventories
20. ULCNFB – Unit Labor Cost
21. IQ – Export Price Index
22. GACDISA066MSFRBNY – Empire State Mfg Index
23. GACDFS066MSFRBPHI – Philadelphia Fed Mfg Index
24. PCEC96 – Real Consumption Spending
25. GDPC1 – Real Gross Domestic Product
26. ICSA – Weekly Unemployment Claims
27. DGS10 – 10-year Treasury rates
28. T10Y2Y – 2-10 year Treasury rate spread
29. WALCL – Total Assets
30. PALLFNFINDEXM – Global Price Index of All Commodities
31. FEDFUNDS – Federal Funds Effective Rate
32. PPIACO – Producer Price Index All Commodities
33. CIVPART – Labor Force Participation Rate
34. M2NS – M2 Money Supply

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Viole, F. (2019) "Multi-variate Time-Series Forecasting: Nonparametric Vector Autoregression Using NNS" [doi:10.2139/ssrn.3489550](https://doi.org/10.2139/ssrn.3489550)

Viole, F. (2020) "NOWCASTING with NNS" [doi:10.2139/ssrn.3589816](https://doi.org/10.2139/ssrn.3589816)

Examples

```
## Not run:
## Interpolates / Extrapolates all variables to current month
NNS.nowcast(h = 0)

## Additional regressors and sources specified
NNS.nowcast(h = 0, additional.regressors = c("SPY", "US0"),
            additional.sources = c("yahoo", "yahoo"))

### PREDICTION INTERVALS
## Store NNS.nowcast output
nns_estimates <- NNS.nowcast(h = 12)

# Create bootstrap replicates using NNS.meboot (GDP Variable)
```

```

gdp_replicates <- NNS.meboot(nns_estimates$ensemble$GDPC1,
                             rho = seq(0,1,.25),
                             reps = 100)["replicates",]

replicates <- do.call(cbind, gdp_replicates)

# Apply UPM.VaR and LPM.VaR for desired prediction interval...95 percent illustrated
# Tail percentage used in first argument per {LPM.VaR} and {UPM.VaR} functions
lower_GDP_CIs <- apply(replicates, 1, function(z) LPM.VaR(0.025, 0, z))
upper_GDP_CIs <- apply(replicates, 1, function(z) UPM.VaR(0.025, 0, z))

# View results
cbind(nns_estimates$ensemble$GDPC1, lower_GDP_CIs, upper_GDP_CIs)

## End(Not run)

```

NNS.part

NNS Partition Map

Description

Creates partitions based on partial moment quadrant centroids, iteratively assigning identifications to observations based on those quadrants (unsupervised partitional and hierarchial clustering method). Basis for correlation, dependence [NNS.dep](#), regression [NNS.reg](#) routines.

Usage

```

NNS.part(
  x,
  y,
  Voronoi = FALSE,
  type = NULL,
  order = NULL,
  obs.req = 8,
  min.obs.stop = TRUE,
  noise.reduction = "off"
)

```

Arguments

x	a numeric vector.
y	a numeric vector with compatible dimensions to x.
Voronoi	logical; FALSE (default) Displays a Voronoi type diagram using partial moment quadrants.
type	NULL (default) Controls the partitioning basis. Set to (type = "XONLY") for X-axis based partitioning. Defaults to NULL for both X and Y-axis partitioning.

order	integer; Number of partial moment quadrants to be generated. (order = "max") will institute a perfect fit.
obs.req	integer; (8 default) Required observations per cluster where quadrants will not be further partitioned if observations are not greater than the entered value. Reduces minimum number of necessary observations in a quadrant to 1 when (obs.req = 1).
min.obs.stop	logical; TRUE (default) Stopping condition where quadrants will not be further partitioned if a single cluster contains less than the entered value of obs.req.
noise.reduction	the method of determining regression points options for the dependent variable y: ("mean", "median", "mode", "off"); (noise.reduction = "mean") uses means for partitions. (noise.reduction = "median") uses medians instead of means for partitions, while (noise.reduction = "mode") uses modes instead of means for partitions. Defaults to (noise.reduction = "off") where an overall central tendency measure is used, which is the default for the independent variable x.

Value

Returns:

- "dt" a data.table of x and y observations with their partition assignment "quadrant" in the 3rd column and their prior partition assignment "prior.quadrant" in the 4th column.
- "regression.points" the data.table of regression points for that given (order = ...).
- "order" the order of the final partition given "min.obs.stop" stopping condition.

Note

min.obs.stop = FALSE will not generate regression points due to unequal partitioning of quadrants from individual cluster observations.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
NNS.part(x, y)

## Data.table of observations and partitions
NNS.part(x, y, order = 1)$dt
```

```
## Regression points
NNS.part(x, y, order = 1)$regression.points

## Voronoi style plot
NNS.part(x, y, Voronoi = TRUE)

## Examine final counts by quadrant
DT <- NNS.part(x, y)$dt
DT[, counts := .N, by = quadrant]
DT

## End(Not run)
```

NNS.reg

NNS Regression

Description

Generates a nonlinear regression based on partial moment quadrant means.

Usage

```
NNS.reg(
  x,
  y,
  factor.2.dummy = TRUE,
  order = NULL,
  stn = 0.95,
  dim.red.method = NULL,
  tau = NULL,
  type = NULL,
  point.est = NULL,
  location = "top",
  return.values = TRUE,
  plot = TRUE,
  plot.regions = FALSE,
  residual.plot = TRUE,
  confidence.interval = NULL,
  threshold = 0,
  n.best = NULL,
  noise.reduction = "off",
  dist = "L2",
  ncores = NULL,
  point.only = FALSE,
  multivariate.call = FALSE
)
```

Arguments

<code>x</code>	a vector, matrix or data frame of variables of numeric or factor data types.
<code>y</code>	a numeric or factor vector with compatible dimensions to <code>x</code> .
<code>factor.2.dummy</code>	logical; TRUE (default) Automatically augments variable matrix with numerical dummy variables based on the levels of factors.
<code>order</code>	integer; Controls the number of partial moment quadrant means. Users are encouraged to try different (<code>order = ...</code>) integer settings with (<code>noise.reduction = "off"</code>). (<code>order = "max"</code>) will force a limit condition perfect fit.
<code>stn</code>	numeric [0, 1]; Signal to noise parameter, sets the threshold of (<code>NNS.dep</code>) which reduces (" <code>order</code> ") when (<code>order = NULL</code>). Defaults to 0.95 to ensure high dependence for higher (" <code>order</code> ") and endpoint determination.
<code>dim.red.method</code>	options: (" <code>cor</code> ", " <code>NNS.dep</code> ", " <code>NNS.caus</code> ", " <code>all</code> ", " <code>equal</code> ", numeric vector, NULL) method for determining synthetic X^* coefficients. Selection of a method automatically engages the dimension reduction regression. The default is NULL for full multivariate regression. (<code>dim.red.method = "NNS.dep"</code>) uses NNS.dep for nonlinear dependence weights, while (<code>dim.red.method = "NNS.caus"</code>) uses NNS.caus for causal weights. (<code>dim.red.method = "cor"</code>) uses standard linear correlation for weights. (<code>dim.red.method = "all"</code>) averages all methods for further feature engineering. (<code>dim.red.method = "equal"</code>) uses unit weights. Alternatively, user can specify a numeric vector of coefficients.
<code>tau</code>	options(" <code>ts</code> ", NULL); NULL (default) To be used in conjunction with (<code>dim.red.method = "NNS.caus"</code>) or (<code>dim.red.method = "all"</code>). If the regression is using time-series data, set (<code>tau = "ts"</code>) for more accurate causal analysis.
<code>type</code>	NULL (default). To perform a classification, set to (<code>type = "CLASS"</code>). Like a logistic regression, it is not necessary for target variable of two classes e.g. [0, 1].
<code>point.est</code>	a numeric or factor vector with compatible dimensions to <code>x</code> . Returns the fitted value $\hat{y}$ for any value of <code>x</code> .
<code>location</code>	Sets the legend location within the plot, per the <code>x</code> and <code>y</code> co-ordinates used in base graphics legend .
<code>return.values</code>	logical; TRUE (default), set to FALSE in order to only display a regression plot and call values as needed.
<code>plot</code>	logical; TRUE (default) To plot regression.
<code>plot.regions</code>	logical; FALSE (default). Generates 3d regions associated with each regression point for multivariate regressions. Note, adds significant time to routine.
<code>residual.plot</code>	logical; TRUE (default) To plot $\hat{y}$ and Y .
<code>confidence.interval</code>	numeric [0, 1]; NULL (default) Plots the associated confidence interval with the estimate and reports the standard error for each individual segment. Also applies the same level for the prediction intervals.
<code>threshold</code>	numeric [0, 1]; (<code>threshold = 0</code>) (default) Sets the threshold for dimension reduction of independent variables when (<code>dim.red.method</code>) is not NULL.

<code>n.best</code>	integer; NULL (default) Sets the number of nearest regression points to use in weighting for multivariate regression at $\sqrt{\text{\# of regressors}}$. (<code>n.best = "all"</code>) will select and weight all generated regression points. Analogous to <code>k</code> in a <code>k</code> Nearest Neighbors algorithm. Different values of <code>n.best</code> are tested using cross-validation in NNS.stack .
<code>noise.reduction</code>	the method of determining regression points options: ("mean", "median", "mode", "off"); In low signal:noise situations, (<code>noise.reduction = "mean"</code>) uses means for NNS.dep restricted partitions, (<code>noise.reduction = "median"</code>) uses medians instead of means for NNS.dep restricted partitions, while (<code>noise.reduction = "mode"</code>) uses modes instead of means for NNS.dep restricted partitions. (<code>noise.reduction = "off"</code>) uses an overall central tendency measure for partitions.
<code>dist</code>	options:("L1", "L2", "FACTOR") the method of distance calculation; Selects the distance calculation used. <code>dist = "L2"</code> (default) selects the Euclidean distance and (<code>dist = "L1"</code>) selects the Manhattan distance; (<code>dist = "FACTOR"</code>) uses a frequency.
<code>ncores</code>	integer; value specifying the number of cores to be used in the parallelized procedure. If NULL (default), the number of cores to be used is equal to the number of cores of the machine - 1.
<code>point.only</code>	Internal argument for abbreviated output.
<code>multivariate.call</code>	Internal argument for multivariate regressions.

Value

UNIVARIATE REGRESSION RETURNS THE FOLLOWING VALUES:

- "R2" provides the goodness of fit;
- "SE" returns the overall standard error of the estimate between `y` and `y.hat`;
- "Prediction.Accuracy" returns the correct rounded "Point.est" used in classifications versus the categorical `y`;
- "derivative" for the coefficient of the `x` and its applicable range;
- "Point.est" for the predicted value generated;
- "pred.int" lower and upper prediction intervals for the "Point.est" returned using the "confidence.interval" provided;
- "regression.points" provides the points used in the regression equation for the given order of partitions;
- "Fitted.xy" returns a data.table of `x`, `y`, `y.hat`, `resid`, `NNS.ID`, `gradient`;

MULTIVARIATE REGRESSION RETURNS THE FOLLOWING VALUES:

- "R2" provides the goodness of fit;
- "equation" returns the numerator of the synthetic X^* dimension reduction equation as a data.table consisting of regressor and its coefficient. Denominator is simply the length of all coefficients > 0 , returned in last row of equation data.table.
- "x.star" returns the synthetic X^* as a vector;

- "rhs.partitions" returns the partition points for each regressor x;
- "RPM" provides the Regression Point Matrix, the points for each x used in the regression equation for the given order of partitions;
- "Point.est" returns the predicted value generated;
- "pred.int" lower and upper prediction intervals for the "Point.est" returned using the "confidence.interval" provided;
- "Fitted.xy" returns a data.table of x,y, y.hat, gradient, and NNS.ID.

Note

- Please ensure point.est is of compatible dimensions to x, error message will ensue if not compatible.
- Like a logistic regression, the (type = "CLASS") setting is not necessary for target variable of two classes e.g. [0, 1]. The response variable base category should be 1 for classification problems.
- For low signal:noise instances, increasing the dimension may yield better results using `NNS.stack(cbind(x, x), y, method = 1, ...)`.

Author(s)

Fred Viole, OVVO Financial Systems

References

- Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)
- Vinod, H. and Viole, F. (2017) "Nonparametric Regression Using Clusters" [doi:10.1007/s10614-01797135](https://doi.org/10.1007/s10614-01797135)
- Vinod, H. and Viole, F. (2018) "Clustering and Curve Fitting by Line Segments" [doi:10.20944/preprints201801.0090.v1](https://doi.org/10.20944/preprints201801.0090.v1)
- Viole, F. (2020) "Partitional Estimation Using Partial Moments" [doi:10.2139/ssrn.3592491](https://doi.org/10.2139/ssrn.3592491)

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
NNS.reg(x, y)

## Manual {order} selection
NNS.reg(x, y, order = 2)

## Maximum {order} selection
NNS.reg(x, y, order = "max")

## x-only partitioning (Univariate only)
NNS.reg(x, y, type = "XONLY")
```

```
## For Multiple Regression:
x <- cbind(rnorm(100), rnorm(100), rnorm(100)) ; y <- rnorm(100)
NNS.reg(x, y, point.est = c(.25, .5, .75))

## For Multiple Regression based on Synthetic X* (Dimension Reduction):
x <- cbind(rnorm(100), rnorm(100), rnorm(100)) ; y <- rnorm(100)
NNS.reg(x, y, point.est = c(.25, .5, .75), dim.red.method = "cor", ncores = 1)

## IRIS dataset examples:
# Dimension Reduction:
NNS.reg(iris[,1:4], iris[,5], dim.red.method = "cor", order = 5, ncores = 1)

# Dimension Reduction using causal weights:
NNS.reg(iris[,1:4], iris[,5], dim.red.method = "NNS.caus", order = 5, ncores = 1)

# Multiple Regression:
NNS.reg(iris[,1:4], iris[,5], order = 2, noise.reduction = "off")

# Classification:
NNS.reg(iris[,1:4], iris[,5], point.est = iris[1:10, 1:4], type = "CLASS")$Point.est

## To call fitted values:
x <- rnorm(100) ; y <- rnorm(100)
NNS.reg(x, y)$Fitted

## To call partial derivative (univariate regression only):
NNS.reg(x, y)$derivative

## End(Not run)
```

NNS.rescale

NNS rescale

Description

Rescale a vector using either min-max scaling or risk-neutral adjustment.

Usage

```
NNS.rescale(x, a, b, method = "minmax", T = NULL, type = "Terminal")
```

Arguments

x	numeric vector; data to rescale (e.g., terminal prices for risk-neutral method).
a	numeric; defines the scaling target: - For method = "minmax": the lower limit of the output range (e.g., 5 to scale to [5, b]). - For method = "riskneutral": the initial price $\backslash(S_0 \backslash)$ (must be positive, e.g., 100), used to set the target mean.

b	numeric; defines the scaling range or rate: - For method = "minmax": the upper limit of the output range (e.g., 10 to scale to [a, 10]). - For method = "riskneutral": the risk-free rate r (e.g., 0.05), used with T to adjust the mean.
method	character; scaling method: "minmax" (default) for min-max scaling, or "riskneutral" for risk-neutral adjustment.
T	numeric; time to maturity in years (required for method = "riskneutral", ignored otherwise; e.g., 1). Default is NULL.
type	character; for method = "riskneutral": "Terminal" (default) or "Discounted" (mean = S_0).

Value

Returns a rescaled distribution: - For "minmax": values scaled linearly to the range [a, b]. - For "riskneutral": values scaled multiplicatively to a risk-neutral mean ($S_0 e^{rT}$) if type = "Terminal", or S_0 if type = "Discounted".

Author(s)

Fred Viole, OVVO Financial Systems

Examples

```
## Not run:
set.seed(123)
# Min-max scaling: a = lower limit, b = upper limit
x <- rnorm(100)
NNS.rescale(x, a = 5, b = 10, method = "minmax") # Scales to [5, 10]

# Risk-neutral scaling (Terminal): a = S_0, b = r # Mean approx 105.13
prices <- 100 * exp(cumsum(rnorm(100, 0.001, 0.02)))
NNS.rescale(prices, a = 100, b = 0.05, method = "riskneutral", T = 1, type = "Terminal")

# Risk-neutral scaling (Discounted): a = S_0, b = r # Mean approx 100
NNS.rescale(prices, a = 100, b = 0.05, method = "riskneutral", T = 1, type = "Discounted")

## End(Not run)
```

NNS.SD.cluster

NNS SD-based Clustering

Description

Clusters a set of variables by iteratively extracting Stochastic Dominance (SD)-efficient sets, subject to a minimum cluster size.

Usage

```
NNS.SD.cluster(  
  data,  
  degree = 1,  
  type = "discrete",  
  min_cluster = 1,  
  dendrogram = FALSE  
)
```

Arguments

data	A numeric matrix or data frame of variables to be clustered.
degree	Numeric options: (1, 2, 3). Degree of stochastic dominance test.
type	Character, either "discrete" (default) or "continuous"; specifies the type of CDF.
min_cluster	Integer. The minimum number of elements required for a valid cluster.
dendrogram	Logical; FALSE (default). If TRUE, a dendrogram is produced based on a simple "distance" measure between clusters.

Details

The function applies [NNS.SD.efficient.set](#) iteratively, peeling off the SD-efficient set at each step if it meets or exceeds `min_cluster` in size, until no more subsets can be extracted or all variables are exhausted. Variables in each SD-efficient set form a cluster, with any remaining variables aggregated into the final cluster if it meets the `min_cluster` threshold.

Value

A list with the following components:

- Clusters: A named list of cluster memberships where each element is the set of variable names belonging to that cluster.
- Dendrogram (optional): If `dendrogram = TRUE`, an `hclust` object is also returned.

Author(s)

Fred Viole, OVVO Financial Systems

References

- Viole, F. and Nawrocki, D. (2016) "LPM Density Functions for the Computation of the SD Efficient Set." *Journal of Mathematical Finance*, 6, 105-126. doi:[10.4236/jmf.2016.61012](https://doi.org/10.4236/jmf.2016.61012).
- Viole, F. (2017) "A Note on Stochastic Dominance." doi:[10.2139/ssrn.3002675](https://doi.org/10.2139/ssrn.3002675)

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100)
y <- rnorm(100)
z <- rnorm(100)
A <- cbind(x, y, z)

# Perform SD-based clustering (degree 1), requiring at least 2 elements per cluster
results <- NNS.SD.cluster(data = A, degree = 1, min_cluster = 2)
print(results$Clusters)

# Produce a dendrogram as well
results_with_dendro <- NNS.SD.cluster(data = A, degree = 1, min_cluster = 2, dendrogram = TRUE)

## End(Not run)
```

NNS.SD.efficient.set *NNS SD Efficient Set*

Description

Determines the set of stochastic dominant variables for various degrees.

Usage

```
NNS.SD.efficient.set(x, degree, type = "discrete", status = TRUE)
```

Arguments

x	a numeric matrix or data frame.
degree	numeric options: (1, 2, 3); Degree of stochastic dominance test from (1, 2 or 3).
type	options: ("discrete", "continuous"); "discrete" (default) selects the type of CDF.
status	logical; TRUE (default) Prints status update message in console.

Value

Returns set of stochastic dominant variable names.

Author(s)

Fred Viole, OVVO Financial Systems

References

- Viole, F. and Nawrocki, D. (2016) "LPM Density Functions for the Computation of the SD Efficient Set." *Journal of Mathematical Finance*, 6, 105-126. doi:[10.4236/jmf.2016.61012](https://doi.org/10.4236/jmf.2016.61012).
- Viole, F. (2017) "A Note on Stochastic Dominance." doi:[10.2139/ssrn.3002675](https://doi.org/10.2139/ssrn.3002675)

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y<-rnorm(100) ; z<-rnorm(100)
A <- cbind(x, y, z)
NNS.SD.efficient.set(A, 1)

## End(Not run)
```

NNS.seas

NNS Seasonality Test

Description

Seasonality test based on the coefficient of variation for the variable and lagged component series.
A result of 1 signifies no seasonality present.

Usage

```
NNS.seas(variable, modulo = NULL, mod.only = TRUE, plot = TRUE)
```

Arguments

variable	a numeric vector.
modulo	integer(s); NULL (default) Used to find the nearest multiple(s) in the reported seasonal period.
mod.only	logical; TRUE (default) Limits the number of seasonal periods returned to the specified modulo.
plot	logical; TRUE (default) Returns the plot of all periods exhibiting seasonality and the variable level reference.

Value

Returns a matrix of all periods exhibiting less coefficient of variation than the variable with "all.periods"; and the single period exhibiting the least coefficient of variation versus the variable with "best.period"; as well as a vector of "periods" for easy call into [NNS.ARMA.optim](#). If no seasonality is detected, NNS.seas will return ("No Seasonality Detected").

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100)

## To call strongest period based on coefficient of variation:
NNS.seas(x, plot = FALSE)$best.period

## Using modulus for logical seasonal inference:
NNS.seas(x, modulo = c(2,3,5,7), plot = FALSE)

## End(Not run)
```

NNS.SSD

NNS SSD Test

Description

Bi-directional test of second degree stochastic dominance using lower partial moments.

Usage

```
NNS.SSD(x, y, plot = TRUE)
```

Arguments

x	a numeric vector.
y	a numeric vector.
plot	logical; TRUE (default) plots the SSD test.

Value

Returns one of the following SSD results: "X SSD Y", "Y SSD X", or "NO SSD EXISTS".

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2016) "LPM Density Functions for the Computation of the SD Efficient Set." Journal of Mathematical Finance, 6, 105-126. doi:[10.4236/jmf.2016.61012](https://doi.org/10.4236/jmf.2016.61012).

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
NNS.SSD(x, y)

## End(Not run)
```

NNS.SSD.uni

NNS SSD Test uni-directional

Description

Uni-directional test of second degree stochastic dominance using lower partial moments used in SD Efficient Set routine.

Usage

```
NNS.SSD.uni(x, y)
```

Arguments

x a numeric vector.
y a numeric vector.

Value

Returns (1) if "X SSD Y", else (0).

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2016) "LPM Density Functions for the Computation of the SD Efficient Set." Journal of Mathematical Finance, 6, 105-126. doi:[10.4236/jmf.2016.61012](https://doi.org/10.4236/jmf.2016.61012).

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
NNS.SSD.uni(x, y)

## End(Not run)
```

NNS.stack

NNS Stack

Description

Prediction model using the predictions of the NNS base models [NNS.reg](#) as features (i.e. meta-features) for the stacked model.

Usage

```
NNS.stack(
  IVs.train,
  DV.train,
  IVs.test = NULL,
  type = NULL,
  obj.fn = expression(sum((predicted - actual)^2)),
  objective = "min",
  optimize.threshold = TRUE,
  dist = "L2",
  CV.size = NULL,
  balance = FALSE,
  ts.test = NULL,
  folds = 5,
  order = NULL,
  norm = NULL,
  method = c(1, 2),
  stack = TRUE,
  dim.red.method = "cor",
  pred.int = NULL,
  status = TRUE,
  ncores = NULL
)
```

Arguments

IVs.train	a vector, matrix or data frame of variables of numeric or factor data types.
DV.train	a numeric or factor vector with compatible dimensions to (IVs.train).
IVs.test	a vector, matrix or data frame of variables of numeric or factor data types with compatible dimensions to (IVs.train). If NULL, will use (IVs.train) as default.
type	NULL (default). To perform a classification of discrete integer classes from factor target variable (DV.train) with a base category of 1, set to (type = "CLASS"), else for continuous (DV.train) set to (type = NULL). Like a logistic regression, this setting is not necessary for target variable of two classes e.g. [0, 1].
obj.fn	expression; expression(sum((predicted - actual)^2)) (default) Sum of squared errors is the default objective function. Any expression() using the specific terms predicted and actual can be used.

objective	options: ("min", "max") "min" (default) Select whether to minimize or maximize the objective function obj.fn.
optimize.threshold	logical; TRUE (default) Will optimize the probability threshold value for rounding in classification problems. If FALSE, returns 0.5.
dist	options:("L1", "L2", "DTW", "FACTOR") the method of distance calculation; Selects the distance calculation used. dist = "L2" (default) selects the Euclidean distance and (dist = "L1") selects the Manhattan distance; (dist = "DTW") selects the dynamic time warping distance; (dist = "FACTOR") uses a frequency.
CV.size	numeric [0, 1]; NULL (default) Sets the cross-validation size if (IVs.test = NULL). Defaults to a random value between 0.2 and 0.33 for a random sampling of the training set.
balance	logical; FALSE (default) Uses both up and down sampling to balance the classes. type="CLASS" required.
ts.test	integer; NULL (default) Sets the length of the test set for time-series data; typically 2*h parameter value from NNS.ARMA or double known periods to forecast.
folds	integer; folds = 5 (default) Select the number of cross-validation folds.
order	options: (integer, "max", NULL); NULL (default) Sets the order for NNS.reg , where (order = "max") is the k-nearest neighbors equivalent, which is suggested for mixed continuous and discrete (unordered, ordered) data.
norm	options: ("std", "NNS", NULL); NULL (default) 3 settings offered: NULL, "std", and "NNS". Selects the norm parameter in NNS.reg .
method	numeric options: (1, 2); Select the NNS method to include in stack. (method = 1) selects NNS.reg ; (method = 2) selects NNS.reg dimension reduction regression. Defaults to method = c(1, 2), which will reduce the dimension first, then find the optimal n.best.
stack	logical; TRUE (default) Uses dimension reduction output in n.best optimization, otherwise performs both analyses independently.
dim.red.method	options: ("cor", "NNS.dep", "NNS.caus", "equal", "all") method for determining synthetic X* coefficients. (dim.red.method = "cor") uses standard linear correlation for weights. (dim.red.method = "NNS.dep") (default) uses NNS.dep for nonlinear dependence weights, while (dim.red.method = "NNS.caus") uses NNS.caus for causal weights. (dim.red.method = "all") averages all methods for further feature engineering.
pred.int	numeric [0,1]; NULL (default) Returns the associated prediction intervals with each method.
status	logical; TRUE (default) Prints status update message in console.
ncores	integer; value specifying the number of cores to be used in the parallelized subroutine NNS.reg . If NULL (default), the number of cores to be used is equal to the number of cores of the machine - 1.

Value

Returns a vector of fitted values for the dependent variable test set for all models.

- "NNS.reg.n.best" returns the optimum "n.best" parameter for the [NNS.reg](#) multivariate regression. "SSE.reg" returns the SSE for the [NNS.reg](#) multivariate regression.
- "OBJfn.reg" returns the obj.fn for the [NNS.reg](#) regression.
- "NNS.dim.red.threshold" returns the optimum "threshold" from the [NNS.reg](#) dimension reduction regression.
- "OBJfn.dim.red" returns the obj.fn for the [NNS.reg](#) dimension reduction regression.
- "probability.threshold" returns the optimum probability threshold for classification, else 0.5 when set to FALSE.
- "reg" returns [NNS.reg](#) output.
- "reg.pred.int" returns the prediction intervals for the regression output.
- "dim.red" returns [NNS.reg](#) dimension reduction regression output.
- "dim.red.pred.int" returns the prediction intervals for the dimension reduction regression output.
- "stack" returns the output of the stacked model.
- "pred.int" returns the prediction intervals for the stacked model.

Note

- Incorporate any objective function from external packages (such as `Metrics::mape`) via `NNS.stack(..., obj.fn = expression(Metrics::mape(actual, predicted)), objective = "min")`
- Like a logistic regression, the `(type = "CLASS")` setting is not necessary for target variable of two classes e.g. [0, 1]. The response variable base category should be 1 for multiple class problems.
- Missing data should be handled prior as well using [na.omit](#) or [complete.cases](#) on the full dataset.

If error received:

```
"Error in is.data.frame(x) : object 'RP' not found"
```

reduce the CV.size.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. (2016) "Classification Using NNS Clustering Analysis" [doi:10.2139/ssrn.2864711](https://doi.org/10.2139/ssrn.2864711)

Examples

```
## Using 'iris' dataset where test set [IVs.test] is 'iris' rows 141:150.
## Not run:
NNS.stack(iris[1:140, 1:4], iris[1:140, 5], IVs.test = iris[141:150, 1:4], type = "CLASS")

## Using 'iris' dataset to determine [n.best] and [threshold] with no test set.
NNS.stack(iris[, 1:4], iris[, 5], type = "CLASS")

## Selecting NNS.reg and dimension reduction techniques.
NNS.stack(iris[1:140, 1:4], iris[1:140, 5], iris[141:150, 1:4], method = c(1, 2), type = "CLASS")

## End(Not run)
```

NNS.term.matrix

NNS Term Matrix

Description

Generates a term matrix for text classification use in [NNS.reg](#).

Usage

```
NNS.term.matrix(x, oos = NULL)
```

Arguments

x	mixed data.frame; character/numeric; A two column dataset should be used. Concatenate text from original sources to comply with format. Also note the possibility of factors in "DV", so "as.numeric(as.character(...))" is used to avoid issues.
oos	mixed data.frame; character/numeric; Out-of-sample text dataset to be classified.

Value

Returns the text as independent variables "IV" and the classification as the dependent variable "DV". Out-of-sample independent variables are returned with "OOS".

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
## Not run:
x <- data.frame(cbind(c("sunny", "rainy"), c(1, -1)))
NNS.term.matrix(x)

### Concatenate Text with space separator, cbind with "DV"
x <- data.frame(cbind(c("sunny", "rainy"), c("windy", "cloudy"), c(1, -1)))
x <- data.frame(cbind(paste(x[, 1], x[, 2], sep = " "), as.numeric(as.character(x[, 3]))))
NNS.term.matrix(x)

### NYT Example
require(RTextTools)
data(NYTimes)

### Concatenate Columns 3 and 4 containing text, with column 5 as DV
NYT <- data.frame(cbind(paste(NYTimes[, 3], NYTimes[, 4], sep = " "),
                          as.numeric(as.character(NYTimes[, 5]))))
NNS.term.matrix(NYT)

## End(Not run)
```

NNS.TSD

NNS TSD Test

Description

Bi-directional test of third degree stochastic dominance using lower partial moments.

Usage

```
NNS.TSD(x, y, plot = TRUE)
```

Arguments

<code>x</code>	a numeric vector.
<code>y</code>	a numeric vector.
<code>plot</code>	logical; TRUE (default) plots the TSD test.

Value

Returns one of the following TSD results: "X TSD Y", "Y TSD X", or "NO TSD EXISTS".

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2016) "LPM Density Functions for the Computation of the SD Efficient Set." Journal of Mathematical Finance, 6, 105-126. doi:[10.4236/jmf.2016.61012](https://doi.org/10.4236/jmf.2016.61012).

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
NNS.TSD(x, y)

## End(Not run)
```

NNS.TSD.uni

NNS TSD Test uni-directional

Description

Uni-directional test of third degree stochastic dominance using lower partial moments used in SD Efficient Set routine.

Usage

```
NNS.TSD.uni(x, y)
```

Arguments

x	a numeric vector.
y	a numeric vector.

Value

Returns (1) if "X TSD Y", else (0).

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2016) "LPM Density Functions for the Computation of the SD Efficient Set." Journal of Mathematical Finance, 6, 105-126. doi:[10.4236/jmf.2016.61012](https://doi.org/10.4236/jmf.2016.61012).

Examples

```
## Not run:
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100)
NNS.TSD.uni(x, y)

## End(Not run)
```

NNS.VAR

*NNS VAR***Description**

Nonparametric vector autoregressive model incorporating [NNS.ARMA](#) estimates of variables into [NNS.reg](#) for a multi-variate time-series forecast.

Usage

```
NNS.VAR(
  variables,
  h,
  tau = 1,
  dim.red.method = "cor",
  naive.weights = TRUE,
  obj.fn = expression(mean((predicted - actual)^2)/(NNS::Co.LPM(1, predicted, actual,
    target_x = mean(predicted), target_y = mean(actual)) + NNS::Co.UPM(1, predicted,
    actual, target_x = mean(predicted), target_y = mean(actual)))),
  objective = "min",
  status = TRUE,
  ncores = NULL,
  nowcast = FALSE
)
```

Arguments

<code>variables</code>	a numeric matrix or data.frame of contemporaneous time-series to forecast.
<code>h</code>	integer; 1 (default) Number of periods to forecast. (<code>h = 0</code>) will return just the interpolated and extrapolated values.
<code>tau</code>	positive integer [> 0]; 1 (default) Number of lagged observations to consider for the time-series data. Vector for single lag for each respective variable or list for multiple lags per each variable.
<code>dim.red.method</code>	options: ("cor", "NNS.dep", "NNS.caus", "all") method for reducing regressors via NNS.stack . (<code>dim.red.method = "cor"</code>) (default) uses standard linear correlation for dimension reduction in the lagged variable matrix. (<code>dim.red.method = "NNS.dep"</code>) uses NNS.dep for nonlinear dependence weights, while (<code>dim.red.method = "NNS.caus"</code>) uses NNS.caus for causal weights. (<code>dim.red.method = "all"</code>) averages all methods for further feature engineering.

<code>naive.weights</code>	logical; TRUE (default) Equal weights applied to univariate and multivariate outputs in ensemble. FALSE will apply weights based on the number of relevant variables detected.
<code>obj.fn</code>	expression; <code>expression(mean((predicted - actual)^2)) / (Sum of NNS Co-partial moments)</code> (default) MSE / co-movements is the default objective function. Any <code>expression(...)</code> using the specific terms <code>predicted</code> and <code>actual</code> can be used.
<code>objective</code>	options: ("min", "max") "min" (default) Select whether to minimize or maximize the objective function <code>obj.fn</code> .
<code>status</code>	logical; TRUE (default) Prints status update message in console.
<code>ncores</code>	integer; value specifying the number of cores to be used in the parallelized subroutine NNS.ARMA.optim . If NULL (default), the number of cores to be used is equal to the number of cores of the machine - 1.
<code>nowcast</code>	logical; FALSE (default) internal call for NNS.nowcast .

Value

Returns the following matrices of forecasted variables:

- `"interpolated_and_extrapolated"` Returns a `data.frame` of the linear interpolated and [NNS.ARMA](#) extrapolated values to replace NA values in the original variables argument. This is required for working with variables containing different frequencies, e.g. where NA would be reported for intra-quarterly data when indexed with monthly periods.
- `"relevant_variables"` Returns the relevant variables from the dimension reduction step.
- `"univariate"` Returns the univariate [NNS.ARMA](#) forecasts.
- `"multivariate"` Returns the multi-variate [NNS.reg](#) forecasts.
- `"ensemble"` Returns the ensemble of both `"univariate"` and `"multivariate"` forecasts.

Note

- `"Error in { : task xx failed -}"` should be re-run with `NNS.VAR(..., ncores = 1)`.
- Not recommended for factor variables, even after transformed to numeric. [NNS.reg](#) is better suited for factor or binary regressor extrapolation.

Author(s)

Fred Viole, OVVO Financial Systems

References

- Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)
- Viole, F. (2019) "Multi-variate Time-Series Forecasting: Nonparametric Vector Autoregression Using NNS" [doi:10.2139/ssrn.3489550](#)
- Viole, F. (2020) "NOWCASTING with NNS" [doi:10.2139/ssrn.3589816](#)
- Viole, F. (2019) "Forecasting Using NNS" [doi:10.2139/ssrn.3382300](#)

Vinod, H. and Viole, F. (2017) "Nonparametric Regression Using Clusters" [doi:10.1007/s10614-01797135](https://doi.org/10.1007/s10614-01797135)

Vinod, H. and Viole, F. (2018) "Clustering and Curve Fitting by Line Segments" [doi:10.20944/preprints201801.0090.v1](https://doi.org/10.20944/preprints201801.0090.v1)

Examples

```
## Not run:
#####
### Standard Nonparametric Vector Autoregression ###
#####

set.seed(123)
x <- rnorm(100) ; y <- rnorm(100) ; z <- rnorm(100)
A <- cbind(x = x, y = y, z = z)

### Using lags 1:4 for each variable
NNS.VAR(A, h = 12, tau = 4, status = TRUE)

### Using lag 1 for variable 1, lag 3 for variable 2 and lag 3 for variable 3
NNS.VAR(A, h = 12, tau = c(1,3,3), status = TRUE)

### Using lags c(1,2,3) for variables 1 and 3, while using lags c(4,5,6) for variable 2
NNS.VAR(A, h = 12, tau = list(c(1,2,3), c(4,5,6), c(1,2,3)), status = TRUE)

### PREDICTION INTERVALS
# Store NNS.VAR output
nns_estimate <- NNS.VAR(A, h = 12, tau = 4, status = TRUE)

# Create bootstrap replicates using NNS.meboot
replicates <- NNS.meboot(nns_estimate$ensemble[,1], rho = seq(-1,1,.25))["replicates",]
replicates <- do.call(cbind, replicates)

# Apply UPM.VaR and LPM.VaR for desired prediction interval...95 percent illustrated
# Tail percentage used in first argument per {LPM.VaR} and {UPM.VaR} functions
lower_CIs <- apply(replicates, 1, function(z) LPM.VaR(0.025, 0, z))
upper_CIs <- apply(replicates, 1, function(z) UPM.VaR(0.025, 0, z))

# View results
cbind(nns_estimate$ensemble[,1], lower_CIs, upper_CIs)

#####
### NOWCASTING with Mixed Frequencies ###
#####

library(Quandl)
econ_variables <- Quandl(c("FRED/GDPC1", "FRED/UNRATE", "FRED/CPIAUCSL"), type = 'ts',
                        order = "asc", collapse = "monthly", start_date = "2000-01-01")

### Note the missing values that need to be imputed
head(econ_variables)
```

```
tail(econ_variables)

NNS.VAR(econ_variables, h = 12, tau = 12, status = TRUE)

## End(Not run)
```

PM.matrix

Partial Moment Matrix

Description

This function generates a co-partial moment matrix for the specified co-partial moment.

Usage

```
PM.matrix(LPM_degree, UPM_degree, target, variable, pop_adj)
```

Arguments

LPM_degree	integer; Degree for variable below target deviations. (LPM_degree = 0) is frequency, (LPM_degree = 1) is area.
UPM_degree	integer; Degree for variable above target deviations. (UPM_degree = 0) is frequency, (UPM_degree = 1) is area.
target	numeric; Typically the mean of Variable X for classical statistics equivalences, but does not have to be. (Vectorized) (target = NULL) (default) will set the target as the mean of every variable.
variable	a numeric matrix or data.frame.
pop_adj	logical; TRUE Adjusts the population co-partial moment matrices for sample statistics, which is default in base R. Use FALSE for degree 0 frequency matrices. Must be provided by user.

Value

Matrix of partial moment quadrant values (CUPM, DUPM, DLPM, CLPM), and overall covariance matrix. Uncalled quadrants will return a matrix of zeros.

Note

For divergent asymmetrical "D.LPM" and "D.UPM" matrices, matrix is D.LPM(column, row, ...).

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Viole, F. (2017) "Bayes' Theorem From Partial Moments" [doi:10.2139/ssrn.3457377](https://doi.org/10.2139/ssrn.3457377)

Examples

```
set.seed(123)
x <- rnorm(100) ; y <- rnorm(100) ; z <- rnorm(100)
A <- cbind(x,y,z)
PM.matrix(LPM_degree = 1, UPM_degree = 1, variable = A, target = colMeans(A), pop_adj = TRUE)

## Use of vectorized numeric targets (target_x, target_y, target_z)
PM.matrix(LPM_degree = 1, UPM_degree = 1, target = c(0, 0.15, .25), variable = A, pop_adj = TRUE)

## Calling Individual Partial Moment Quadrants
cov.mtx <- PM.matrix(LPM_degree = 1, UPM_degree = 1, variable = A, target = colMeans(A),
                     pop_adj = TRUE)
cov.mtx$cupm

## Full covariance matrix
cov.mtx$cov.matrix
```

UPM

Upper Partial Moment

Description

This function generates a univariate upper partial moment for any degree or target.

Usage

```
UPM(degree, target, variable, excess_ret = FALSE)
```

Arguments

degree	integer; (degree = 0) is frequency, (degree = 1) is area.
target	numeric; Set to target = mean(variable) for classical equivalences, but does not have to be. (Vectorized)@param variable a numeric vector. data.frame or list type objects are not permissible.
variable	a numeric vector. data.frame or list type objects are not permissible.
excess_ret	Logical; FALSE (default)

Value

UPM of variable

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
set.seed(123)
x <- rnorm(100)
UPM(0, mean(x), x)
```

UPM.ratio

Upper Partial Moment RATIO

Description

This function generates a standardized univariate upper partial moment for any degree or target.

Usage

```
UPM.ratio(degree, target, variable)
```

Arguments

degree	integer; (degree = 0) is frequency, (degree = 1) is area.
target	numeric; Typically set to mean, but does not have to be. (Vectorized)
variable	a numeric vector.

Value

Standardized UPM of variable

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```

set.seed(123)
x <- rnorm(100)
UPM.ratio(0, mean(x), x)

## Joint Upper CDF
## Not run:
x <- rnorm(5000) ; y <- rnorm(5000)
plot3d(x, y, Co.UPM(0, sort(x), sort(y), x, y), col = "blue", xlab = "X", ylab = "Y",
zlab = "Probability", box = FALSE)

## End(Not run)

```

UPM.VaR

*UPM VaR***Description**

Generates an upside value at risk (VaR) quantile based on the Upper Partial Moment ratio

Usage

```
UPM.VaR(percentile, degree, x)
```

Arguments

percentile	numeric [0, 1]; The percentile for right-tail VaR (vectorized).
degree	integer; (degree = 0) for discrete distributions, (degree = 1) for continuous distributions.
x	a numeric vector.

Value

Returns a numeric value representing the point at which "percentile" of the area of x is above.

Author(s)

Fred Viole, OVVO Financial Systems

References

Viole, F. and Nawrocki, D. (2013) "Nonlinear Nonparametric Statistics: Using Partial Moments" (ISBN: 1490523995)

Examples

```
set.seed(123)
x <- rnorm(100)

## For 5th percentile, right-tail
UPM.VaR(0.05, 0, x)
```

Index

Co.LPM, [3](#), [25](#)
Co.UPM, [4](#), [25](#)
complete.cases, [57](#)

D.LPM, [5](#)
D.UPM, [6](#)
data.frame, [3–6](#), [10](#), [38](#), [65](#)
dy.d_, [8](#)
dy.dx, [7](#)

getSymbols, [39](#)

legend, [38](#), [45](#)
list, [3–6](#), [10](#), [65](#)
LPM, [10](#)
LPM.ratio, [11](#), [23](#)
LPM.VaR, [12](#)

na.omit, [57](#)
NNS.ANOVA, [13](#)
NNS.ARMA, [15](#), [17–19](#), [21](#), [40](#), [56](#), [61](#), [62](#)
NNS.ARMA.optim, [17](#), [40](#), [52](#), [62](#)
NNS.boost, [20](#)
NNS.caus, [22](#), [45](#), [56](#), [61](#)
NNS.CDF, [23](#)
NNS.copula, [25](#)
NNS.dep, [26](#), [42](#), [45](#), [46](#), [56](#), [61](#)
NNS.diff, [27](#)
NNS.distance, [28](#)
NNS.FSD, [29](#)
NNS.FSD.uni, [30](#)
NNS.gravity, [31](#)
NNS.MC, [31](#)
NNS.meboot, [16](#), [18](#), [31](#), [32](#), [33](#)
NNS.mode, [36](#)
NNS.moments, [37](#)
NNS.norm, [38](#)
NNS.nowcast, [39](#), [62](#)
NNS.part, [42](#)
NNS.reg, [8](#), [19](#), [20](#), [28](#), [40](#), [42](#), [44](#), [55–58](#), [61](#),
[62](#)

NNS.rescale, [48](#)
NNS.SD.cluster, [49](#)
NNS.SD.efficient.set, [50](#), [51](#)
NNS.seas, [16](#), [52](#)
NNS.SSD, [53](#)
NNS.SSD.uni, [54](#)
NNS.stack, [21](#), [46](#), [55](#), [61](#)
NNS.term.matrix, [58](#)
NNS.TSD, [59](#)
NNS.TSD.uni, [60](#)
NNS.VAR, [39](#), [61](#)

PM.matrix, [25](#), [64](#)

UPM, [65](#)
UPM.ratio, [66](#)
UPM.VaR, [67](#)