

Package ‘betaregscale’

August 23, 2026

Type Package

Title Beta Regression for Interval-Censored Scale-Derived Outcomes

Version 2.7.4

Maintainer José Evandeilton Lopes <evandeilton@gmail.com>

Description Maximum-likelihood estimation of beta regression models for responses derived from bounded rating scales. Observations are treated as interval-censored on (0, 1) after a scale-to-unit transformation, and the likelihood is built from the difference of the beta CDF at the interval endpoints. The complete likelihood supports mixed censoring types: uncensored, left-censored, right-censored, and interval-censored observations. Both fixed- and variable-dispersion submodels are supported, with flexible link functions for the mean and precision components. A compiled C++ backend (via 'Rcpp' and 'RcppArmadillo') provides numerically stable, high-performance log-likelihood evaluation. Standard S3 methods (print(), summary(), coef(), fitted(), residuals(), predict(), plot(), confint(), vcov(), logLik(), AIC(), BIC()) are available for fitted objects.

License MIT + file LICENSE

URL <https://evandeilton.github.io/betaregscale/>,
<https://github.com/evandeilton/betaregscale>

BugReports <https://github.com/evandeilton/betaregscale/issues>

Depends R (>= 4.1.0)

Imports Formula, ggplot2, numDeriv, Rcpp (>= 1.0.12), rlang, stats

Suggests gridExtra, knitr, MASS, rmarkdown, testthat (>= 3.0.0)

LinkingTo Rcpp, RcppArmadillo, RcppEigen

VignetteBuilder knitr

Encoding UTF-8

NeedsCompilation yes

RoxygenNote 7.3.3

Config/testthat/edition 3

Author José Evandeilton Lopes [aut, cre] (ORCID:
<https://orcid.org/0009-0007-5887-4084>),
 Wagner Hugo Bonat [aut] (ORCID:
<https://orcid.org/0000-0002-0349-7054>)

Repository CRAN

Date/Publication 2026-08-23 18:00:02 UTC

Contents

AIC.brs	3
AIC.brsmm	4
anova.brs	5
anova.brsmm	6
autoplot.brs	7
autoplot.brsmm	9
autoplot.brs_bootstrap	11
autoplot.brs_marginaleffects	12
BIC.brs	14
BIC.brsmm	15
brs	16
brsmm	17
brsmm_re_study	20
brs_bootstrap	21
brs_cens	22
brs_check	24
brs_coef	27
brs_cv	28
brs_est	29
brs_gof	31
brs_hessian	32
brs_marginaleffects	33
brs_predict_scoreprob	35
brs_prep	36
brs_repar	40
brs_sim	41
brs_table	43
coef.brs	44
coef.brsmm	45
confint.brs	46
confint.brsmm	47
fitted.brs	48
fitted.brsmm	49
formula.brs	50
formula.brsmm	51
logLik.brs	52
logLik.brsmm	53

model.matrix.brs	54
model.matrix.brsmm	55
nobs.brs	56
nobs.brsmm	57
plot.brs	58
plot.brsmm	59
predict.brs	61
predict.brsmm	62
print.brs	63
print.brsmm	64
print.brsmm_re_study	65
print.summary.brs	66
print.summary.brsmm	67
ranef	68
ranef.brsmm	69
residuals.brs	70
residuals.brsmm	71
summary.brs	72
summary.brsmm	73
vcov.brs	74
vcov.brsmm	75
Index	76

AIC.brs

*Akaike information criterion***Description**

Akaike information criterion

Usage

```
## S3 method for class 'brs'
AIC(object, ..., k = 2)
```

Arguments

object	A fitted "betaregscale" object.
...	Ignored.
k	Penalty per parameter (default 2).

Value

Scalar AIC value.

See Also

[brs](#), [logLik.brs](#), [BIC.brs](#), [brs_gof](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
AIC(fit)
```

AIC.brsmm	<i>AIC for brsmm models</i>
-----------	-----------------------------

Description

AIC for brsmm models

Usage

```
## S3 method for class 'brsmm'
AIC(object, ..., k = 2)
```

Arguments

- object A fitted "brsmm" object.
- ... Currently ignored.
- k Numeric penalty per parameter.

Value

Numeric scalar.

See Also

[brsmm](#), [logLik.brsmm](#), [BIC.brsmm](#), [brs_gof](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
AIC(fit)
```

anova.brs

Model comparison by analysis of deviance (LR test) for ‘brs’

Description

Model comparison by analysis of deviance (LR test) for ‘brs’

Usage

```
## S3 method for class 'brs'
anova(object, ..., test = c("Chisq", "none"))
```

Arguments

object	A fitted "brs" model.
...	Additional fitted "brs" and/or "brsmm" models to compare.
test	Character; "Chisq" (default) or "none".

Value

An object of class "anova" and "data.frame" with model-wise log-likelihood, information criteria, and (optionally) LR test columns.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master’s dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Ferrari, S. L. P., and Cribari-Neto, F. (2004). Beta regression for modelling rates and proportions. *Journal of Applied Statistics*, **31**(7), 799–815. doi:[10.1080/0266476042000214501](https://doi.org/10.1080/0266476042000214501)

See Also

[brs](#), [logLik.brs](#), [AIC.brs](#), [BIC.brs](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  x2 = rep(c(0, 0, 1, 1), 5)
)
prep <- brs_prep(dat, ncuts = 100)
m1 <- brs(y ~ 1, data = prep)
m2 <- brs(y ~ x1, data = prep)
m3 <- brs(y ~ x1 + x2, data = prep)
anova(m1, m2, m3)
```

anova.brsmm

Model comparison by analysis of deviance (LR test) for 'brsmm'

Description

Model comparison by analysis of deviance (LR test) for 'brsmm'

Usage

```
## S3 method for class 'brsmm'
anova(object, ..., test = c("Chisq", "none"))
```

Arguments

object	A fitted "brsmm" model.
...	Additional fitted "brsmm" and/or "brs" models to compare.
test	Character; "Chisq" (default) or "none".

Value

An object of class "anova" and "data.frame" with model-wise log-likelihood, information criteria, and (optionally) LR test columns.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Ferrari, S. L. P., and Cribari-Neto, F. (2004). Beta regression for modelling rates and proportions. *Journal of Applied Statistics*, **31**(7), 799–815. doi:[10.1080/0266476042000214501](https://doi.org/10.1080/0266476042000214501)

See Also

[brsmm](#), [logLik.brsmm](#), [AIC.brsmm](#), [BIC.brsmm](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
m1 <- brs(y ~ 1, data = prep)
m2 <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
anova(m1, m2)
```

autoplot.brs

ggplot2 autoplot for brs models

Description

Produces ggplot2 diagnostics tailored to interval-censored scale models.

Usage

```
## S3 method for class 'brs'
autoplot(
  object,
  type = c("calibration", "score_dist", "cdf", "residuals_by_delta", "all"),
  bins = 10L,
  scores = NULL,
  newdata = NULL,
  n_grid = 200L,
  max_curves = 6L,
  residual_type = "rqr",
  title = NULL,
  xlab = NULL,
  ylab = NULL,
  ncol = 2L,
  theme = ggplot2::theme_minimal(),
  ...
)
```

Arguments

object	A fitted "brs" object.
type	Plot type: "calibration", "score_dist", "cdf", "residuals_by_delta", or "all" (produces all panels in a single grid).
bins	Number of bins for "calibration".
scores	Optional integer vector of scores for "score_dist". Defaults to all scores from 0 to ncuts.
newdata	Optional data frame of covariate scenarios for "cdf".
n_grid	Number of points on (0, 1) used to draw CDF curves.
max_curves	Maximum number of CDF curves shown when newdata is not provided.
residual_type	Residual type for "residuals_by_delta"; passed to residuals.brs .
title	Optional character: override the plot title via <code>ggplot2::labs(title = ...)</code> . Ignored when type = "all".
xlab	Optional character: override the x-axis label. Ignored when type = "all".
ylab	Optional character: override the y-axis label. Ignored when type = "all".
ncol	Number of columns for the grid when type = "all". Defaults to 2.
theme	A ggplot2 theme object (e.g., <code>ggplot2::theme_bw()</code>) or a theme function. Applied to every panel. Defaults to <code>ggplot2::theme_minimal()</code> .
...	Additional arguments forwarded to <code>ggplot2::theme()</code> and applied on top of theme. Use named theme element arguments, e.g. <code>legend.position = "none"</code> .

Details

type = "calibration" bins predictions and compares mean observed vs mean predicted response in each bin.

type = "score_dist" compares observed score frequencies against expected frequencies implied by the fitted beta interval model.

Value

A ggplot2 object.

References

- Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.
- Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:[10.1002/acr.20543](https://doi.org/10.1002/acr.20543)
- Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:[10.1016/j.jpainsymman.2010.08.016](https://doi.org/10.1016/j.jpainsymman.2010.08.016)

See Also

[brs](#), [plot.brs](#), [autoplot.brs_bootstrap](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  x2 = rep(c(0, 0, 1, 1), 5)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1 + x2, data = prep)
ggplot2::autoplot(fit, type = "calibration")
ggplot2::autoplot(fit,
  type = "calibration",
  title = "My calibration", ylab = "Observed"
)
ggplot2::autoplot(fit, type = "all")
```

autoplot.brsmm

ggplot2 autoplot for brsmm models

Description

Produces ggplot2 diagnostics tailored to mixed beta interval models.

Usage

```
## S3 method for class 'brsmm'
autoplot(
  object,
  type = c("calibration", "score_dist", "ranef_qq", "residuals_by_group",
    "ranef_caterpillar", "ranef_density", "ranef_pairs", "shrinkage", "all"),
  bins = 10L,
  scores = NULL,
  residual_type = c("response", "pearson"),
  max_groups = 25L,
  title = NULL,
  xlab = NULL,
  ylab = NULL,
  ncol = 2L,
  theme = ggplot2::theme_minimal(),
  ...
)
```

Arguments

<code>object</code>	A fitted "brsmm" object.
<code>type</code>	Plot type. One of "calibration", "score_dist", "ranef_qq", "residuals_by_group", "ranef_caterpillar", "ranef_density", "ranef_pairs", "shrinkage", or "all" (produces all panels in a single grid).
<code>bins</code>	Number of bins for "calibration".
<code>scores</code>	Optional integer vector of scores for "score_dist". Defaults to all scores from 0 to ncuts.
<code>residual_type</code>	Residual type for "residuals_by_group"; passed to <code>residuals.brsmm</code> .
<code>max_groups</code>	Maximum groups in "residuals_by_group".
<code>title</code>	Optional character: override the plot title via <code>ggplot2::labs(title = ...)</code> . Ignored when <code>type = "all"</code> .
<code>xlab</code>	Optional character: override the x-axis label. Ignored when <code>type = "all"</code> .
<code>ylab</code>	Optional character: override the y-axis label. Ignored when <code>type = "all"</code> .
<code>ncol</code>	Number of columns for the grid when <code>type = "all"</code> . Defaults to 2.
<code>theme</code>	A ggplot2 theme object (e.g., <code>ggplot2::theme_bw()</code>) or a theme function. Applied to every panel. Defaults to <code>ggplot2::theme_minimal()</code> .
<code>...</code>	Additional arguments forwarded to <code>ggplot2::theme()</code> and applied on top of theme. Use named theme element arguments, e.g. <code>legend.position = "none"</code> .

Value

A ggplot2 object, or (when `type = "all"`) invisibly returns the list of all panels after rendering the grid.

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit_mm <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
ggplot2::autoplot(fit_mm, type = "calibration", bins = 4)
ggplot2::autoplot(fit_mm,
  type = "ranef_caterpillar",
  title = "My title", ylab = "Mode"
)
ggplot2::autoplot(fit_mm, type = "all")

```

```
autoplot.brs_bootstrap
      ggplot2 autoplot for bootstrap results
```

Description

Produces visual summaries for objects returned by [brs_bootstrap](#).

Usage

```
## S3 method for class 'brs_bootstrap'
autoplot(
  object,
  type = c("ci_forest", "dist", "qq", "stability"),
  parameter = NULL,
  title = NULL,
  caption = NULL,
  max_parameters = 12L,
  ci_level = NULL,
  theme = NULL,
  ...
)
```

Arguments

<code>object</code>	An object of class "brs_bootstrap".
<code>type</code>	Plot type: "ci_forest", "dist", "qq", or "stability".
<code>parameter</code>	Optional parameter name used by type = "dist", "qq", and "stability". If NULL, the first parameter is used.
<code>title</code>	Optional plot title override.
<code>caption</code>	Optional subtitles/titles for plot types. Accepts: • a single string (used for the selected type); • a character vector/list with up to four entries in the order ci_forest, dist, qq, stability.
<code>max_parameters</code>	Maximum number of parameters shown in type = "ci_forest".
<code>ci_level</code>	Confidence level used in type = "stability". Defaults to the level stored in object.
<code>theme</code>	Optional ggplot2 theme object (e.g., <code>ggplot2::theme_bw()</code>). If NULL, <code>ggplot2::theme_minimal()</code> is used.
<code>...</code>	Currently ignored.

Details

For type = "dist", "qq", and "stability", bootstrap draws must be present in `attr(object, "boot_draws")`, obtained by fitting with `brs_bootstrap(..., keep_draws = TRUE)`.

Value

A ggplot2 object.

See Also

[brs_bootstrap](#), [brs](#), [autoplot.brs](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
boot <- brs_bootstrap(fit, R = 50)
ggplot2::autoplot(boot, type = "ci_forest")
```

`autoplot.brs_marginaleffects`

ggplot2 autoplot for marginal effects

Description

Produces visual summaries for objects returned by [brs_marginaleffects](#).

Usage

```
## S3 method for class 'brs_marginaleffects'
autoplot(
  object,
  type = c("forest", "magnitude", "dist"),
  variable = NULL,
  top_n = 12L,
  title = NULL,
  caption = NULL,
  theme = NULL,
  ...
)
```

Arguments

object	An object of class "brs_marginaleffects".
type	Plot type: "forest", "magnitude", or "dist".
variable	Optional variable name for type = "dist".
top_n	Maximum number of variables shown in "magnitude" (ordered by AME).
title	Optional plot title override.
caption	Optional subtitle override.
theme	Optional ggplot2 theme object. If NULL, ggplot2::theme_minimal() is used.
...	Currently ignored.

Details

type = "dist" requires AME simulation draws stored in attr(object, "ame_draws"), which are available when marginal effects are computed with keep_draws = TRUE and interval = TRUE.

Value

A ggplot2 object.

See Also

[brs_marginaleffects](#), [brs](#), [autoplot.brs](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
ame <- brs_marginaleffects(fit)
ggplot2::autoplot(ame, type = "forest")
```

BIC.ars	<i>Bayesian information criterion</i>
---------	---------------------------------------

Description

Bayesian information criterion

Usage

```
## S3 method for class 'ars'  
BIC(object, ...)
```

Arguments

object	A fitted "betaregscale" object.
...	Ignored.

Value

Scalar BIC value.

See Also

[ars](#), [logLik.ars](#), [AIC.ars](#), [ars_gof](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10)  
)  
prep <- ars_prep(dat, ncuts = 100)  
fit <- ars(y ~ x1, data = prep)  
BIC(fit)
```

BIC.brsmm	<i>BIC for brsmm models</i>
-----------	-----------------------------

Description

BIC for brsmm models

Usage

```
## S3 method for class 'brsmm'  
BIC(object, ...)
```

Arguments

object	A fitted "brsmm" object.
...	Currently ignored.

Value

Numeric scalar.

See Also

[brsmm](#), [logLik.brsmm](#), [AIC.brsmm](#), [brs_gof](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10),  
  id = factor(rep(1:4, each = 5))  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)  
BIC(fit)
```

brs

*Fit a beta interval regression model***Description**

Unified interface that dispatches to `brs_fit_fixed` (fixed dispersion) or `brs_fit_var` (variable dispersion) based on the formula structure.

Usage

```
brs(
  formula,
  data,
  link = "logit",
  link_phi = "logit",
  ncuts = 100L,
  lim = 0.5,
  reparam = 2L,
  method = c("BFGS", "L-BFGS-B"),
  hessian_method = c("numDeriv", "optim")
)
```

Arguments

<code>formula</code>	A Formula -style formula with two parts: $y \sim x_1 + x_2 \mid z_1 + z_2$.
<code>data</code>	Data frame.
<code>link</code>	Mean link function (default "logit").
<code>link_phi</code>	Dispersion link function (default "logit").
<code>ncuts</code>	Number of scale categories (default 100).
<code>lim</code>	Uncertainty half-width (default 0.5).
<code>reparam</code>	Reparameterization scheme (default 2).
<code>method</code>	Optimization method (default "BFGS").
<code>hessian_method</code>	Character: "numDeriv" or "optim".

Details

If the formula contains a `|` separator (e.g., $y \sim x_1 + x_2 \mid z_1$), the variable-dispersion model is fitted; otherwise, a fixed-dispersion model is used.

Value

An object of class "brs".

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:[10.1002/acr.20543](https://doi.org/10.1002/acr.20543)

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:[10.1016/j.jpainsymman.2010.08.016](https://doi.org/10.1016/j.jpainsymman.2010.08.016)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  x2 = rep(c(0, 0, 1, 1), 5)
)
prep <- brs_prep(dat, ncuts = 100)
# Fixed dispersion
fit1 <- brs(y ~ x1, data = prep)
print(fit1)
# Variable dispersion
fit2 <- brs(y ~ x1 | x2, data = prep)
print(fit2)
```

brsmm

Fit a mixed-effects beta interval regression model

Description

Fits a beta interval-censored mixed model with Gaussian random intercepts/slopes using marginal maximum likelihood. The implementation supports random-effects formulas such as $\sim 1 \mid \text{group}$ and $\sim 1 + x \mid \text{group}$, and offers three integration methods for the random effects: Laplace approximation, Adaptive Gauss-Hermite Quadrature (AGHQ), and Quasi-Monte Carlo (QMC).

Usage

```
brsmm(
  formula,
  random = ~1 | id,
  data,
  link = "logit",
  link_phi = "logit",
  reparam = 2L,
  ncuts = 100L,
  lim = 0.5,
  int_method = c("laplace", "aghq", "qmc"),
  n_points = 11L,
  qmc_points = 1024L,
  start = NULL,
  method = c("BFGS", "L-BFGS-B"),
  hessian_method = c("numDeriv", "optim"),
  control = list(maxit = 2000L)
)
```

Arguments

formula	Model formula. Supports one- or two-part formulas: $y \sim x_1 + x_2$ or $y \sim x_1 + x_2 \mid z_1 + z_2$.
random	Random-effects specification of the form $\sim \text{terms} \mid \text{group}$, e.g. $\sim 1 \mid \text{id}$ or $\sim 1 + x \mid \text{id}$.
data	Data frame.
link	Mean link function.
link_phi	Precision link function.
reparam	Beta reparameterization code (0, 1, 2).
ncuts	Number of categories on the original scale.
lim	Half-width used to construct interval endpoints.
int_method	Integration method: "laplace" (default), "aghq", or "qmc".
n_points	Number of quadrature points for <code>int_method="aghq"</code> . Ignored for other methods. Default is 11.
qmc_points	Number of QMC points for <code>int_method="qmc"</code> . Default is 1024.
start	Optional numeric vector of starting values (beta, gamma, and packed lower-Cholesky random parameters).
method	Optimizer passed to optim .
hessian_method	"numDeriv" (default) or "optim".
control	Control list for optim .

Details

The conditional contribution for each observation follows the same mixed censoring likelihood used by [brs](#):

1. $\delta = 0$: exact contribution via beta density,
2. $\delta = 1$: left-censored contribution via beta CDF,
3. $\delta = 2$: right-censored contribution via survival CDF,
4. $\delta = 3$: interval contribution via CDF difference.

For group i , the random-effects vector $\mathbf{b}_i \sim N(\mathbf{0}, D)$ is integrated out numerically.

- "laplace": Uses a second-order Laplace approximation at the conditional mode. Fast and generally accurate for n_i large.
- "aghq": Adaptive Gauss-Hermite Quadrature. Uses `n_points` quadrature nodes centered and scaled by the conditional mode and curvature. More accurate than Laplace, especially for small n_i .
- "qmc": Quasi-Monte Carlo integration using a Halton sequence. Uses `qmc_points` evaluation points. Suitable for high-dimensional integration (future proofing) or checking robustness.

Value

An object of class "brsmm".

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Ferrari, S. L. P., and Cribari-Neto, F. (2004). Beta regression for modelling rates and proportions. *Journal of Applied Statistics*, **31**(7), 799–815. doi:[10.1080/0266476042000214501](https://doi.org/10.1080/0266476042000214501)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit_mm <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
fit_mm
```

brsmm_re_study	<i>Random-effects study for brsmm models</i>
----------------	--

Description

Provides a compact numeric study of random effects, including: estimated covariance matrix, correlation matrix, per-term standard deviations, empirical mean/SD of posterior modes, shrinkage ratio, and a normality check by Shapiro-Wilk (when applicable).

Usage

```
brsmm_re_study(object, ...)
```

Arguments

object	A fitted "brsmm" object.
...	Currently ignored.

Value

A list with class "brsmm_re_study".

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Ferrari, S. L. P., and Cribari-Neto, F. (2004). Beta regression for modelling rates and proportions. *Journal of Applied Statistics*, **31**(7), 799–815. doi:[10.1080/0266476042000214501](https://doi.org/10.1080/0266476042000214501)

See Also

[brsmm](#), [ranef.brsmm](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
rs <- brsmm_re_study(fit)
print(rs)
rs$summary
```

brs_bootstrap

*Parametric bootstrap confidence intervals for brs models***Description**

Computes bootstrap-based confidence intervals for the parameters of a fitted "brs" model by repeatedly simulating data from the fitted model and re-estimating parameters. Only "brs" (fixed or variable-dispersion) objects are supported; "brsmm" is not supported.

Usage

```
brs_bootstrap(
  object,
  R = 199L,
  level = 0.95,
  ci_type = c("percentile", "basic", "normal", "bca"),
  max_tries = NULL,
  keep_draws = FALSE
)

## S3 method for class 'brs_bootstrap'
print(x, ...)
```

Arguments

object	A fitted "brs" object (fixed or variable dispersion).
R	Integer: number of bootstrap replicates (default 199).
level	Numeric: confidence level (default 0.95).
ci_type	Character: type of confidence interval. One of "percentile" (default), "basic", "normal", or "bca". See the section on the cost of "bca" below.
max_tries	Optional integer: maximum number of bootstrap attempts to obtain converged replicates. If NULL, uses $\max(3 * R, 50)$.
keep_draws	Logical: if TRUE, stores successful bootstrap parameter draws in attribute "boot_draws".
x	Object returned by brs_bootstrap.
...	Ignored.

Details

For each replicate, data are simulated via [brs_sim](#) using the estimated coefficients (on the link scale) and the original design. The model is then re-fitted with [brs](#). Replicates that fail to converge are discarded; if the number of successful replicates is too low, a warning is issued. Intervals are the empirical quantiles of the bootstrap distribution of each parameter.

Value

A data frame with columns `parameter`, `estimate` (original point estimate), `se_boot` (bootstrap standard error), `ci_lower`, `ci_upper`, `mcse_lower`, `mcse_upper`, `wald_lower`, `wald_upper`, and `level`. The attribute `"n_success"` gives the number of replicates that converged. Additional attributes include `"R"`, `"n_attempted"`, `"ci_type"`, and optionally `"boot_draws"`.

Methods (by generic)

- `print(brs_bootstrap)`: Print method for bootstrap results

Cost of `ci_type = "bca"`

The bias-corrected and accelerated interval needs an acceleration constant, which is obtained here by a leave-one-out jackknife. That requires n additional model fits, one per observation, on top of the R bootstrap replicates: the total is $R + n$ fits rather than R . The cost is therefore driven by the sample size, not by R , and grows quickly – for $n = 1000$ the jackknife alone dominates the run time by an order of magnitude. The other three interval types need only the R replicates. Prefer `"percentile"` or `"basic"` for exploratory work on large samples, and reserve `"bca"` for a final result.

See Also

[confint.brs](#) for Wald intervals; [brs_sim](#) for simulation; [brs](#) for fitting.

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  x2 = rep(c(0, 0, 1, 1), 5)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
boot <- brs_bootstrap(fit, R = 50, level = 0.95)
print(boot)
```

Description

Produces a visual summary of the censoring structure in a fitted "brs" model or a response matrix produced by [brs_check](#). The summary includes:

1. Bar chart of censoring type counts
2. Histogram of midpoint responses colored by censoring type
3. Interval plot showing $[l_i, u_i]$ segments
4. Proportion table of censoring types

Usage

```
brs_cens(
  object,
  n_sample = 100L,
  which = 1:4,
  caption = NULL,
  gg = FALSE,
  title = "Censoring diagnostic overview",
  sub.caption = NULL,
  theme = NULL,
  palette = NULL,
  inform = FALSE,
  ...
)
```

Arguments

object	A fitted "brs" object, a matrix returned by brs_check , or a data frame returned by brs_prep (must contain columns left, right, yt, and delta).
n_sample	Integer: maximum number of observations to show in the interval plot (default 100). If the data has more observations, a random sample is drawn.
which	Integer vector selecting which panels to draw (default 1:4).
caption	Optional panel captions. Accepts a character vector (or list coercible to character) with up to 4 labels, in the order: burden, midpoint-by-type, width-by-type, ordered interval map.
gg	Logical: use ggplot2? (default FALSE).
title	Optional global title for the plotting page.
sub.caption	Optional subtitle/caption for the plotting page.
theme	Optional ggplot2 theme object (e.g., <code>ggplot2::theme_bw()</code>). If NULL, a minimal theme is used when <code>gg = TRUE</code> .
palette	Optional named character vector with colors for censoring types Exact, Left, Right, and Interval.
inform	Logical; if TRUE, prints brief interpretation messages about boundary and interval censoring intensity.
...	Further arguments (currently ignored).

Value

Invisibly returns a data frame with censoring counts and proportions, percentages, and interpretation flags.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:[10.1002/acr.20543](https://doi.org/10.1002/acr.20543)

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:[10.1016/j.jpainsymman.2010.08.016](https://doi.org/10.1016/j.jpainsymman.2010.08.016)

Examples

```
y <- c(0, 3, 5, 7, 10)
Y <- brs_check(y, ncuts = 10)
brs_cens(Y)

prep <- brs_prep(data.frame(y = y), ncuts = 10)
brs_cens(prepare)
```

brs_check

Transform and validate a scale-derived response variable

Description

Takes a discrete (or continuous) response on the scale $0, 1, \dots, K$ (where $K = \text{ncuts}$) and converts it to a pair of interval endpoints on the open unit interval $(0, 1)$. Each observation is classified into one of four censoring types following the complete likelihood used in this package:

$\delta = 0$ Uncensored (exact): the observation is a continuous value already in $(0, 1)$. The likelihood contribution is the density $f(y_i|\theta)$. Endpoints: $l_i = u_i = y_i$ (or y_i/K when on the scale).

$\delta = 1$ Left-censored: the latent value is below some upper bound u_i . The contribution is $F(u_i|\theta)$. When the observation is at the scale minimum ($y = 0$), the upper bound is $u_i = \lim/K$. When the user forces $\delta = 1$ on a non-boundary observation ($y \neq 0$), the upper bound is $u_i = (y + \lim)/K$, preserving observation-specific variation. In both cases $l_i = \epsilon$.

$\delta = 2$ Right-censored: the latent value is above some lower bound l_i . The contribution is $1 - F(l_i|\theta)$. When the observation is at the scale maximum ($y = K$), the lower bound is $l_i = (K - \text{lim})/K$. When the user forces $\delta = 2$ on a non-boundary observation ($y \neq K$), the lower bound is $l_i = (y - \text{lim})/K$, preserving observation-specific variation. In both cases $u_i = 1 - \epsilon$.

$\delta = 3$ Interval-censored: the standard case for scale data. The contribution is $F(u_i|\theta) - F(l_i|\theta)$ with midpoint interval endpoints $[(y - \text{lim})/K, (y + \text{lim})/K]$.

Usage

```
brs_check(y, ncuts = 100L, lim = 0.5, delta = NULL)
```

Arguments

y	Numeric vector: the raw response. Can be either integer scores on the scale $\{0, 1, \dots, K\}$ or continuous values already in $(0, 1)$.
ncuts	Integer: number of scale categories K (default 100). Must be $\geq \max(y)$.
lim	Numeric: half-width h of the uncertainty region (default 0.5). Controls the width of the interval around each scale point.
delta	Integer vector or NULL. If NULL (default), censoring types are inferred automatically from the boundary rules described above. If provided, must have the same length as y, with every element in $\{0, 1, 2, 3\}$. The supplied values override the automatic classification on a per-observation basis, and the endpoint formulas adapt to non-boundary observations as described in the table above. This parameter is used internally by the simulation functions when the analyst forces a specific censoring type (e.g., <code>brs_sim(..., delta = 2)</code>).

Details

Automatic classification (delta = NULL):

If the entire input vector is already in $(0, 1)$ (i.e., all values satisfy $0 < y < 1$), all observations are treated as uncensored ($\delta = 0$).

Otherwise, for scale (integer) data:

- $y = 0$: left-censored ($\delta = 1$).
- $y = K$: right-censored ($\delta = 2$).
- $0 < y < K$: interval-censored ($\delta = 3$).

User-supplied delta (delta vector):

When the delta argument is provided, the user-supplied censoring indicators override the automatic boundary-based rules on a per-observation basis. This is the mechanism used by `brs_sim` when the analyst forces a specific censoring type in Monte Carlo studies.

The endpoint formulas for each delta value are:

δ	Condition	l_i (left)	u_i (right)
----------	-----------	--------------	---------------

0	$y \in (0, 1)$	y	y
0	y on scale	y/K	y/K
1	$y = 0$ (boundary)	ϵ	lim/K
1	$y \neq 0$ (forced)	ϵ	$(y + \text{lim})/K$
2	$y = K$ (boundary)	$(K - \text{lim})/K$	$1 - \epsilon$
2	$y \neq K$ (forced)	$(y - \text{lim})/K$	$1 - \epsilon$
3	midpoint interval	$(y - \text{lim})/K$	$(y + \text{lim})/K$

All endpoints are clamped to $[\epsilon, 1 - \epsilon]$ with $\epsilon = 10^{-5}$ to avoid boundary issues in the beta likelihood.

The midpoint approximation y_t is computed as:

- $y_t = y$ when $y \in (0, 1)$ (continuous data).
- $y_t = y/K$ when y is on the integer scale.

This value is used exclusively as an initialization aid for starting-value computation and does not enter the likelihood.

Interaction with the fitting pipeline:

This function is called internally by `.extract_response()` when the data does *not* carry the "is_prepared" attribute. If data has already been processed by `brs_prep` or by simulation with forced delta (`brs_sim` with `delta != NULL`), the pre-computed columns are used directly and `brs_check()` is skipped.

Value

A numeric matrix with n rows and 5 columns:

`left` Lower endpoint l_i on $(0, 1)$, clamped to $[\epsilon, 1 - \epsilon]$.

`right` Upper endpoint u_i on $(0, 1)$, clamped to $[\epsilon, 1 - \epsilon]$.

`yt` Midpoint approximation y_t for starting-value computation (does not enter the likelihood).

`y` Original response value (preserved unchanged).

`delta` Censoring indicator: 0 = exact (density), 1 = left-censored $F(u)$, 2 = right-censored $1 - F(l)$, 3 = interval-censored $F(u) - F(l)$.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:10.1002/acr.20543

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:10.1016/j.jpainsymman.2010.08.016

See Also

[brs_prep](#) for the analyst-facing pre-processing function; [brs_sim](#) for simulation with forced delta.

Examples

```
# Scale data with boundary observations
y <- c(0, 3, 5, 7, 9, 10)
brs_check(y, ncuts = 10)

# Force all observations to be exact (delta = 0)
brs_check(y, ncuts = 10, delta = rep(0L, length(y)))

# Force delta = 1 on non-boundary observations:
# endpoints use actual y values, preserving variation
y2 <- c(30, 60)
brs_check(y2, ncuts = 100, delta = c(1L, 1L))
# left = (eps, eps), right = (30.5/100, 60.5/100)
```

brs_coef	<i>Internal coefficient table (deprecated, use brs_est() or summary())</i>
----------	--

Description

Deprecated convenience wrapper. Use [brs_est](#) for coefficient estimates or [summary.brs](#) for a full model summary.

Usage

```
brs_coef(fit, alpha = 0.05)
```

Arguments

fit	A fitted "brs" object.
alpha	Significance level.

Value

A list with components est (from [brs_est](#)) and gof (from [brs_gof](#)).

References

- Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.
- Ferrari, S. L. P., and Cribari-Neto, F. (2004). Beta regression for modelling rates and proportions. *Journal of Applied Statistics*, **31**(7), 799–815. doi:[10.1080/0266476042000214501](https://doi.org/10.1080/0266476042000214501)
- Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale

(CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). Arthritis Care and Research, 63(S11), S240-S252. doi:10.1002/acr.20543

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. Journal of Pain and Symptom Management, 41(6), 1073-1093. doi:10.1016/j.jpainsymman.2010.08.016

See Also

[brs_est](#), [brs_gof](#), [summary.brs](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
suppressWarnings(brs_coef(fit)) # deprecated; use brs_est()
```

brs_cv

K-fold cross-validation for brs models

Description

Performs repeated k-fold cross-validation for [brs](#) models.

Usage

```
brs_cv(formula, data, k = 5L, repeats = 1L, ...)
```

Arguments

formula	Model formula passed to brs .
data	Data frame.
k	Number of folds.
repeats	Number of repeated k-fold runs.
...	Additional arguments forwarded to brs (e.g., <code>repar</code> , <code>link</code> , <code>method</code>).

Details

The log_score is the mean log predictive contribution under the complete likelihood contribution implied by each observation’s censoring type (delta).

Value

A data frame with one row per fold and columns: repeat, fold, n_train, n_test, log_score, rmse_yt, mae_yt, converged, and error. The object has class "brs_cv".

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master’s dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:[10.1002/acr.20543](https://doi.org/10.1002/acr.20543)

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:[10.1016/j.jpainsymman.2010.08.016](https://doi.org/10.1016/j.jpainsymman.2010.08.016)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  x2 = rep(c(0, 0, 1, 1), 5)
)
prep <- brs_prep(dat, ncuts = 100)
cv <- brs_cv(y ~ x1, data = prep, k = 3, repeats = 1)
cv
```

brs_est	<i>Coefficient estimates with inference</i>
---------	---

Description

Coefficient estimates with inference

Usage

```
brs_est(object, alpha = 0.05)
```

Arguments

object	A fitted "betaregscale" object.
alpha	Significance level (default 0.05).

Value

Data frame of estimates, standard errors, z-values, and p-values.

References

- Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.
- Ferrari, S. L. P., and Cribari-Neto, F. (2004). Beta regression for modelling rates and proportions. *Journal of Applied Statistics*, **31**(7), 799–815. doi:[10.1080/0266476042000214501](https://doi.org/10.1080/0266476042000214501)
- Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:[10.1002/acr.20543](https://doi.org/10.1002/acr.20543)
- Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:[10.1016/j.jpainsymman.2010.08.016](https://doi.org/10.1016/j.jpainsymman.2010.08.016)

See Also

[brs](#), [brs_gof](#), [brs_hessian](#), [summary.brs](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
brs_est(fit)
```

brs_gof	<i>Goodness-of-fit measures</i>
---------	---------------------------------

Description

Goodness-of-fit measures

Usage

```
brs_gof(object)
```

Arguments

object A fitted "brs" or "brsmm" object.

Value

Data frame with logLik, AIC, BIC, and pseudo-R-squared.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:[10.1002/acr.20543](https://doi.org/10.1002/acr.20543)

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:[10.1016/j.jpainsymman.2010.08.016](https://doi.org/10.1016/j.jpainsymman.2010.08.016)

See Also

[brs](#), [brs_est](#), [brs_hessian](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
```

```
fit <- brs(y ~ x1, data = prep)
brs_gof(fit)
```

brs_hessian

Extract the Hessian matrix

Description

Extract the Hessian matrix

Usage

```
brs_hessian(object)
```

Arguments

object A fitted "brs" or "brsmm" object.

Value

Numeric Hessian matrix.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:[10.1002/acr.20543](https://doi.org/10.1002/acr.20543)

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:[10.1016/j.jpainsymman.2010.08.016](https://doi.org/10.1016/j.jpainsymman.2010.08.016)

See Also

[brs](#), [vcov.brs](#), [brs_est](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
brs_hessian(fit)

```

brs_marginaleffects	<i>Marginal effects for brs models</i>
---------------------	--

Description

Computes average marginal effects (AME) for numeric covariates in the mean or precision sub-model of a fitted "brs" object.

Usage

```

brs_marginaleffects(
  object,
  newdata = NULL,
  model = c("mean", "precision"),
  type = c("response", "link"),
  variables = NULL,
  h = 1e-05,
  interval = TRUE,
  level = 0.95,
  n_sim = 400L,
  keep_draws = FALSE
)

```

Arguments

object	A fitted "brs" object.
newdata	Optional data frame for evaluation; defaults to the data used in fitting.
model	Character; "mean" (default) or "precision".
type	Character prediction scale: "response" (default) or "link".
variables	Optional character vector of covariate names. Defaults to all numeric covariates in the selected submodel.
h	Finite-difference step for non-binary numeric covariates.

interval	Logical; compute interval estimates via simulation.
level	Confidence level for interval estimates.
n_sim	Number of parameter draws when interval = TRUE.
keep_draws	Logical; if TRUE and interval = TRUE, stores AME simulation draws in attribute "ame_draws".

Details

AMEs are computed by finite differences on predictions:

$$\text{AME}_j = \frac{1}{n} \sum_{i=1}^n \frac{\hat{g}_i(x_{ij} + h) - \hat{g}_i(x_{ij})}{h},$$

where $\hat{g}_i$ is the selected prediction scale.

For binary covariates coded as 0/1, the effect is computed as the average discrete difference $\hat{g}(x_j = 1) - \hat{g}(x_j = 0)$.

If interval = TRUE, uncertainty is approximated by asymptotic parameter simulation from $\mathcal{N}(\hat{\theta}, \hat{V})$.

Value

A data frame with one row per variable and columns: variable, ame, std.error, ci.lower, ci.upper, model, type, and n. The returned object has class "brs_marginaleffects" and attributes with analysis metadata.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:10.1002/acr.20543

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:10.1016/j.jpainsymman.2010.08.016

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  x2 = rep(c(0, 0, 1, 1), 5)
```

```

)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
brs_marginaleffects(fit, model = "mean", type = "response")

```

brs_predict_scoreprob *Predict score probabilities from a fitted brs model*

Description

Computes predicted probabilities for integer scores on the original scale $\{0, 1, \dots, K\}$ implied by the fitted beta interval model.

Usage

```

brs_predict_scoreprob(
  object,
  newdata = NULL,
  scores = NULL,
  format = c("matrix", "long"),
  id_col = "id"
)

```

Arguments

object	A fitted "brs" object.
newdata	Optional data frame for prediction.
scores	Optional integer vector of scores to evaluate. Defaults to all scores in $0:ncuts$.
format	Output format: "matrix" (default) or "long".
id_col	Column name for observation id when format = "long".

Details

For a score s and $K = ncuts$, probabilities are computed as:

- $P(Y = s) = F(\text{lim}/K)$ for $s = 0$,
- $P(Y = s) = 1 - F((K - \text{lim})/K)$ for $s = K$,
- $P(Y = s) = F((s + \text{lim})/K) - F((s - \text{lim})/K)$ for $s \in \{1, \dots, K - 1\}$,

where F is the beta CDF under the fitted (μ_i, ϕ_i) .

Value

If format = "matrix", a numeric matrix with one row per observation and one column per requested score.

If format = "long", a long data frame with columns id_col, score, and prob.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:[10.1002/acr.20543](https://doi.org/10.1002/acr.20543)

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:[10.1016/j.jpainsymman.2010.08.016](https://doi.org/10.1016/j.jpainsymman.2010.08.016)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  x2 = rep(c(0, 0, 1, 1), 5)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
pmat <- brs_predict_scoreprob(fit)
head(pmat[, 1:5])
plong <- brs_predict_scoreprob(fit, scores = 0:10, format = "long")
head(plong)
```

brs_prep

Pre-process analyst data for beta interval regression

Description

Validates and transforms raw data into the format required by [brs](#). The analyst can supply data in several ways:

1. **Minimal (Mode 1):** only the score y . Censoring is inferred automatically: $y = 0 \rightarrow \delta = 1$, $y = K \rightarrow \delta = 2$, $0 < y < K \rightarrow \delta = 3$, $y \in (0, 1) \rightarrow \delta = 0$.
2. **Classic (Mode 2):** y + explicit delta. The analyst declares the censoring type; interval endpoints are computed using the actual y value.
3. **Interval (Mode 3):** left and/or right columns (on the original scale). Censoring is inferred from the NA pattern.

4. **Full (Mode 4):** y, left, and right together. The analyst's own endpoints are rescaled directly to (0, 1).

All covariate columns are preserved unchanged in the output.

Usage

```
brs_prep(
  data,
  y = "y",
  delta = "delta",
  left = "left",
  right = "right",
  ncuts = 100L,
  lim = 0.5
)
```

Arguments

data	Data frame containing the response variable and covariates.
y	Character: name of the score column (default "y").
delta	Character: name of the censoring indicator column (default "delta"). Values must be in {0, 1, 2, 3}.
left	Character: name of the left-endpoint column (default "left").
right	Character: name of the right-endpoint column (default "right").
ncuts	Integer: number of scale categories (default 100).
lim	Numeric: half-width of the uncertainty region (default 0.5). Used only when constructing intervals from y alone.

Details

Priority rule: if delta is provided (non-NA), it takes precedence over all automatic classification rules. When delta is NA, the function infers the censoring type from the pattern of left, right, and y:

left	right	y	delta	Interpretation	Inferred δ
NA	5	NA	NA	Left-censored (below 5)	1
20	NA	NA	NA	Right-censored (above 20)	2
30	45	NA	NA	Interval-censored [30, 45]	3
NA	NA	50	NA	Exact observation	0
NA	NA	50	3	Analyst says interval	3
NA	NA	0	1	Analyst says left-censored	1
NA	NA	99	2	Analyst says right-censored	2

When y, left, and right are all present for the same observation, the analyst's left/right values are used directly (rescaled by $K = \text{ncuts}$) and delta is set to 3 (interval-censored) unless the analyst supplied delta explicitly.

Endpoint formulas for Mode 2 (y + explicit delta):

When the analyst supplies delta explicitly, the endpoint computation uses the actual y value to produce observation-specific bounds. This is the same logic used by `brs_check` with a user-supplied delta vector:

δ	Condition	l_i (left)	u_i (right)
0	(any)	y/K	y/K
1	$y = 0$	ϵ	lim/K
1	$y \neq 0$	ϵ	$(y + \text{lim})/K$
2	$y = K$	$(K - \text{lim})/K$	$1 - \epsilon$
2	$y \neq K$	$(y - \text{lim})/K$	$1 - \epsilon$
3	type "m"	$(y - \text{lim})/K$	$(y + \text{lim})/K$

Consistency warnings: when the analyst supplies delta values that are unusual for the given y (e.g., $\delta = 1$ but $y \neq 0$), the function emits a warning but proceeds. This is by design for Monte Carlo workflows where forced delta on non-boundary observations is intentional.

All endpoints are clamped to $[\epsilon, 1 - \epsilon]$ with $\epsilon = 10^{-5}$.

Value

A data.frame with the following columns appended or replaced:

left Lower endpoint on $(0, 1)$.

right Upper endpoint on $(0, 1)$.

yt Midpoint approximation on $(0, 1)$.

y Original scale value (preserved for reference).

delta Censoring indicator: 0 = exact, 1 = left, 2 = right, 3 = interval.

Covariate columns are preserved. The output carries attributes "is_prepared" (TRUE), "ncuts" and "lim" so that `brs` can detect prepared data and skip the internal `brs_check` call.

References

- Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.
- Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:10.1002/acr.20543
- Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:10.1016/j.jpainsymman.2010.08.016

See Also

[brs_check](#) for the automatic classification of raw scale scores; [brs](#) for fitting the model.

Examples

```
# --- Mode 1: y only (automatic classification, like brs_check) ---
d1 <- data.frame(y = c(0, 3, 5, 7, 10), x1 = rnorm(5))
brs_prep(d1, ncuts = 10)

# --- Mode 2: y + explicit delta ---
d2 <- data.frame(
  y = d1$y,
  delta = c(0, 3, 3, 3, 0), # Force interval-censoring for 3,5,7
  x1 = d1$x1
)
brs_prep(d2, ncuts = 100)

# --- Mode 3: left/right with NA patterns ---
d3 <- data.frame(
  left = c(NA, 20, 30, NA),
  right = c(5, NA, 45, NA),
  y = c(NA, NA, NA, 50),
  x1 = d1$x1[1:4]
)
brs_prep(d3, ncuts = 100)

# --- Mode 4: y + left + right (analyst-supplied intervals) ---
d4 <- data.frame(
  y = c(50, 75),
  left = c(48, 73),
  right = c(52, 77),
  x1 = rnorm(2)
)
brs_prep(d4, ncuts = 100)

# --- Fitting after prep ---

dat5 <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep5 <- brs_prep(dat5, ncuts = 100)
fit5 <- brs(y ~ x1, data = prep5)
summary(fit5)
```

brs_repar	<i>Reparameterize (mu, phi) into beta shape parameters</i>
-----------	--

Description

Converts a mean–dispersion pair (μ, ϕ) to the shape parameters (a, b) of the beta distribution under one of three reparameterization schemes.

Usage

```
brs_repar(mu, phi, repar = 2L)
```

Arguments

- mu Numeric vector of mean values in $(0, 1)$.
- phi Numeric vector (or scalar) of dispersion values.
- repar Integer (0, 1, or 2) selecting the scheme.

Details

The three schemes are:

repar = 0 Direct: $a = \mu, b = \phi$.

repar = 1 Ferrari–Cribari–Neto: $a = \mu\phi, b = (1 - \mu)\phi$, where ϕ acts as a precision parameter.

repar = 2 Mean–variance: $a = \mu(1 - \phi)/\phi, b = (1 - \mu)(1 - \phi)/\phi$, where $\phi \in (0, 1)$ is analogous to a coefficient of variation.

Value

A data.frame with columns shape1 and shape2.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master’s dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:10.1002/acr.20543

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:10.1016/j.jpainsymman.2010.08.016

Examples

```
brs_repar(mu = 0.5, phi = 0.2, repar = 2)
```

brs_sim

*Simulate data from beta interval models***Description**

Simulates interval-censored responses from fixed- or variable-dispersion beta regression models.

Usage

```
brs_sim(
  formula,
  data,
  beta,
  phi = 1/5,
  zeta = NULL,
  link = "logit",
  link_phi = "logit",
  ncuts = 100L,
  lim = 0.5,
  repar = 2L,
  delta = NULL
)
```

Arguments

formula	Model formula with one (mean) or two parts (mean precision). A left-hand-side response is allowed but ignored.
data	Data frame with predictor variables.
beta	Numeric vector of mean-model coefficients.
phi	Scalar dispersion parameter (link scale), used only for one-part formulas.
zeta	Numeric vector of precision-model coefficients (link scale), required for two-part formulas.
link	Mean link function.
link_phi	Precision link function.
ncuts	Number of scale categories.
lim	Half-width used in interval construction.
repar	Reparameterization scheme.
delta	Forced censoring type (0, 1, 2, 3) or NULL.

Details

The model structure is controlled by `formula` in the same style as `brs`:

- one-part formula ($\sim x_1 + x_2$ or $y \sim x_1 + x_2$): fixed dispersion using scalar ϕ .
- two-part formula ($\sim x_1 + x_2 \mid z_1$ or $y \sim x_1 + x_2 \mid z_1$): variable dispersion using coefficient vector ζ .

The `delta` argument can force a single censoring type (0, 1, 2, 3) for all observations; otherwise, censoring is classified automatically from simulated scale values via `brs_check`.

Value

A data frame with columns `left`, `right`, `yt`, `y`, `delta`, plus simulated predictor columns from the model matrices. When `delta != NULL`, the output carries `attr(, "is_prepared") = TRUE`.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master's dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. doi:10.1002/acr.20543

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. doi:10.1016/j.jpainsymman.2010.08.016

Examples

```
dat <- data.frame(
  x1 = rep(c(1, 2), 10),
  x2 = rep(c(0, 0, 1, 1), 5)
)
# Fixed dispersion
sim_fixed <- brs_sim(
  formula = ~ x1 + x2, data = dat,
  beta = c(0.2, -0.5, 0.3), phi = 1 / 5
)
# Variable dispersion
sim_var <- brs_sim(
  formula = ~ x1 | x2, data = dat,
  beta = c(0.2, -0.5), zeta = c(0.5, -0.5)
)
```

brs_table	<i>Compare fitted brs models in a single table</i>
-----------	--

Description

Builds a comparison table for one or more fitted "brs" objects, summarizing fit statistics and (optionally) censoring composition.

Usage

```
brs_table(  
  ...,  
  models = NULL,  
  include_censoring = TRUE,  
  sort_by = c("none", "AIC", "BIC", "logLik"),  
  decreasing = FALSE,  
  digits = 4L  
)
```

Arguments

- ... Fitted "brs" objects passed individually.
- models Optional list of fitted "brs" objects. Use either ... or models, not both.
- include_censoring Logical; include censoring counts/proportions. Default is TRUE.
- sort_by Character; optional sort criterion: "none" (default), "AIC", "BIC", or "logLik".
- decreasing Logical; sort direction when sort_by != "none".
- digits Integer number of digits used for numeric rounding.

Value

A data frame with one row per model.

References

Lopes, J. E. (2023). *Modelos de regressao beta para dados de escala*. Master’s dissertation, Universidade Federal do Parana, Curitiba. URI: <https://hdl.handle.net/1884/86624>.

Hawker, G. A., Mian, S., Kendzerska, T., and French, M. (2011). Measures of adult pain: Visual Analog Scale for Pain (VAS Pain), Numeric Rating Scale for Pain (NRS Pain), McGill Pain Questionnaire (MPQ), Short-Form McGill Pain Questionnaire (SF-MPQ), Chronic Pain Grade Scale (CPGS), Short Form-36 Bodily Pain Scale (SF-36 BPS), and Measure of Intermittent and Constant Osteoarthritis Pain (ICOAP). *Arthritis Care and Research*, 63(S11), S240-S252. [doi:10.1002/acr.20543](https://doi.org/10.1002/acr.20543)

Hjermstad, M. J., Fayers, P. M., Haugen, D. F., et al. (2011). Studies comparing Numerical Rating Scales, Verbal Rating Scales, and Visual Analogue Scales for assessment of pain intensity in adults: a systematic literature review. *Journal of Pain and Symptom Management*, 41(6), 1073-1093. [doi:10.1016/j.jpainsymman.2010.08.016](https://doi.org/10.1016/j.jpainsymman.2010.08.016)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  x2 = rep(c(0, 0, 1, 1), 5)
)
prep <- brs_prep(dat, ncuts = 100)
m1 <- brs(y ~ 1, data = prep)
m2 <- brs(y ~ x1, data = prep)
brs_table(null = m1, x1 = m2, sort_by = "AIC")

```

coef.brs

*Extract model coefficients***Description**

Extract model coefficients

Usage

```

## S3 method for class 'brs'
coef(object, model = c("full", "mean", "precision"), ...)

```

Arguments

object	A fitted "betaregscale" object.
model	Character: which component to return. "full" (default) returns all parameters, "mean" returns only the mean-model coefficients, "precision" returns only the precision coefficients.
...	Ignored.

Value

Named numeric vector of estimated parameters.

See Also

[brs](#), [brs_est](#), [vcov.brs](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
coef(fit)
coef(fit, model = "mean")
coef(fit, model = "precision")

```

coef.brsmm

*Extract coefficients from a brsmm fit***Description**

Extract coefficients from a brsmm fit

Usage

```

## S3 method for class 'brsmm'
coef(object, model = c("full", "mean", "precision", "random"), ...)

```

Arguments

object	A fitted "brsmm" object.
model	Character: "full" (default), "mean", "precision", or "random".
...	Currently ignored.

Value

Named numeric vector.

See Also

[brsmm](#), [vcov.brsmm](#), [confint.brsmm](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
coef(fit)
coef(fit, model = "mean")
coef(fit, model = "random")

```

confint.brs

Wald confidence intervals

Description

Computes Wald confidence intervals for model parameters using the normal approximation.

Usage

```

## S3 method for class 'brs'
confint(
  object,
  parm,
  level = 0.95,
  model = c("full", "mean", "precision"),
  ...
)

```

Arguments

object	A fitted "betaregscale" object.
parm	Character or integer: which parameters. If missing, all parameters are returned.
level	Confidence level (default 0.95).
model	Character: "full", "mean", or "precision".
...	Currently ignored.

Value

Matrix with columns for lower and upper confidence bounds.

See Also

[brs](#), [coef.brs](#), [vcov.brs](#), [brs_est](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
confint(fit)
confint(fit, model = "mean")
```

confint.brsmm

Wald confidence intervals for brsmm models

Description

Wald confidence intervals for brsmm models

Usage

```
## S3 method for class 'brsmm'
confint(
  object,
  parm,
  level = 0.95,
  model = c("full", "mean", "precision", "random"),
  ...
)
```

Arguments

object	A fitted "brsmm" object.
parm	Character or integer: which parameters.
level	Confidence level (default 0.95).
model	Character: "full", "mean", "precision", or "random".
...	Currently ignored.

Value

Matrix with columns for lower and upper confidence bounds.

See Also

[brsmm](#), [coef.brsmm](#), [vcov.brsmm](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
confint(fit, model = "mean")
```

fitted.brs	<i>Extract fitted values</i>
------------	------------------------------

Description

Extract fitted values

Usage

```
## S3 method for class 'brs'
fitted(object, type = c("mu", "phi"), ...)
```

Arguments

- object A fitted "betaregscale" object.
- type Character: "mu" (default) or "phi".
- ... Currently ignored.

Value

Numeric vector of fitted values.

See Also

[brs](#), [residuals.brs](#), [predict.brs](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
head(fitted(fit))
head(fitted(fit, type = "phi"))

```

fitted.brsmm

*Fitted values from a brsmm model***Description**

Fitted values from a brsmm model

Usage

```

## S3 method for class 'brsmm'
fitted(object, type = c("mu", "phi"), ...)

```

Arguments

object	A fitted "brsmm" object.
type	Character: "mu" (default) or "phi".
...	Currently ignored.

Value

Numeric vector.

See Also

[brsmm](#), [residuals.brsmm](#), [predict.brsmm](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),

```

```

x1 = rep(c(1, 2), 10),
id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
head(fitted(fit))
head(fitted(fit, type = "phi"))

```

formula.brs

*Extract model formula***Description**

Extract model formula

Usage

```

## S3 method for class 'brs'
formula(x, ...)

```

Arguments

x	A fitted "betaregscale" object.
...	Ignored.

Value

The formula used to fit the model.

See Also

[brs](#), [model.matrix.brs](#), [coef.brs](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
formula(fit)

```

formula.brsmm	<i>Extract model formula</i>
---------------	------------------------------

Description

Extract model formula

Usage

```
## S3 method for class 'brsmm'  
formula(x, ...)
```

Arguments

x	A fitted "brsmm" object.
...	Ignored.

Value

The formula used to fit the model.

See Also

[brsmm](#), [model.matrix.brsmm](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10),  
  id = factor(rep(1:4, each = 5))  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)  
formula(fit)
```

logLik.brs	<i>Extract log-likelihood</i>
------------	-------------------------------

Description

Extract log-likelihood

Usage

```
## S3 method for class 'brs'  
logLik(object, ...)
```

Arguments

object	A fitted "betaregscale" object.
...	Ignored.

Value

An object of class "logLik" with attributes df (number of estimated parameters) and nobs (number of observations).

See Also

[brs](#), [AIC.brs](#), [BIC.brs](#), [brs_gof](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10)  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brs(y ~ x1, data = prep)  
logLik(fit)
```

logLik.brsmm	<i>Log-likelihood for brsmm models</i>
--------------	--

Description

Log-likelihood for brsmm models

Usage

```
## S3 method for class 'brsmm'  
logLik(object, ...)
```

Arguments

object	A fitted "brsmm" object.
...	Currently ignored.

Value

Object of class "logLik".

See Also

[brsmm](#), [AIC.brsmm](#), [BIC.brsmm](#), [brs_gof](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10),  
  id = factor(rep(1:4, each = 5))  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)  
logLik(fit)
```

model.matrix.brs	<i>Extract design matrix</i>
------------------	------------------------------

Description

Extract design matrix

Usage

```
## S3 method for class 'brs'  
model.matrix(object, model = c("mean", "precision"), ...)
```

Arguments

object	A fitted "betaregscale" object.
model	Character: "mean" (default) or "precision".
...	Ignored.

Value

The design matrix for the specified submodel.

See Also

[brs](#), [formula.brs](#), [coef.brs](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10)  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brs(y ~ x1, data = prep)  
head(model.matrix(fit))  
head(model.matrix(fit, model = "precision"))
```

model.matrix.brsmm	<i>Extract design matrix</i>
--------------------	------------------------------

Description

Extract design matrix

Usage

```
## S3 method for class 'brsmm'  
model.matrix(object, model = c("mean", "precision", "random"), ...)
```

Arguments

object	A fitted "brsmm" object.
model	Character: "mean" (default), "precision", or "random".
...	Ignored.

Value

The design matrix for the specified submodel.

See Also

[brsmm](#), [formula.brsmm](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10),  
  id = factor(rep(1:4, each = 5))  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)  
head(model.matrix(fit))  
head(model.matrix(fit, model = "random"))
```

nobs.brs	<i>Number of observations</i>
----------	-------------------------------

Description

Number of observations

Usage

```
## S3 method for class 'brs'
nobs(object, ...)
```

Arguments

object	A fitted "betaregscale" object.
...	Ignored.

Value

Integer: number of observations.

See Also

[brs](#), [fitted.brs](#), [brs_gof](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
nobs(fit)
```

nobs.brsmm	<i>Number of observations in a brsmm fit</i>
------------	--

Description

Number of observations in a brsmm fit

Usage

```
## S3 method for class 'brsmm'  
nobs(object, ...)
```

Arguments

object	A fitted "brsmm" object.
...	Currently ignored.

Value

Integer.

See Also

[brsmm](#), [fitted.brsmm](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10),  
  id = factor(rep(1:4, each = 5))  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)  
nobs(fit)
```

Description

Produces up to six diagnostic plots for a fitted "brs" model: residuals vs indices, Cook's distance, residuals vs linear predictor, residuals vs fitted values, a half-normal plot with simulated envelope, and predicted vs observed.

Usage

```
## S3 method for class 'brs'
plot(
  x,
  which = 1:4,
  type = "rqr",
  nsim = 100L,
  level = 0.9,
  caption = c("Residuals vs indices", "Cook's distance", "Residuals vs linear predictor",
    "Residuals vs fitted values", "Half-normal plot", "Predicted vs observed"),
  sub.caption = NULL,
  ask = prod(par("mfcol")) < length(which) && dev.interactive(),
  gg = FALSE,
  title = NULL,
  theme = NULL,
  ...
)
```

Arguments

x	A fitted "brs" object.
which	Integer vector selecting which plots to draw (default 1:4).
type	Character: residual type passed to residuals.brs (default "rqr").
nsim	Integer: number of simulations for the half-normal envelope (default 100).
level	Numeric: confidence level for the envelope (default 0.9).
caption	Character vector of panel captions.
sub.caption	Subtitle; defaults to the model call.
ask	Logical: prompt before each page of plots?
gg	Logical: use ggplot2? (default FALSE).
title	Optional global title for ggplot output. If NULL, panel captions are used.
theme	Optional ggplot2 theme object (e.g., <code>ggplot2::theme_bw()</code>). If NULL, a minimal theme is used.
...	Further arguments passed to base <code>plot()</code> .

Value

Invisibly returns `x`.

See Also

[brs](#), [residuals.brs](#), [autoplot.brs](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
plot(fit, which = 1:4)
```

plot.brsmm

Diagnostic plots for mixed beta interval regression

Description

Produces diagnostic plots for fitted "brsmm" models: residuals vs indices, Cook's distance, residuals vs linear predictor, residuals vs fitted values, half-normal envelope, and predicted vs observed.

Usage

```
## S3 method for class 'brsmm'
plot(
  x,
  which = 1:4,
  type = c("response", "pearson"),
  nsim = 100L,
  level = 0.9,
  caption = c("Residuals vs indices", "Cook's distance", "Residuals vs linear predictor",
    "Residuals vs fitted values", "Half-normal plot", "Predicted vs observed",
    "Random-effects Q-Q", "Random-effects caterpillar"),
  sub.caption = NULL,
  ask = prod(par("mfcol")) < length(which) && dev.interactive(),
  gg = FALSE,
  title = NULL,
  theme = NULL,
  ...
)
```

Arguments

x	A fitted "brsmm" object.
which	Integer vector selecting which panels to draw (default 1:4).
type	Residual type passed to <code>residuals.brsmm</code> ("response" or "pearson").
nsim	Number of simulations for half-normal envelope.
level	Confidence level for the half-normal envelope.
caption	Character vector of plot captions.
sub.caption	Optional subtitle; defaults to model call.
ask	Logical: prompt before each new page?
gg	Logical: use ggplot2 backend?
title	Optional global title for ggplot output. If NULL, panel captions are used.
theme	Optional ggplot2 theme object (e.g., <code>ggplot2::theme_bw()</code>). If NULL, a minimal theme is used.
...	Further arguments passed to base <code>plot()</code> .

Value

Invisibly returns x.

See Also

`brsmm`, `residuals.brsmm`, `autoplot.brsmm`

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
plot(fit, which = 1:4)
```

predict.brs	<i>Predict from a fitted model</i>
-------------	------------------------------------

Description

Predict from a fitted model

Usage

```
## S3 method for class 'brs'
predict(
  object,
  newdata = NULL,
  type = c("response", "link", "precision", "variance", "quantile"),
  at = 0.5,
  ...
)
```

Arguments

object	A fitted "betaregyscale" object.
newdata	Optional data frame for prediction.
type	Prediction type: "response" (default), "link", "precision", "variance", or "quantile".
at	Numeric vector of probabilities for quantile predictions (default 0.5).
...	Currently ignored.

Value

Numeric vector or matrix.

See Also

[brs](#), [fitted.brs](#), [brs_predict_scoreprob](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
head(predict(fit))
```

```
head(predict(fit, type = "precision"))
newdat <- data.frame(x1 = c(1, 2))
predict(fit, newdata = newdat)
```

predict.brsmm	<i>Predict from a brsmm model</i>
---------------	-----------------------------------

Description

Predict from a brsmm model

Usage

```
## S3 method for class 'brsmm'
predict(
  object,
  newdata = NULL,
  type = c("response", "link", "precision", "variance", "quantile"),
  at = 0.5,
  ...
)
```

Arguments

object	A fitted "brsmm" object.
newdata	Optional data frame.
type	Character: "response" (default), "link", "precision", "variance", or "quantile".
at	Numeric vector of probabilities for quantile predictions (default 0.5).
...	Currently ignored.

Value

Numeric vector.

See Also

[brsmm](#), [fitted.brsmm](#), [brs_predict_scoreprob](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
head(predict(fit))
head(predict(fit, type = "precision"))

```

print.brs

Print a fitted model (brief betareg style)

Description

Print a fitted model (brief betareg style)

Usage

```

## S3 method for class 'brs'
print(x, digits = max(3, getOption("digits") - 3), ...)

```

Arguments

x	A fitted "betaregscale" object.
digits	Number of significant digits.
...	Included for consistency with generic methods. Currently passed to internal methods where applicable.

Value

Invisibly returns the input object x. The function is called for its side effect of printing a formatted summary of the fitted model to the console, including the model call, mean coefficients (with link function), and precision coefficients (with link function).

See Also

[summary.brs](#), [print.summary.brs](#), [brs](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
print(fit)

```

print.brsmm

Print a fitted brsmm model

Description

Print a fitted brsmm model

Usage

```

## S3 method for class 'brsmm'
print(x, digits = max(3, getOption("digits") - 3), ...)

```

Arguments

x	A fitted "brsmm" object.
digits	Number of digits.
...	Included for consistency with generic methods.

Value

Invisibly returns x.

See Also

[summary.brsmm](#), [print.summary.brsmm](#), [brsmm](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),

```

```

    id = factor(rep(1:4, each = 5))
  )
  prep <- brs_prep(dat, ncuts = 100)
  fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
  print(fit)

```

```
print.brsmm_re_study
```

Print a random-effects study

Description

Prints a compact summary of the random-effects study returned by [brsmm_re_study](#), including per-term standard deviations, shrinkage ratios, Shapiro-Wilk p-values, and the estimated covariance and correlation matrices.

Usage

```

## S3 method for class 'brsmm_re_study'
print(x, digits = max(3, getOption("digits") - 3), ...)

```

Arguments

x	A "brsmm_re_study" object returned by brsmm_re_study .
digits	Integer: number of significant digits for rounding (default <code>max(3, getOption("digits") - 3)</code>).
...	Currently ignored.

Value

Invisibly returns x. Called for its side-effect of printing the study to the console.

See Also

[brsmm_re_study](#), [brsmm](#), [ranef.brsmm](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)

```

```
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
rs <- brsmm_re_study(fit)
print(rs)
```

print.summary.brs	<i>Print a model summary (betareg style)</i>
-------------------	--

Description

Print a model summary (betareg style)

Usage

```
## S3 method for class 'summary.brs'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

x	A "summary.betaregscale" object.
digits	Number of digits.
...	Passed to printCoefmat.

Value

Invisibly returns the input object x. The function is called for its side effect of printing a comprehensive summary to the console, including the model call, quantile residuals, coefficient tables for mean and precision submodels with significance stars, goodness-of-fit statistics (log-likelihood, pseudo R-squared), optimization details, and censoring information.

See Also

[summary.brs](#), [brs](#), [print.brs](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
print(summary(fit))
```

print.summary.brsmm *Print summary for brsmm models*

Description

Print summary for brsmm models

Usage

```
## S3 method for class 'summary.brsmm'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

x	A "summary.brsmm" object.
digits	Number of digits.
...	Passed to printCoefmat.

Value

Invisibly returns x.

See Also

[summary.brsmm](#), [brsmm](#), [print.brsmm](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
print(summary(fit))
```

ranef	<i>Extract random effects</i>
-------	-------------------------------

Description

Generic function for extracting random effects.

Usage

```
ranef(object, ...)
```

Arguments

object	A fitted model object.
...	Additional arguments passed to methods.

Value

Method-specific; for "brsmm" objects, a matrix or named numeric vector of group-specific random-effect modes.

See Also

[ranef.brsmm](#), [brsmm_re_study](#)

Examples

```
dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
ranef(fit)
```

ranef.brsmm	<i>Extract random effects from a brsmm model</i>
-------------	--

Description

Extract random effects from a brsmm model

Usage

```
## S3 method for class 'brsmm'  
ranef(object, ...)
```

Arguments

object	A fitted "brsmm" object.
...	Currently ignored.

Value

A matrix or named numeric vector of group-specific random-effect posterior modes.

See Also

[brsmm](#), [brsmm_re_study](#), [ranef](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10),  
  id = factor(rep(1:4, each = 5))  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)  
ranef(fit)
```

residuals.brs	<i>Extract residuals</i>
---------------	--------------------------

Description

Extract residuals

Usage

```
## S3 method for class 'brs'
residuals(
  object,
  type = c("response", "pearson", "deviance", "rqr", "weighted", "sweighted"),
  ...
)
```

Arguments

object	A fitted "betareg" object.
type	Residual type. One of "response" (default), "pearson", "deviance", "rqr" (randomized quantile), "weighted", or "sweighted".
...	Currently ignored.

Details

For Pearson residuals the variance formula depends on the reparameterization stored in `object$repar`:

repar = 1 (precision) $V = \mu(1 - \mu) / (1 + \phi)$

repar = 2 (mean-variance) $V = \mu(1 - \mu) * \phi$

The weighted and sweighted residuals use the digamma/trigamma formulation from the precision parameterization (`repar = 1`), so internal conversion is applied when `repar != 1`.

Value

Numeric vector of residuals.

See Also

[brs](#), [fitted.brs](#), [plot.brs](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
head(residuals(fit))
head(residuals(fit, type = "pearson"))

```

residuals.brsmm	<i>Residuals from a brsmm model</i>
-----------------	-------------------------------------

Description

Residuals from a brsmm model

Usage

```

## S3 method for class 'brsmm'
residuals(
  object,
  type = c("response", "pearson", "deviance", "rqr", "weighted", "sweighted"),
  ...
)

```

Arguments

object	A fitted "brsmm" object.
type	Character: "response" (default), "pearson", "deviance", "rqr", "weighted", or "sweighted".
...	Currently ignored.

Value

Numeric vector.

See Also

[brsmm](#), [fitted.brsmm](#), [plot.brsmm](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
head(residuals(fit))
head(residuals(fit, type = "pearson"))

```

summary.brs

*Summarize a fitted model (betareg style)***Description**

Summarize a fitted model (betareg style)

Usage

```

## S3 method for class 'brs'
summary(object, ...)

```

Arguments

object	A fitted "betaregscale" object.
...	Ignored.

Value

A list of class "summary.betaregscale".

See Also

[brs](#), [print.summary.brs](#), [brs_est](#), [brs_gof](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10)
)

```

```

)
prep <- brs_prep(dat, ncuts = 100)
fit <- brs(y ~ x1, data = prep)
s <- summary(fit)
s$coefficients$mean

```

summary.brsmm

*Summarize a fitted brsmm model***Description**

Summarize a fitted brsmm model

Usage

```

## S3 method for class 'brsmm'
summary(object, ...)

```

Arguments

object	A fitted "brsmm" object.
...	Currently ignored.

Value

Object of class "summary.brsmm".

See Also

[brsmm](#), [print.summary.brsmm](#), [brs_gof](#), [brsmm_re_study](#)

Examples

```

dat <- data.frame(
  y = c(
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15
  ),
  x1 = rep(c(1, 2), 10),
  id = factor(rep(1:4, each = 5))
)
prep <- brs_prep(dat, ncuts = 100)
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)
s <- summary(fit)
s$coefficients$mean

```

`vcov.brs`*Variance-covariance matrix of estimated coefficients*

Description

Variance-covariance matrix of estimated coefficients

Usage

```
## S3 method for class 'brs'  
vcov(object, model = c("full", "mean", "precision"), ...)
```

Arguments

<code>object</code>	A fitted "betaregscale" object.
<code>model</code>	Character: which component ("full", "mean", or "precision").
<code>...</code>	Ignored.

Value

A square numeric matrix.

See Also

[brs](#), [coef.brs](#), [confint.brs](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10)  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brs(y ~ x1, data = prep)  
vcov(fit)  
vcov(fit, model = "mean")
```

vcov.brsmm	<i>Variance-covariance matrix for brsmm coefficients</i>
------------	--

Description

Variance-covariance matrix for brsmm coefficients

Usage

```
## S3 method for class 'brsmm'  
vcov(object, model = c("full", "mean", "precision", "random"), ...)
```

Arguments

object	A fitted "brsmm" object.
model	Character: "full", "mean", "precision", or "random".
...	Currently ignored.

Value

Numeric matrix.

See Also

[brsmm](#), [coef.brsmm](#), [confint.brsmm](#)

Examples

```
dat <- data.frame(  
  y = c(  
    0, 5, 20, 50, 75, 90, 100, 30, 60, 45,  
    10, 40, 55, 70, 85, 25, 35, 65, 80, 15  
  ),  
  x1 = rep(c(1, 2), 10),  
  id = factor(rep(1:4, each = 5))  
)  
prep <- brs_prep(dat, ncuts = 100)  
fit <- brsmm(y ~ x1, random = ~ 1 | id, data = prep)  
vcov(fit, model = "mean")
```

Index

AIC.brs, [3](#), [5](#), [14](#), [52](#)
AIC.brsmm, [4](#), [7](#), [15](#), [53](#)
anova.brs, [5](#)
anova.brsmm, [6](#)
autoplot.brs, [7](#), [12](#), [13](#), [59](#)
autoplot.brs_bootstrap, [9](#), [11](#)
autoplot.brs_marginaleffects, [12](#)
autoplot.brsmm, [9](#), [60](#)

BIC.brs, [4](#), [5](#), [14](#), [52](#)
BIC.brsmm, [4](#), [7](#), [15](#), [53](#)
brs, [4](#), [5](#), [9](#), [12–14](#), [16](#), [19](#), [21](#), [22](#), [28](#), [30–32](#),
[36](#), [38](#), [39](#), [42](#), [44](#), [47](#), [48](#), [50](#), [52](#), [54](#),
[56](#), [59](#), [61](#), [63](#), [66](#), [70](#), [72](#), [74](#)
brs_bootstrap, [11](#), [12](#), [21](#)
brs_cens, [22](#)
brs_check, [23](#), [24](#), [38](#), [39](#), [42](#)
brs_coef, [27](#)
brs_cv, [28](#)
brs_est, [27](#), [28](#), [29](#), [31](#), [32](#), [44](#), [47](#), [72](#)
brs_fit_fixed, [16](#)
brs_fit_var, [16](#)
brs_gof, [4](#), [14](#), [15](#), [27](#), [28](#), [30](#), [31](#), [52](#), [53](#), [56](#),
[72](#), [73](#)
brs_hessian, [30](#), [31](#), [32](#)
brs_marginaleffects, [12](#), [13](#), [33](#)
brs_predict_scoreprob, [35](#), [61](#), [62](#)
brs_prep, [23](#), [26](#), [27](#), [36](#)
brs_repar, [40](#)
brs_sim, [21](#), [22](#), [25–27](#), [41](#)
brs_table, [43](#)
brsmm, [4](#), [7](#), [15](#), [17](#), [20](#), [45](#), [48](#), [49](#), [51](#), [53](#), [55](#),
[57](#), [60](#), [62](#), [64](#), [65](#), [67](#), [69](#), [71](#), [73](#), [75](#)
brsmm_re_study, [20](#), [65](#), [68](#), [69](#), [73](#)

coef.brs, [44](#), [47](#), [50](#), [54](#), [74](#)
coef.brsmm, [45](#), [48](#), [75](#)
confint.brs, [22](#), [46](#), [74](#)
confint.brsmm, [45](#), [47](#), [75](#)

fitted.brs, [48](#), [56](#), [61](#), [70](#)
fitted.brsmm, [49](#), [57](#), [62](#), [71](#)
Formula, [16](#)
formula.brs, [50](#), [54](#)
formula.brsmm, [51](#), [55](#)

logLik.brs, [4](#), [5](#), [14](#), [52](#)
logLik.brsmm, [4](#), [7](#), [15](#), [53](#)

model.matrix.brs, [50](#), [54](#)
model.matrix.brsmm, [51](#), [55](#)

nobs.brs, [56](#)
nobs.brsmm, [57](#)

optim, [18](#)

plot.brs, [9](#), [58](#), [70](#)
plot.brsmm, [59](#), [71](#)
predict.brs, [48](#), [61](#)
predict.brsmm, [49](#), [62](#)
print.brs, [63](#), [66](#)
print.brs_bootstrap (brs_bootstrap), [21](#)
print.brsmm, [64](#), [67](#)
print.brsmm_re_study, [65](#)
print.summary.brs, [63](#), [66](#), [72](#)
print.summary.brsmm, [64](#), [67](#), [73](#)

ranef, [68](#), [69](#)
ranef.brsmm, [20](#), [65](#), [68](#), [69](#)
residuals.brs, [8](#), [48](#), [58](#), [59](#), [70](#)
residuals.brsmm, [10](#), [49](#), [60](#), [71](#)

summary.brs, [27](#), [28](#), [30](#), [63](#), [66](#), [72](#)
summary.brsmm, [64](#), [67](#), [73](#)

vcov.brs, [32](#), [44](#), [47](#), [74](#)
vcov.brsmm, [45](#), [48](#), [75](#)