

Package ‘funcml’

August 22, 2026

Type Package

Title Functional Machine Learning Framework

Version 0.9.0

Depends R (>= 3.5.0)

Description A compact and explicit machine learning framework for supervised learning, resampling-based evaluation, hyperparameter tuning, learner comparison, interpretation, and plug-in g-computation. The package uses standard formulas for model specification and provides stable S3 interfaces for fitting, evaluation, tuning, interpretation, and causal estimation across a learner registry with multiple backend engines. Implemented interpretation methods build on established approaches such as permutation-based variable importance, partial dependence, individual conditional expectation, accumulated local effects, SHAP, and LIME; see Friedman (2001) <doi:10.1214/aos/1013203451>, Goldstein et al. (2015) <doi:10.1080/10618600.2014.907095>, Apley and Zhu (2020) <doi:10.1111/rssb.12377>, Lundberg and Lee (2017) <doi:10.48550/arXiv.1705.07874>, and Ribeiro et al. (2016) <doi:10.48550/arXiv.1602.04938>. The framework is intentionally opinionated: preprocessing is expected to occur outside the modeling step, and the API emphasizes explicit inputs, consistent object contracts, and compact interfaces rather than feature-by-feature competition with larger machine learning ecosystems. Plug-in g-computation follows Naimi, Cole, and Kennedy (2016) <doi:10.1093/ije/dyw323>.

License GPL-3

URL <https://CRAN.R-project.org/package=funcml>

BugReports <https://github.com/ielbadisy/funcml/issues>

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

Imports stats, utils, ggplot2, functionals, grDevices, tools,
 data.table, MASS, mgcv, nnet, rpart, glmnet, ranger, e1071,
 randomForest, gbm, C50, kkn, earth, naivebayes, mda, ada, pls,
 partykit, dbarts, torch, xgboost, lightgbm, densemlp

Suggests testthat (>= 3.1.0), knitr, rmarkdown, roxygen2, gggenes,
 ggfittext, pROC

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Imad El Badisy [aut, cre]

Maintainer Imad El Badisy <elbadisyimad@gmail.com>

Repository CRAN

Date/Publication 2026-08-22 15:10:24 UTC

Contents

funcml-package	3
arthritis	4
auc_ci	5
bangladeshmaternalrisk	6
birthweight	7
breastcancerdiagnostic	8
breastcancerwisconsin	9
cancerremission	10
cd4counts	11
cigsmoke	11
compare	13
compare-methods	14
cv	15
dca	16
dca-methods	17
doctorvisits	18
estimate	19
estimate-methods	20
evaluate	21
evaluate-methods	22
fit	23
fit-methods	24
group_cv	26
haberman	26
heartdisease	27
heartfailure	28
holdout	29
infantmortality	29
interpret	30

interpret-ale-methods	32
interpret-calibration-methods	33
interpret-ice-methods	34
interpret-interaction-methods	35
interpret-local-methods	36
interpret-local-model-methods	37
interpret-pdp-methods	38
interpret-permute-methods	39
interpret-shap-methods	40
interpret-surrogate-methods	41
ketapain	42
learners	43
list_interpretability_methods	44
list_learners	44
list_metrics	45
list_tunable_learners	46
mammography	47
metrics	47
newthyroid	50
pimadiabetes	51
roc-methods	52
roc_curve	52
theme_funcml	53
time_cv	54
tune	54
tune-methods	56
Index	58

funcml-package	<i>funcml: Functional Machine Learning Framework</i>
----------------	--

Description

A compact and explicit machine learning framework for supervised learning, resampling-based evaluation, hyperparameter tuning, learner comparison, interpretation, and plug-in g-computation. The package uses standard formulas for model specification and provides stable S3 interfaces for fitting, evaluation, tuning, interpretation, and causal estimation across a learner registry with multiple backend engines. Implemented interpretation methods build on established approaches such as permutation-based variable importance, partial dependence, individual conditional expectation, accumulated local effects, SHAP, and LIME; see Friedman (2001) [doi:10.1214/aos/1013203451](https://doi.org/10.1214/aos/1013203451), Goldstein et al. (2015) [doi:10.1080/10618600.2014.907095](https://doi.org/10.1080/10618600.2014.907095), Apley and Zhu (2020) [doi:10.1111/rssb.12377](https://doi.org/10.1111/rssb.12377), Lundberg and Lee (2017) [doi:10.48550/arXiv.1705.07874](https://doi.org/10.48550/arXiv.1705.07874), and Ribeiro et al. (2016) [doi:10.48550/arXiv.1602.04938](https://doi.org/10.48550/arXiv.1602.04938). The framework is intentionally opinionated: preprocessing is expected to occur outside the modeling step, and the API emphasizes explicit inputs, consistent object contracts, and compact interfaces rather than feature-by-feature competition with larger machine learning ecosystems. Plug-in g-computation follows Naimi, Cole, and Kennedy (2016) [doi:10.1093/ije/dyw323](https://doi.org/10.1093/ije/dyw323).

Author(s)

Maintainer: Imad El Badisy <elbadisyimad@gmail.com>

See Also

Useful links:

- <https://github.com/ielbadisy/funcml>
- Report bugs at <https://github.com/ielbadisy/funcml/issues>

arthritis

Arthritis survey data

Description

A classification dataset on arthritis status and related demographic and behavioral covariates.

Usage

arthritis

Format

A data frame with 4,856 rows and 12 variables:

id Participant identifier.

status Arthritis status ("Yes" or "No").

heart_attack_relative Whether a relative had a heart attack.

gender Participant gender.

age Participant age in years.

bmi Body mass index.

diabetes Whether the participant has diabetes.

alcohol Whether the participant reports alcohol use.

smoke Whether the participant smokes.

prehypertension Whether the participant has prehypertension.

vegetarian Whether the participant follows a vegetarian diet.

covered_health Whether the participant has health coverage.

Details

Column names were standardized to snake_case when packaging the data.

Source

Original arthritis survey dataset distributed with the project materials.

Examples

```
str(funcml::arthritis)
table(funcml::arthritis$status)
```

auc_ci	<i>AUC with a confidence interval.</i>
--------	--

Description

Computes AUC together with a confidence interval, using `pROC::ci.auc()` as the backend (DeLong by default, or bootstrap).

Usage

```
auc_ci(
  truth,
  prob,
  positive = NULL,
  conf_level = 0.95,
  method = c("delong", "bootstrap"),
  boot_n = 2000L,
  digits = 4L
)
```

Arguments

truth	Factor (or coercible to factor) of true class labels.
prob	Predicted probability of the positive class, or a probability matrix/data frame with one column per class level.
positive	Optional positive class level. Defaults to the second factor level.
conf_level	Confidence level.
method	"delong" (default, analytic) or "bootstrap".
boot_n	Number of bootstrap replicates when method = "bootstrap".
digits	Number of digits numeric columns are rounded to.

Value

A one-row data frame with auc, conf_low, conf_high, conf_level, and method.

Examples

```
if (requireNamespace("pROC", quietly = TRUE)) {
  set.seed(1)
  truth <- factor(rbinom(100, 1, 0.4))
  prob <- runif(100)
  auc_ci(truth, prob)
}
```

`bangladeshmaternalrisk`*Bangladesh maternal risk data*

Description

A classification dataset for maternal health risk level with vital signs, diabetes history, and related clinical indicators.

Usage

```
bangladeshmaternalrisk
```

Format

A data frame with 1,205 rows and 12 variables:

age Maternal age in years.

systolic_bp Systolic blood pressure.

diastolic Diastolic blood pressure.

bs Blood sugar measurement.

body_temp Body temperature.

bmi Body mass index.

previous_complications Indicator for previous pregnancy complications.

preexisting_diabetes Indicator for preexisting diabetes.

gestational_diabetes Indicator for gestational diabetes.

mental_health Indicator for mental health concerns.

heart_rate Heart rate.

risk_level Maternal risk level outcome.

Details

Column names were standardized to snake_case when packaging the data.

Source

Mojumdar MU, Sarker D, Assaduzzaman M, et al. (2025). Maternal health risk factors dataset: Clinical parameters and insights from rural Bangladesh. *Data in Brief*, 59(Suppl 2), 111363. doi:10.1016/j.dib.2025.111363.

Examples

```
str(funcml::bangladeshmaternalrisk)
table(funcml::bangladeshmaternalrisk$risk_level)
```

birthweight

Birth weight data

Description

A regression-oriented birth weight dataset with maternal risk factors and a derived low-birth-weight indicator.

Usage

```
birthweight
```

Format

A data frame with 189 rows and 10 variables:

age Maternal age in years.

lwt Maternal weight at the last menstrual period.

race Maternal race code.

smoke Smoking status indicator.

ptl Number of previous premature labors.

ht History of hypertension indicator.

ui Presence of uterine irritability indicator.

ftv Number of physician visits in the first trimester.

birth_weight_g Birth weight in grams.

low_birth_weight Low-birth-weight outcome indicator.

Source

Hosmer DW, Lemeshow S (1989). *Applied Logistic Regression*. Wiley. The packaged data are a lightly renamed version of the classic MASS::birthwt dataset.

Examples

```
str(funcml::birthweight)
summary(funcml::birthweight$birth_weight_g)
```

breastcancerdiagnostic

Breast cancer diagnostic data

Description

A binary classification dataset for breast cancer diagnosis using tumor morphology measurements.

Usage

```
breastcancerdiagnostic
```

Format

A data frame with 569 rows and 31 variables:

radius_mean Mean radius.
texture_mean Mean texture.
perimeter_mean Mean perimeter.
area_mean Mean area.
smoothness_mean Mean smoothness.
compactness_mean Mean compactness.
concavity_mean Mean concavity.
concave_pts_mean Mean number of concave points.
symmetry_mean Mean symmetry.
fractal_dim_mean Mean fractal dimension.
radius_se Radius standard error.
texture_se Texture standard error.
perimeter_se Perimeter standard error.
area_se Area standard error.
smoothness_se Smoothness standard error.
compactness_se Compactness standard error.
concavity_se Concavity standard error.
concave_pts_se Concave points standard error.
symmetry_se Symmetry standard error.
fractal_dim_se Fractal dimension standard error.
radius_worst Worst radius.
texture_worst Worst texture.
perimeter_worst Worst perimeter.
area_worst Worst area.

smoothness_worst Worst smoothness.
compactness_worst Worst compactness.
concavity_worst Worst concavity.
concave_pts_worst Worst number of concave points.
symmetry_worst Worst symmetry.
fractal_dim_worst Worst fractal dimension.
diagnosis Diagnosis outcome ("B" = benign, "M" = malignant).

Details

Column names were standardized to snake_case when packaging the data.

Source

Breast Cancer Wisconsin Diagnostic Dataset from the UCI Machine Learning Repository, packaged in `dslabs::brca`.

Examples

```
str(funcml::breastcancerdiagnostic)
table(funcml::breastcancerdiagnostic$diagnosis)
```

breastcancerwisconsin *Wisconsin breast cancer data*

Description

A binary classification dataset for breast cancer diagnosis from cytology measurements.

Usage

```
breastcancerwisconsin
```

Format

A data frame with 699 rows and 10 variables:

clump_thickness Clump thickness score.
uniformity_cell_size Uniformity of cell size score.
uniformity_cell_shape Uniformity of cell shape score.
marginal_adhesion Marginal adhesion score.
single_epithelial_cell_size Single epithelial cell size score.
bare_nuclei Bare nuclei score.
bland_chromatin Bland chromatin score.
normal_nucleoli Normal nucleoli score.
mitoses Mitoses score.
class Diagnostic class (2 = benign, 4 = malignant).

Source

Wisconsin Breast Cancer Database from University of Wisconsin Hospitals, distributed through the UCI Machine Learning Repository.

Examples

```
str(funcml::breastcancerwisconsin)
table(funcml::breastcancerwisconsin$class)
```

cancerremission	<i>Cancer remission data</i>
-----------------	------------------------------

Description

A binary classification dataset on cancer remission status using leukemia index and treatment group indicators.

Usage

```
cancerremission
```

Format

A data frame with 27 rows and 3 variables:

li Leukemia index measurement.

m Treatment group indicator.

remission Remission outcome indicator (0 = no remission, 1 = remission).

Details

Column names were standardized to snake_case when packaging the data.

Source

Davison AC, Hinkley DV (1997). *Bootstrap Methods and Their Application*. Cambridge University Press. The packaged data are from `boot::remission`.

Examples

```
str(funcml::cancerremission)
table(funcml::cancerremission$remission)
```

cd4counts	<i>CD4 follow-up data</i>
-----------	---------------------------

Description

A regression dataset relating baseline CD4 counts to one-year follow-up CD4 measurements in HIV-positive patients.

Usage

```
cd4counts
```

Format

A data frame with 20 rows and 2 variables:

baseline Baseline CD4 count.

oneyear One-year follow-up CD4 count.

Source

Davison AC, Hinkley DV (1997). *Bootstrap Methods and Their Application*. Cambridge University Press. The packaged data are from `boot::cd4`.

Examples

```
str(funcml::cd4counts)
summary(funcml::cd4counts$oneyear)
```

cigsmoke	<i>Youth tobacco survey data</i>
----------	----------------------------------

Description

A classification-oriented survey dataset on smoking exposure, tobacco use, and tobacco-related environments among youth respondents.

Usage

```
cigsmoke
```

Format

A data frame with 3,915 rows and 27 variables:

final_wgt Survey final weight.
age Age group.
gender Gender.
income Personal spending money category.
parent_work Parental work status.
father_education Father's education level.
mother_education Mother's education level.
living_env Living environment.
age_first_cig Age at first cigarette.
cigar_use Cigar use indicator.
noncig_use Non-cigarette tobacco use indicator.
smokeless_use Smokeless tobacco use indicator.
parent_smoke Parental smoking exposure.
friends_smoke Friends' smoking exposure.
home_shs Secondhand smoke exposure at home.
outside_shs Secondhand smoke exposure outside the home.
indoor_ban Indoor smoking ban indicator.
outdoor_ban Outdoor smoking ban indicator.
antitobacco_media Exposure to antitobacco media.
antitobacco_school Exposure to school antitobacco education.
tobacco_media Exposure to tobacco media.
offer_freetobacco Whether free tobacco was offered.
own_items Ownership of tobacco-branded items.
knowledge_harm Knowledge that tobacco is harmful.
e_cig Electronic cigarette use indicator.
stratum Survey stratum identifier.
psu Primary sampling unit identifier.

Details

Column names were standardized to snake_case when packaging the data.

Source

Morocco Global Youth Tobacco Survey public-use survey data.

References

Kim N, Loh WY, McCarthy DE (2021). Machine learning models of tobacco susceptibility and current use among adolescents from 97 countries in the Global Youth Tobacco Survey, 2013-2017. *PLOS Global Public Health*, 1(12), e0000060. doi:10.1371/journal.pgph.0000060.

Examples

```
str(funcml::cigsmoke)
table(funcml::cigsmoke$e_cig)
```

compare

Compare multiple learners with optional tuning.

Description

Compare multiple learners with optional tuning.

Usage

```
compare(
  data,
  formula,
  models,
  specs = NULL,
  resampling = cv(5),
  metrics = NULL,
  type = NULL,
  conf_level = 0.95,
  seed = NULL,
  ncores = NULL,
  tune = FALSE,
  grids = NULL,
  metric = NULL,
  ...
)
```

Arguments

data	Data frame.
formula	Model formula.
models	Character vector of learner ids.
specs	Optional named list of fixed specs per learner.
resampling	Resampling object from <code>cv()</code> .
metrics	Character vector of metrics to report. When <code>tune = TRUE</code> , these are computed for each learner's tuned best configuration.

type	Prediction type override.
conf_level	Confidence level for learner summary intervals.
seed	Optional seed.
ncores	Optional number of CPU cores used to compare learners. NULL or 1 runs sequentially.
tune	Logical; if TRUE, run <code>tune()</code> for each learner before comparing.
grids	Optional tuning grids. Supply either a single data frame to reuse across learners or a named list of data frames keyed by learner id.
metric	Optimization metric used when <code>tune = TRUE</code> .
...	Additional arguments passed to <code>evaluate()</code> or <code>tune()</code> / <code>fit()</code> .

Value

A `funcml_compare` object.

Examples

```
cmp <- compare(
  data = mtcars,
  formula = mpg ~ wt + hp,
  models = c("glm", "rpart"),
  resampling = cv(3, seed = 1),
  metrics = c("rmse", "mae")
)
cmp$results
```

compare-methods

Methods for learner comparison results.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_compare` objects.

Usage

```
## S3 method for class 'funcml_compare'
print(x, digits = 4L, ...)

## S3 method for class 'funcml_compare'
summary(object, digits = 4L, ...)

## S3 method for class 'funcml_compare'
plot(x, ...)
```

Arguments

<code>x</code>	A <code>funcml_compare</code> object.
<code>digits</code>	Number of digits numeric columns are rounded to when printed.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_compare</code> object.

Value

`print()` and `summary()` return the input object or results table invisibly. `plot()` returns a `ggplot2` object.

Examples

```
cmp <- compare(
  data = mtcars,
  formula = mpg ~ wt + hp,
  models = c("glm", "rpart"),
  resampling = cv(3, seed = 1),
  metrics = c("rmse", "mae")
)
print(cmp)
summary(cmp)
plot(cmp)
```

cv

Resampling specification generator.

Description

Resampling specification generator.

Usage

```
cv(
  v = 5,
  repeats = 1,
  strata = TRUE,
  seed = NULL,
  method = c("vfold", "holdout", "group_vfold", "time"),
  prop = 0.8,
  group = NULL,
  time = NULL,
  initial = NULL,
  assess = NULL,
  skip = 0,
  cumulative = TRUE
)
```

Arguments

<code>v</code>	Number of folds for cross-validation.
<code>repeats</code>	Number of repeats for standard or grouped cross-validation.
<code>strata</code>	Logical; stratify classification outcomes when supported.
<code>seed</code>	Optional seed for reproducibility.
<code>method</code>	Resampling strategy: "vfold", "holdout", "group_vfold", or "time".
<code>prop</code>	Training-set proportion for holdout splits.
<code>group</code>	Optional grouping variable name or vector for grouped CV.
<code>time</code>	Optional ordering variable name or vector for time-aware splits.
<code>initial</code>	Initial training window size for time-aware CV.
<code>assess</code>	Assessment window size for time-aware CV.
<code>skip</code>	Number of observations to skip between successive time splits.
<code>cumulative</code>	Logical; use an expanding training window for time-aware CV.

Value

A `funcml_cv` object containing fold indices and parameters.

Examples

```
cv(v = 3, repeats = 2, seed = 1)
```

dca

Decision curve analysis: net benefit.

Description

Computes net benefit across a range of risk thresholds for a binary classifier's predicted probabilities, alongside the "treat all" and "treat none" reference strategies (Vickers and Elkin, 2006).

Usage

```
dca(truth, prob, positive = NULL, thresholds = seq(0.01, 0.99, by = 0.01))
```

Arguments

<code>truth</code>	Factor (or coercible to factor) of true class labels.
<code>prob</code>	Predicted probability of the positive class, or a probability matrix/data frame with one column per class level.
<code>positive</code>	Optional positive class level. Defaults to the second factor level.
<code>thresholds</code>	Numeric vector of risk thresholds in (0, 1).

Value

A data frame with threshold, model, treat_all, and treat_none net benefit columns.

Examples

```
set.seed(1)
truth <- factor(rbinom(200, 1, 0.3))
prob <- pmin(pmax(rnorm(200, mean = ifelse(truth == 1, 0.6, 0.3), sd = 0.15), 0), 1)
dca(truth, prob)
```

dca-methods

Methods for decision curve analysis results.

Description

These provide the standard print() and plot() interfaces for funcml_dca objects returned by interpret(method = "dca").

Usage

```
## S3 method for class 'funcml_dca'
print(x, digits = 4L, ...)

## S3 method for class 'funcml_dca'
plot(x, ...)
```

Arguments

x	A funcml_dca object.
digits	Number of digits numeric columns are rounded to when printed.
...	Additional arguments (unused).

Value

print() returns the input object invisibly. plot() returns a ggplot2 object.

doctorvisits*Doctor visits data*

Description

A regression dataset on annual doctor visit counts and related health, demographic, and insurance covariates.

Usage

```
doctorvisits
```

Format

A data frame with 5,190 rows and 12 variables:

visits Number of doctor visits.

gender Recorded gender.

age Age in years scaled to decades.

income Income measure scaled by household composition.

illness Number of illnesses in the previous two weeks.

reduced Number of days with reduced activity.

health Self-rated health score.

private Private insurance indicator.

freepoor Free care indicator for low-income patients.

freerepat Free care indicator for pensioners or veterans.

nchronic Indicator for no chronic condition.

lchronic Indicator for limiting chronic condition.

Source

Cameron AC, Trivedi PK (1998). *Regression Analysis of Count Data*. Cambridge University Press. The packaged data are from AER::DoctorVisits.

Examples

```
str(funcml::doctorvisits)
summary(funcml::doctorvisits$visits)
```

estimate	<i>Causal effect estimation via plug-in g-computation.</i>
----------	--

Description

Causal effect estimation via plug-in g-computation.

Usage

```
estimate(
  data,
  formula,
  model = NULL,
  treatment = NULL,
  estimand = c("ATE", "ATT", "CATE", "IATE"),
  newdata = NULL,
  treatment_level = NULL,
  control_level = NULL,
  spec = NULL,
  type = NULL,
  interval = c("normal", "bootstrap"),
  conf_level = 0.95,
  n_boot = 200,
  seed = NULL,
  fit = NULL,
  ...
)
```

Arguments

data	Data frame.
formula	Outcome model formula. The first term on the right-hand side is treated as the treatment variable unless treatment is supplied.
model	Learner id (ignored if fit supplied).
treatment	Optional treatment variable name.
estimand	One of "ATE", "ATT", "CATE", or "IATE".
newdata	Optional target population for estimand = "CATE" or "IATE".
treatment_level	Optional treated level for binary treatment.
control_level	Optional control level for binary treatment.
spec	Hyperparameter list passed to fit().
type	Prediction type override for the outcome model.
interval	Interval method: "normal" or "bootstrap".
conf_level	Confidence level for uncertainty intervals.

<code>n_boot</code>	Number of bootstrap resamples used when <code>interval = "bootstrap"</code> .
<code>seed</code>	Optional seed.
<code>fit</code>	Optional preconfigured <code>funcml_fit</code> object.
<code>...</code>	Passed to <code>fit()</code> .

Value

A `funcml_estimand` object.

Examples

```
causal_data <- mtcars
causal_data$am <- factor(causal_data$am, labels = c("auto", "manual"))
ate <- estimate(
  data = causal_data,
  formula = mpg ~ am + wt + hp,
  model = "glm",
  treatment = "am",
  estimand = "ATE"
)
ate$estimate
```

estimate-methods

Methods for causal estimand results.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_estimand` objects.

Usage

```
## S3 method for class 'funcml_estimand'
print(x, ...)

## S3 method for class 'funcml_estimand'
summary(object, ...)

## S3 method for class 'funcml_estimand'
plot(x, style = c("outcomes", "effects"), bins = 24, alpha = 0.45, ...)
```

Arguments

<code>x</code>	A <code>funcml_estimand</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_estimand</code> object.

style	Plot style. "outcomes" shows the model-implied potential outcome distributions under treatment and control. "effects" shows the existing histogram of estimated unit-level effects.
bins	Number of bins used when style = "effects".
alpha	Fill opacity used when style = "outcomes".

Value

`print()` and `summary()` return the input object or summary table invisibly. `plot()` returns a `ggplot2` object.

Examples

```
causal_data <- mtcars
causal_data$am <- factor(causal_data$am, labels = c("auto", "manual"))
ate <- estimate(
  data = causal_data,
  formula = mpg ~ am + wt + hp,
  model = "glm",
  treatment = "am",
  estimand = "ATE"
)
print(ate)
summary(ate)
plot(ate)
```

evaluate

Cross-validated evaluation.

Description

Cross-validated evaluation.

Usage

```
evaluate(
  data,
  formula,
  model = NULL,
  spec = NULL,
  resampling = cv(5),
  metrics = NULL,
  type = NULL,
  conf_level = 0.95,
  seed = NULL,
  fit = NULL,
  ncores = NULL,
  ...
)
```

Arguments

<code>data</code>	Data frame.
<code>formula</code>	Model formula.
<code>model</code>	Learner id (ignored if <code>fit</code> supplied).
<code>spec</code>	Hyperparameter list.
<code>resampling</code>	Resampling object from <code>cv()</code> .
<code>metrics</code>	Character vector of metric names.
<code>type</code>	Prediction type override.
<code>conf_level</code>	Confidence level for fold-based summary intervals.
<code>seed</code>	Optional seed.
<code>fit</code>	Optional preconfigured <code>funcml_fit</code> object (re-fit per fold).
<code>ncores</code>	Optional number of CPU cores used to evaluate resampling folds. <code>NULL</code> or 1 runs sequentially.
<code>...</code>	Passed to <code>fit()</code> .

Value

A `funcml_eval` object.

Examples

```
eval_obj <- evaluate(
  data = mtcars,
  formula = mpg ~ wt + hp,
  model = "glm",
  resampling = cv(3, seed = 1),
  metrics = c("rmse", "mae")
)
eval_obj$summary
```

evaluate-methods

Methods for cross-validation results.

Description

These methods provide the standard `print()` and `summary()` interfaces for `funcml_eval` objects, plus a `plot()` method for fold-level diagnostics.

Usage

```
## S3 method for class 'funcml_eval'
print(x, digits = 4L, ...)

## S3 method for class 'funcml_eval'
summary(object, digits = 4L, ...)

## S3 method for class 'funcml_eval'
plot(x, ...)
```

Arguments

x	A funcml_eval object.
digits	Number of digits numeric columns are rounded to when printed.
...	Additional arguments passed to the underlying method.
object	A funcml_eval object.

Value

print() and summary() return the input object or summary table invisibly. plot() returns a ggplot2 object.

Examples

```
eval_obj <- evaluate(
  data = mtcars,
  formula = mpg ~ wt + hp,
  model = "glm",
  resampling = cv(3, seed = 1),
  metrics = c("rmse", "mae")
)
print(eval_obj)
summary(eval_obj)
plot(eval_obj)
```

fit

Fit a model using the funcml interface.

Description

Registered learner ids currently include: regression and classification: glm, rpart, glmnet, ranger, nnet, mlp, densemlp, e1071_svm, randomForest, gbm, kknn, ctree, cforest, lightgbm, xgboost, stacking, superlearner; regression plus binary classification: gam, bart; classification only: C50, naivebayes, fda, lda, qda; binary classification only: adaboost; regression plus binary classification: earth; regression only: pls.

Usage

```
fit(
  formula,
  data,
  model,
  spec = NULL,
  seed = NULL,
  na_action = stats::na.fail,
  ...
)
```

Arguments

formula	Model formula.
data	Data frame.
model	Learner id (see <code>learners()</code>).
spec	Optional list of hyperparameters for the learner.
seed	Optional seed for reproducibility.
na_action	NA handling passed to <code>model.frame/model.matrix</code> (default <code>stats::na.fail</code>).
...	Additional parameters merged into <code>spec</code> .

Details

The learner engine packages are installed with `funcml`, so the advertised registry is intended to be available after a standard installation.

Value

An object of class `funcml_fit`.

Examples

```
fit_obj <- fit(mpg ~ wt + hp, data = mtcars, model = "glm")
predict(fit_obj, newdata = mtcars[1:3, , drop = FALSE])
```

fit-methods

Methods for fitted funcml models.

Description

These methods provide the standard `print()`, `summary()`, `predict()`, and `coef()` interfaces for `funcml_fit` objects.

Usage

```
## S3 method for class 'funcml_fit'
print(x, ...)

## S3 method for class 'funcml_fit'
summary(object, ...)

## S3 method for class 'funcml_fit'
predict(
  object,
  newdata,
  type = NULL,
  class_level = NULL,
  pos_level = NULL,
  na_action = object$na_action,
  ...
)

## S3 method for class 'funcml_fit'
coef(object, ...)
```

Arguments

<code>x</code>	A <code>funcml_fit</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_fit</code> object.
<code>newdata</code>	Data frame of new observations.
<code>type</code>	Prediction type override.
<code>class_level</code>	Target class for multiclass probability predictions.
<code>pos_level</code>	Alias for the binary positive class.
<code>na_action</code>	NA handling for new data.

Value

`print()` and `summary()` return the input object invisibly. `predict()` returns predictions in the requested format. `coef()` returns a named numeric coefficient vector when available.

Examples

```
fit_obj <- fit(mpg ~ wt + hp, data = mtcars, model = "glm")
print(fit_obj)
summary(fit_obj)
predict(fit_obj, newdata = mtcars[1:3, , drop = FALSE])
coef(fit_obj)
```

group_cv	<i>Grouped cross-validation.</i>
----------	----------------------------------

Description

Grouped cross-validation.

Usage

```
group_cv(v = 5, group, repeats = 1, seed = NULL)
```

Arguments

v	Number of folds.
group	Grouping variable name or vector.
repeats	Number of repeats.
seed	Optional seed.

Value

A funcml_cv object.

Examples

```
group_cv(v = 3, group = rep(letters[1:3], each = 4), seed = 1)
```

haberman	<i>Haberman survival data</i>
----------	-------------------------------

Description

A binary classification dataset on breast cancer survival after surgery.

Usage

```
haberman
```

Format

A data frame with 306 rows and 4 variables:

age Age of patient at operation time in years.

operation_year Year of operation minus 1900.

positive_axillary_nodes Number of positive axillary nodes detected.

survival_status Survival status (1 = survived 5 years or longer, 2 = died within 5 years).

Source

Haberman's Survival Data from the University of Chicago's Billings Hospital study, distributed through the UCI Machine Learning Repository.

Examples

```
str(funcml::haberman)
table(funcml::haberman$survival_status)
```

heartdisease	<i>Heart disease patient data</i>
--------------	-----------------------------------

Description

A binary classification dataset on heart disease status using demographic and clinical risk factors.

Usage

```
heartdisease
```

Format

A data frame with 303 rows and 9 variables:

age Age in years.

sex Recorded sex.

chest_pain Chest pain type.

bp Resting blood pressure.

cholesterol Serum cholesterol measurement.

blood_sugar High fasting blood sugar indicator.

maximum_hr Maximum heart rate achieved.

exercise_induced_angina Exercise-induced angina indicator.

heart_disease Heart disease outcome ("Yes" or "No").

Details

Column names were standardized to snake_case when packaging the data.

Source

CardioDataSets package dataset CardioDataSets::heartdisease_tbl_df.

Examples

```
str(funcml::heartdisease)
table(funcml::heartdisease$heart_disease)
```

heartfailure	<i>Heart failure data</i>
--------------	---------------------------

Description

A binary classification dataset on heart failure mortality using demographic, laboratory, and clinical covariates.

Usage

```
heartfailure
```

Format

A data frame with 299 rows and 13 variables:

age Age in years.

anaemia Anaemia indicator.

creatinine_phosphokinase Creatinine phosphokinase level.

diabetes Diabetes indicator.

ejection_fraction Ejection fraction percentage.

high_blood_pressure High blood pressure indicator.

platelets Platelet count.

serum_creatinine Serum creatinine level.

serum_sodium Serum sodium level.

sex Sex indicator.

smoking Smoking indicator.

time Follow-up time.

death_event Death event outcome indicator (0 = no event, 1 = death).

Details

Column names were standardized to snake_case when packaging the data.

Source

CardioDataSets package dataset CardioDataSets::cardiac_failure_df.

Examples

```
str(funcml::heartfailure)
table(funcml::heartfailure$death_event)
```

holdout	<i>Plain holdout resampling.</i>
---------	----------------------------------

Description

Plain holdout resampling.

Usage

```
holdout(prop = 0.8, strata = TRUE, seed = NULL)
```

Arguments

prop	Training-set proportion.
strata	Logical; stratify classification outcomes.
seed	Optional seed.

Value

A `funcml_cv` object.

Examples

```
holdout(prop = 0.75, seed = 1)
```

infantmortality	<i>Infant mortality data</i>
-----------------	------------------------------

Description

A regression dataset on infant mortality with country-level income, region, and oil-export status covariates.

Usage

```
infantmortality
```

Format

A data frame with 105 rows and 5 variables:

country	Country name.
income	Per-capita income.
infant	Infant mortality rate.
region	Geographic region.
oil	Oil-exporting country indicator.

Details

Column names were standardized to snake_case when packaging the data.

Source

Fox J, Weisberg S (2019). *An R Companion to Applied Regression*. Sage. The packaged data are from `carData::Leinhardt`.

Examples

```
str(funcml::infantmortality)
summary(funcml::infantmortality$infant)
```

interpret	<i>Model-agnostic interpretation (global + local).</i>
-----------	--

Description

Implements native permutation VI, PDP/ICE/ALE, SHAP approximations, local surrogate explanations, interaction strength, and global surrogate models.

Usage

```
interpret(
  fit,
  data,
  formula = fit$formula,
  method = c("vip", "permute", "pdp", "ice", "ale", "local", "lime", "shap",
    "local_model", "interaction", "surrogate", "profile", "ceteris_paribus",
    "calibration", "dca"),
  features = NULL,
  type = NULL,
  metric = NULL,
  importance_type = c("permute", "model", "auto"),
  compare = c("difference", "ratio"),
  keep = TRUE,
  k = NULL,
  gower_power = NULL,
  class_level = NULL,
  pos_level = NULL,
  newdata = NULL,
  nsim = NULL,
  nsamples = NULL,
  grid = NULL,
  seed = NULL,
  bins = 10,
  strategy = c("quantile", "uniform"),
```

```

    ncores = NULL,
    ...
)

```

Arguments

<code>fit</code>	A <code>funcml_fit</code> object.
<code>data</code>	Reference data (typically training set).
<code>formula</code>	Optional formula (defaults to <code>fit\$formula</code>).
<code>method</code>	One of "vip", "permute", "pdp", "ice", "ale", "local", "lime", "shap", "local_model", "interaction", "surrogate", "ceteris_paribus", or "calibration".
<code>features</code>	Optional subset of features; defaults to all predictors.
<code>type</code>	Prediction scale: regression -> "response"; classification -> "prob" or "class".
<code>metric</code>	Loss/score for importance (reg: rmse/mae/mse/medae/mape/rsq; cls: accuracy/precision/recall/specificity)
<code>importance_type</code>	Importance engine for method = "vip". Internal permutation importance is always used; accepted values are retained only for backward-compatible argument parsing.
<code>compare</code>	How to compare baseline and perturbed performance for importance: "difference" or "ratio".
<code>keep</code>	Keep per-repetition raw importance scores when <code>nsim > 1</code> .
<code>k</code>	Sparsity target for local surrogate fits (method = "local", "local_model", or "lime").
<code>gower_power</code>	Exponent applied to native similarity weights when constructing the local neighborhood.
<code>class_level</code>	Target class for multiclass/local prob explanations.
<code>pos_level</code>	Alias for binary positive class (second level default).
<code>newdata</code>	Single-row data frame for local/SHAP explanations; defaults to first row of data.
<code>nsim</code>	Number of Monte Carlo simulations (importance/SHAP) or repetitions.
<code>nsamples</code>	Row subsample for speed (reference/background set).
<code>grid</code>	Optional list of grids per feature for PDP/ICE/ALE.
<code>seed</code>	Optional seed for determinism.
<code>bins</code>	Number of bins for calibration diagnostics.
<code>strategy</code>	Binning strategy for calibration diagnostics.
<code>ncores</code>	Optional number of CPU cores used to parallelize the per-observation SHAP computation (method = "shap"). NULL or 1 runs sequentially. Ignored by other methods, and ignored (with a warning) for <code>xgboost</code> , <code>lightgbm</code> , <code>mlp</code> , <code>densemlp</code> , and <code>bart</code> fits on Unix, since reusing their fitted state across a forked process is unsafe.
<code>...</code>	Additional method-specific args.

Value

An interpretation object whose class depends on method. Returned objects contain computed explanation values and metadata used for printing, summarizing, and plotting.

Examples

```
fit_obj <- fit(
  mpg ~ wt + hp + disp,
  data = mtcars,
  model = "rpart",
  spec = list(cp = 0.01, minsplit = 5)
)
vi <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "permute",
  features = c("wt", "hp"),
  nsim = 2,
  metric = "rmse"
)
vi$result$scores
```

interpret-ale-methods *ALE result methods.*

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_ale` objects returned by `interpret(method = "ale")`.

Usage

```
## S3 method for class 'funcml_ale'
plot(x, ...)

## S3 method for class 'funcml_ale'
print(x, ...)

## S3 method for class 'funcml_ale'
summary(object, ...)
```

Arguments

<code>x</code>	A <code>funcml_ale</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_ale</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns the ALE curve table invisibly.

Examples

```
fit_obj <- fit(mpg ~ wt + hp + disp, data = mtcars, model = "rpart",
  spec = list(cp = 0.01, minsplit = 5))
ale <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "ale",
  features = c("wt", "hp"),
  nsamples = 20
)
print(ale)
summary(ale)
plot(ale)
```

 interpret-calibration-methods

Calibration result methods.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_calibration` objects returned by `interpret(method = "calibration")`.

Usage

```
## S3 method for class 'funcml_calibration'
plot(x, style = c("curve", "histogram"), ...)

## S3 method for class 'funcml_calibration'
print(x, digits = 4L, ...)

## S3 method for class 'funcml_calibration'
summary(object, digits = 4L, ...)
```

Arguments

<code>x</code>	A <code>funcml_calibration</code> object.
<code>style</code>	Plot style: "curve" or "histogram".
<code>...</code>	Additional arguments passed to the underlying method.
<code>digits</code>	Number of digits numeric columns are rounded to when printed.
<code>object</code>	A <code>funcml_calibration</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns a list with calibration curve and summary diagnostics invisibly.

Examples

```
fit_obj <- fit(mpg > 20 ~ wt + hp + disp, data = mtcars, model = "glm")
cal <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "calibration"
)
print(cal)
summary(cal)
plot(cal)
```

interpret-ice-methods *ICE result methods.*

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_ice` objects returned by `interpret(method = "ice")` or `interpret(method = "ceteris_paribus")`.

Usage

```
## S3 method for class 'funcml_ice'
plot(x, ...)

## S3 method for class 'funcml_ice'
print(x, ...)

## S3 method for class 'funcml_ice'
summary(object, ...)
```

Arguments

<code>x</code>	A <code>funcml_ice</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_ice</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns the ICE curve table invisibly.

Examples

```
fit_obj <- fit(mpg ~ wt + hp + disp, data = mtcars, model = "rpart",
  spec = list(cp = 0.01, minsplit = 5))
ice <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "ice",
  features = c("wt", "hp"),
  nsamples = 20
)
print(ice)
summary(ice)
plot(ice)
```

interpret-interaction-methods

Interaction result methods.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_interaction` objects returned by `interpret(method = "interaction")`.

Usage

```
## S3 method for class 'funcml_interaction'
plot(x, ...)

## S3 method for class 'funcml_interaction'
print(x, ...)

## S3 method for class 'funcml_interaction'
summary(object, ...)
```

Arguments

<code>x</code>	A <code>funcml_interaction</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_interaction</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns the interaction summary table invisibly.

Examples

```

fit_obj <- fit(mpg ~ wt + hp + disp, data = mtcars, model = "rpart",
  spec = list(cp = 0.01, minsplitted = 5))
interaction_obj <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "interaction",
  features = c("wt", "hp"),
  nsamples = 20,
  grid_size = 5
)
print(interaction_obj)
summary(interaction_obj)
plot(interaction_obj)

```

interpret-local-methods

Local surrogate result methods.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_local` objects returned by `interpret(method = "local")` or `interpret(method = "lime")`.

Usage

```

## S3 method for class 'funcml_local'
plot(x, ...)

## S3 method for class 'funcml_local'
print(x, ...)

## S3 method for class 'funcml_local'
summary(object, ...)

```

Arguments

<code>x</code>	A <code>funcml_local</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_local</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns the local explanation payload invisibly.

Examples

```

fit_obj <- fit(mpg ~ wt + hp + disp, data = mtcars, model = "rpart",
  spec = list(cp = 0.01, minsplit = 5))
local_obj <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "local",
  newdata = mtcars[1, , drop = FALSE],
  k = 2
)
print(local_obj)
summary(local_obj)
plot(local_obj)

```

interpret-local-model-methods

Local surrogate result methods for local_model and lime.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_uml_local_model` objects returned by `interpret(method = "local_model")` or `interpret(method = "lime")`.

Usage

```

## S3 method for class 'funcml_uml_local_model'
plot(x, ...)

## S3 method for class 'funcml_lime'
plot(x, ...)

## S3 method for class 'funcml_uml_local_model'
print(x, ...)

## S3 method for class 'funcml_uml_local_model'
summary(object, ...)

```

Arguments

<code>x</code>	A <code>funcml_uml_local_model</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_uml_local_model</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns the local model explanation payload invisibly.

Examples

```

fit_obj <- fit(mpg ~ wt + hp + disp, data = mtcars, model = "rpart",
  spec = list(cp = 0.01, minsplit = 5))
local_model <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "local_model",
  newdata = mtcars[1, , drop = FALSE],
  k = 2
)
print(local_model)
summary(local_model)
plot(local_model)

```

interpret-pdp-methods *Partial dependence result methods.*

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_pdp` objects returned by `interpret(method = "pdp")`.

Usage

```

## S3 method for class 'funcml_pdp'
plot(x, ...)

## S3 method for class 'funcml_pdp'
print(x, ...)

## S3 method for class 'funcml_pdp'
summary(object, ...)

```

Arguments

<code>x</code>	A <code>funcml_pdp</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_pdp</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns the partial dependence table invisibly.

Examples

```
fit_obj <- fit(mpg ~ wt + hp + disp, data = mtcars, model = "rpart",
  spec = list(cp = 0.01, minsplit = 5))
pdp <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "pdp",
  features = c("wt", "hp"),
  nsamples = 20
)
print(pdp)
summary(pdp)
plot(pdp)
```

interpret-permute-methods

Permutation importance result methods.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_permute` objects returned by `interpret(method = "permute")`.

Usage

```
## S3 method for class 'funcml_permute'
plot(x, ...)

## S3 method for class 'funcml_permute'
print(x, ...)

## S3 method for class 'funcml_permute'
summary(object, ...)
```

Arguments

<code>x</code>	A <code>funcml_permute</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_permute</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns the permutation importance table invisibly.

Examples

```
fit_obj <- fit(mpg ~ wt + hp + disp, data = mtcars, model = "rpart",
  spec = list(cp = 0.01, minsplit = 5))
perm <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "permute",
  features = c("wt", "hp"),
  nsim = 1,
  metric = "rmse"
)
print(perm)
summary(perm)
plot(perm)
```

interpret-shap-methods

SHAP result methods.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_shap` objects returned by `interpret(method = "shap")`.

Usage

```
## S3 method for class 'funcml_shap'
plot(
  x,
  kind = c("auto", "waterfall", "force", "summary", "beeswarm", "importance", "bar",
    "dependence", "dependence2d", "interaction"),
  ...
)

## S3 method for class 'funcml_shap'
print(x, ...)

## S3 method for class 'funcml_shap'
summary(object, ...)
```

Arguments

<code>x</code>	A <code>funcml_shap</code> object.
<code>kind</code>	Plot kind. One of "auto", "waterfall", "force", "summary", "beeswarm", "importance", "bar", "dependence", "dependence2d", or "interaction".
<code>...</code>	Additional arguments passed to the underlying method. For <code>kind = "summary"/"beeswarm"</code> , <code>v</code> restricts the plot to a single feature (default: all interpreted features).
<code>object</code>	A <code>funcml_shap</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns the SHAP contribution table invisibly.

Examples

```
fit_obj <- fit(mpg ~ wt + hp + disp, data = mtcars, model = "rpart",
  spec = list(cp = 0.01, minsplit = 5))
shap <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "shap",
  newdata = mtcars[1, , drop = FALSE],
  nsim = 1
)
print(shap)
summary(shap)
plot(shap)
```

interpret-surrogate-methods

Global surrogate result methods.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_surrogate` objects returned by `interpret(method = "surrogate")`.

Usage

```
## S3 method for class 'funcml_surrogate'
plot(x, ...)

## S3 method for class 'funcml_surrogate'
print(x, ...)

## S3 method for class 'funcml_surrogate'
summary(object, ...)
```

Arguments

<code>x</code>	A <code>funcml_surrogate</code> object.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_surrogate</code> object.

Value

`plot()` returns a `ggplot2` object. `print()` returns the input object invisibly. `summary()` returns the surrogate model summary object invisibly.

Examples

```
fit_obj <- fit(mpg ~ wt + hp + disp, data = mtcars, model = "rpart",
  spec = list(cp = 0.01, minsplit = 5))
surrogate <- interpret(
  fit = fit_obj,
  data = mtcars,
  method = "surrogate"
)
print(surrogate)
summary(surrogate)
plot(surrogate)
```

ketapain

*Ketamine pain management data***Description**

A regression dataset on ketamine dosing, treatment characteristics, cost, quality-adjusted life years, and administration mode.

Usage

```
ketapain
```

Format

A data frame with 184 rows and 11 variables:

patient_id Patient identifier.

sexe Recorded sex.

age Patient age in years.

av_dose Average dose.

level_dose Dose level category.

cum_dose Cumulative dose.

cum_days Cumulative treatment days.

perfusion Perfusion duration.

cost Treatment cost.

qaly Quality-adjusted life years.

mode Administration mode.

Details

Column names were standardized to snake_case when packaging the data.

Source

Original ketamine pain management dataset distributed with the project materials.

Examples

```
str(funcml::ketapain)
summary(funcml::ketapain$qaly)
```

learners	<i>Available learners.</i>
----------	----------------------------

Description

learners() returns the registry keys accepted by `fit()`. Task support is: regression and classification: glm, rpart, glmnet, ranger, nnet, mlp, densemlp, e1071_svm, randomForest, gbm, kkn, ctree, cforest, lightgbm, xgboost, stacking, superlearner; regression plus binary classification: gam, bart, earth; classification only: C50, naivebayes, fda, lda, qda; binary classification only: adaboost; regression only: pls.

Usage

```
learners()
```

Details

The learner engine packages are installed with funcml, so the advertised registry is intended to be available after a standard installation.

Value

Character vector of learner ids.

Examples

```
learners()
```

```
list_interpretability_methods
```

List available interpretability methods.

Description

Returns a compact catalog of `interpret()` entry points and whether each method has a corresponding `plot()` method.

Usage

```
list_interpretability_methods(has_plot = NULL, columns = NULL)
```

Arguments

`has_plot` Optional logical filter for methods with plot support.
`columns` Optional character vector of columns to return.

Value

Data frame of interpretability methods.

Examples

```
list_interpretability_methods()
subset(list_interpretability_methods(), has_plot)
```

```
list_learners
```

Learner inventory table with capabilities.

Description

`list_learners()` returns a compact learner registry in the style of a catalog table. By default it focuses on the most user-visible columns: learner id, generic fit/predict/tune entry points, and availability in the current session.

Usage

```
list_learners(
  has_fit = NULL,
  has_predict = NULL,
  has_tune = NULL,
  available = NULL,
  columns = NULL,
  regression = NULL,
  classification = NULL,
```

```

    prob = NULL,
    multiclass = NULL,
    importance = NULL,
    tune = NULL
  )

```

Arguments

has_fit	Optional logical filter for fit support.
has_predict	Optional logical filter for predict support.
has_tune	Optional logical filter for tuning support.
available	Optional logical filter for engine availability in the current session.
columns	Optional character vector of columns to return.
regression	Optional logical filter for regression support.
classification	Optional logical filter for classification support.
prob	Optional logical filter for probability support.
multiclass	Optional logical filter for multiclass support.
importance	Optional logical filter for feature-importance support.
tune	Deprecated alias for has_tune.

Details

Additional capability metadata remains available through `columns =`.

Value

Data frame with learner metadata and capability columns.

Examples

```

list_learners()
list_learners(has_tune = TRUE)
list_tunable_learners()
list_learners(classification = TRUE, prob = TRUE,
               columns = c("learner", "has_tune", "supports_prob", "engine_package"))

```

list_metrics	<i>List available metrics used in scoring and resampling summaries.</i>
--------------	---

Description

List available metrics used in scoring and resampling summaries.

Usage

```
list_metrics(direction = NULL, columns = NULL)
```

Arguments

direction	Optional character filter: "maximize" or "minimize".
columns	Optional character vector of columns to return.

Value

Data frame of metric metadata.

Examples

```
list_metrics()
list_metrics(direction = "minimize")
```

`list_tunable_learners` *Shortcut for learners with tuning support.*

Description

Shortcut for learners with tuning support.

Usage

```
list_tunable_learners(...)
```

Arguments

... Passed to `list_learners()`.

Value

Data frame with the same columns as `list_learners()`.

Examples

```
list_tunable_learners()
```

mammography

Mammography calcification data

Description

A binary classification dataset for detection of mammographic microcalcifications.

Usage

mammography

Format

A data frame with 11,183 rows and 7 variables:

attr1 Numeric imaging-derived predictor 1.

attr2 Numeric imaging-derived predictor 2.

attr3 Numeric imaging-derived predictor 3.

attr4 Numeric imaging-derived predictor 4.

attr5 Numeric imaging-derived predictor 5.

attr6 Numeric imaging-derived predictor 6.

class Calcification class (\"-1\" or \"1\").

Source

Woods K, Doss C, Bowyer K, Solka J, Priebe C, Kegelmeyer P (1993). Comparative evaluation of pattern recognition techniques for detection of microcalcifications in mammography.

Examples

```
str(funcml::mammography)
table(funcml::mammography$class)
```

metrics

Regression and classification metrics.

Description

Base R implementations used across evaluation and interpretation utilities.

Usage

```
rmse(truth, pred)

mae(truth, pred)

mse(truth, pred)

rsq(truth, pred)

medae(truth, pred)

mape(truth, pred)

logloss(truth, prob_matrix)

brier(truth, prob_matrix)

accuracy(truth, pred_class)

precision(truth, pred_class)

recall(truth, pred_class)

specificity(truth, pred_class)

f1(truth, pred_class)

balanced_accuracy(truth, pred_class)

auc(truth, prob, average = c("macro", "weighted"))

auc_weighted(truth, prob)

calibration_curve(
  truth,
  prob,
  bins = 10,
  strategy = c("quantile", "uniform"),
  positive = NULL
)

ece(
  truth,
  prob,
  bins = 10,
  strategy = c("quantile", "uniform"),
  positive = NULL
)
```

```

mce(
  truth,
  prob,
  bins = 10,
  strategy = c("quantile", "uniform"),
  positive = NULL
)

```

Arguments

<code>truth</code>	Observed outcomes.
<code>pred</code>	Predicted numeric values or class labels.
<code>prob_matrix</code>	Matrix or vector of predicted probabilities (classification).
<code>pred_class</code>	Predicted class labels (classification).
<code>prob</code>	Probability vector (binary) or probability matrix with one column per class (multiclass).
<code>average</code>	For multiclass AUC, aggregation mode: "macro" or "weighted" (class-frequency weighted one-vs-rest AUC). Ignored for binary AUC.
<code>bins</code>	Number of bins for calibration summaries.
<code>strategy</code>	Binning strategy: "quantile" or "uniform".
<code>positive</code>	Optional positive/event class for binary classification.

Value

Numeric scalar metric.

Examples

```

truth_reg <- c(3, 5, 2.5, 7)
pred_reg <- c(2.8, 4.9, 2.7, 6.8)
rmse(truth_reg, pred_reg)
mae(truth_reg, pred_reg)
mse(truth_reg, pred_reg)
rsq(truth_reg, pred_reg)
medae(truth_reg, pred_reg)
mape(truth_reg, pred_reg)

truth_cls <- factor(c("no", "yes", "yes", "no"), levels = c("no", "yes"))
pred_cls <- factor(c("no", "yes", "no", "no"), levels = levels(truth_cls))
prob_cls <- cbind(
  no = c(0.8, 0.2, 0.6, 0.7),
  yes = c(0.2, 0.8, 0.4, 0.3)
)
logloss(truth_cls, prob_cls)
brier(truth_cls, prob_cls)
accuracy(truth_cls, pred_cls)
precision(truth_cls, pred_cls)

```

```

recall(truth_cls, pred_cls)
specificity(truth_cls, pred_cls)
f1(truth_cls, pred_cls)
balanced_accuracy(truth_cls, pred_cls)
auc(truth_cls, prob_cls[, "yes"])

truth_multi <- factor(c("a", "b", "c", "a", "b", "c"), levels = c("a", "b", "c"))
prob_multi <- rbind(
  c(0.90, 0.05, 0.05),
  c(0.05, 0.90, 0.05),
  c(0.05, 0.05, 0.90),
  c(0.85, 0.10, 0.05),
  c(0.10, 0.80, 0.10),
  c(0.05, 0.10, 0.85)
)
colnames(prob_multi) <- levels(truth_multi)
auc(truth_multi, prob_multi)
auc_weighted(truth_multi, prob_multi)
calibration_curve(truth_cls, prob_cls[, "yes"])
ece(truth_cls, prob_cls[, "yes"])
mce(truth_cls, prob_cls[, "yes"])

```

newthyroid

*Thyroid function data***Description**

A multiclass classification dataset on thyroid functional state using five laboratory test measurements.

Usage

```
newthyroid
```

Format

A data frame with 215 rows and 6 variables:

t3_resin_uptake T3-resin uptake percentage.

total_serum_thyroxin Total serum thyroxin measurement.

total_serum_triiodothyronine Total serum triiodothyronine measurement.

basal_tsh Basal thyroid-stimulating hormone measurement.

max_abs_tsh_diff Maximum absolute TSH difference after thyrotropin- releasing hormone injection.

class Thyroid class (1 = normal, 2 = hyperthyroid, 3 = hypothyroid).

Source

Thyroid gland data distributed through the UCI Machine Learning Repository.

Examples

```
str(funcml::newthyroid)
table(funcml::newthyroid$class)
```

pimadiabetes	<i>Pima diabetes data</i>
--------------	---------------------------

Description

A diabetes classification dataset with clinical measurements and a predefined train/test split column.

Usage

```
pimadiabetes
```

Format

A data frame with 532 rows and 9 variables:

npreg Number of pregnancies.
glu Plasma glucose concentration.
bp Diastolic blood pressure.
skin Triceps skin fold thickness.
bmi Body mass index.
ped Diabetes pedigree function.
age Age in years.
diabetes Diabetes outcome ("Yes" or "No").
split Suggested split indicator ("train" or "test").

Source

National Institute of Diabetes and Digestive and Kidney Diseases Pima Indians Diabetes Database.

References

Smith JW, Everhart JE, Dickson WC, Knowler WC, Johannes RS (1988). Using the ADAP learning algorithm to forecast the onset of diabetes mellitus. In *Proceedings of the Annual Symposium on Computer Application in Medical Care*, 261-265.

Examples

```
str(funcml::pimadiabetes)
table(funcml::pimadiabetes$split)
```

roc-methods

*Methods for ROC curve results.***Description**

Methods for ROC curve results.

Usage

```
## S3 method for class 'funcml_roc'
print(x, digits = 4L, ...)

## S3 method for class 'funcml_roc'
plot(x, ...)
```

Arguments

x	A funcml_roc object.
digits	Number of digits numeric columns are rounded to when printed.
...	Additional arguments (unused).

Value

print() returns the input object invisibly. plot() returns a ggplot2 object.

roc_curve

*ROC curve.***Description**

Computes the receiver operating characteristic curve for binary classification predictions, using [pROC::roc\(\)](#) as the backend.

Usage

```
roc_curve(truth, prob, positive = NULL)
```

Arguments

truth	Factor (or coercible to factor) of true class labels.
prob	Predicted probability of the positive class, or a probability matrix/data frame with one column per class level.
positive	Optional positive class level. Defaults to the second factor level.

Value

A funcml_roc object: a list with a curve data frame (threshold, sensitivity, specificity), the AUC, and the underlying pROC::roc object (proc).

Examples

```
if (requireNamespace("pROC", quietly = TRUE)) {
  set.seed(1)
  truth <- factor(rbinom(100, 1, 0.4))
  prob <- runif(100)
  roc_obj <- roc_curve(truth, prob)
  roc_obj$curve
}
```

theme_funcml	<i>FuncML plotting theme.</i>
--------------	-------------------------------

Description

A custom ggplot2 theme used across funcml plots, built on theme_classic() with an Okabe-Ito colorblind-safe palette. It keeps a clean background, restrained grid lines, and high-contrast labels so package figures remain consistent and publication-friendly.

Usage

```
theme_funcml(base_size = 10)
```

Arguments

base_size Base text size passed to the theme.

Value

A ggplot2 theme object.

Examples

```
ggplot2::ggplot(mtcars, ggplot2::aes(wt, mpg)) +
  ggplot2::geom_point() +
  theme_funcml()
```

time_cv	<i>Time-aware rolling resampling.</i>
---------	---------------------------------------

Description

Time-aware rolling resampling.

Usage

```
time_cv(
  initial,
  assess = 1,
  time = NULL,
  skip = 0,
  cumulative = TRUE,
  seed = NULL
)
```

Arguments

initial	Initial training window size.
assess	Assessment window size.
time	Ordering variable name or vector.
skip	Number of observations to skip between splits.
cumulative	Logical; use an expanding training window.
seed	Optional seed.

Value

A `funcml_cv` object.

Examples

```
time_cv(initial = 8, assess = 2, skip = 1)
```

tune	<i>Hyperparameter tuning via grid or random search.</i>
------	---

Description

Hyperparameter tuning via grid or random search.

Usage

```
tune(
  data,
  formula,
  model,
  grid,
  resampling = cv(5),
  metric = NULL,
  type = NULL,
  search = c("grid", "random"),
  n_evals = NULL,
  outer_resampling = NULL,
  seed = NULL,
  ncores = NULL,
  ...
)
```

Arguments

<code>data</code>	Data frame.
<code>formula</code>	Model formula.
<code>model</code>	Learner id.
<code>grid</code>	Data frame of hyperparameter combinations.
<code>resampling</code>	Resampling object.
<code>metric</code>	Metric to optimize.
<code>type</code>	Prediction type override.
<code>search</code>	Search strategy: "grid" or "random".
<code>n_evals</code>	Maximum number of configurations to evaluate when <code>search = "random"</code> .
<code>outer_resampling</code>	Optional outer resampling object. When supplied, <code>tune()</code> performs nested resampling and reports outer-fold performance estimates for the tuned model-selection procedure.
<code>seed</code>	Optional seed.
<code>ncores</code>	Optional number of CPU cores used for tuning tasks. <code>NULL</code> or <code>1</code> runs sequentially.
<code>...</code>	Passed to <code>fit()</code> .

Value

A `funcml_tune` object.

Examples

```
tune_obj <- tune(
  data = mtcars,
  formula = mpg ~ wt + hp,
  model = "rpart",
  grid = expand.grid(cp = c(0.001, 0.01), minsplit = c(5, 10)),
  resampling = cv(3, seed = 1),
  metric = "rmse"
)
tune_obj$best
```

tune-methods

Methods for tuning results.

Description

These methods provide the standard `print()`, `summary()`, and `plot()` interfaces for `funcml_tune` objects.

Usage

```
## S3 method for class 'funcml_tune'
print(x, digits = 4L, ...)

## S3 method for class 'funcml_tune'
summary(object, digits = 4L, ...)

## S3 method for class 'funcml_tune'
plot(x, ...)
```

Arguments

<code>x</code>	A <code>funcml_tune</code> object.
<code>digits</code>	Number of digits numeric columns are rounded to when printed.
<code>...</code>	Additional arguments passed to the underlying method.
<code>object</code>	A <code>funcml_tune</code> object.

Value

`print()` and `summary()` return the input object or results table invisibly. `plot()` returns a `ggplot2` object.

Examples

```
tune_obj <- tune(  
  data = mtcars,  
  formula = mpg ~ wt + hp,  
  model = "rpart",  
  grid = expand.grid(cp = c(0.001, 0.01), minsplit = c(5, 10)),  
  resampling = cv(3, seed = 1),  
  metric = "rmse"  
)  
print(tune_obj)  
summary(tune_obj)  
plot(tune_obj)
```

Index

* datasets

- arthritis, [4](#)
- bangladeshmaternalrisk, [6](#)
- birthweight, [7](#)
- breastcancerdiagnostic, [8](#)
- breastcancerwisconsin, [9](#)
- cancerremission, [10](#)
- cd4counts, [11](#)
- cigsmoke, [11](#)
- doctorvisits, [18](#)
- haberman, [26](#)
- heartdisease, [27](#)
- heartfailure, [28](#)
- infantmortality, [29](#)
- ketapain, [42](#)
- mammography, [47](#)
- newthyroid, [50](#)
- pimadiabetes, [51](#)

accuracy (metrics), [47](#)

arthritis, [4](#)

auc (metrics), [47](#)

auc_ci, [5](#)

auc_weighted (metrics), [47](#)

balanced_accuracy (metrics), [47](#)

bangladeshmaternalrisk, [6](#)

birthweight, [7](#)

breastcancerdiagnostic, [8](#)

breastcancerwisconsin, [9](#)

brier (metrics), [47](#)

calibration_curve (metrics), [47](#)

cancerremission, [10](#)

cd4counts, [11](#)

cigsmoke, [11](#)

coef.funcml_fit (fit-methods), [24](#)

compare, [13](#)

compare-methods, [14](#)

cv, [15](#)

dca, [16](#)

dca-methods, [17](#)

doctorvisits, [18](#)

ece (metrics), [47](#)

estimate, [19](#)

estimate-methods, [20](#)

evaluate, [21](#)

evaluate-methods, [22](#)

f1 (metrics), [47](#)

fit, [23](#)

fit(), [43](#)

fit-methods, [24](#)

funcml (funcml-package), [3](#)

funcml-package, [3](#)

group_cv, [26](#)

haberman, [26](#)

heartdisease, [27](#)

heartfailure, [28](#)

holdout, [29](#)

infantmortality, [29](#)

interpret, [30](#)

interpret-ale-methods, [32](#)

interpret-calibration-methods, [33](#)

interpret-ice-methods, [34](#)

interpret-interaction-methods, [35](#)

interpret-local-methods, [36](#)

interpret-local-model-methods, [37](#)

interpret-pdp-methods, [38](#)

interpret-permute-methods, [39](#)

interpret-shap-methods, [40](#)

interpret-surrogate-methods, [41](#)

ketapain, [42](#)

learners, [43](#)

list_interpretability_methods, [44](#)

- `list_learners`, 44
- `list_learners()`, 46
- `list_metrics`, 45
- `list_tunable_learners`, 46
- `logloss (metrics)`, 47
-
- `mae (metrics)`, 47
- `mammography`, 47
- `mape (metrics)`, 47
- `mce (metrics)`, 47
- `medae (metrics)`, 47
- `metrics`, 47
- `mse (metrics)`, 47
-
- `newthyroid`, 50
-
- `pimadiabetes`, 51
- `plot.funcml_ale`
 - (interpret-ale-methods), 32
- `plot.funcml_calibration`
 - (interpret-calibration-methods), 33
- `plot.funcml_compare (compare-methods)`, 14
- `plot.funcml_dca (dca-methods)`, 17
- `plot.funcml_estimand`
 - (estimate-methods), 20
- `plot.funcml_eval (evaluate-methods)`, 22
- `plot.funcml_ice`
 - (interpret-ice-methods), 34
- `plot.funcml_isml_local_model`
 - (interpret-local-model-methods), 37
- `plot.funcml_interaction`
 - (interpret-interaction-methods), 35
- `plot.funcml_isml`
 - (interpret-local-model-methods), 37
- `plot.funcml_local`
 - (interpret-local-methods), 36
- `plot.funcml_pdp`
 - (interpret-pdp-methods), 38
- `plot.funcml_permute`
 - (interpret-permute-methods), 39
- `plot.funcml_roc (roc-methods)`, 52
- `plot.funcml_shap`
 - (interpret-shap-methods), 40
-
- `plot.funcml_surrogate`
 - (interpret-surrogate-methods), 41
- `plot.funcml_tune (tune-methods)`, 56
- `precision (metrics)`, 47
- `predict.funcml_fit (fit-methods)`, 24
- `print.funcml_ale`
 - (interpret-ale-methods), 32
- `print.funcml_calibration`
 - (interpret-calibration-methods), 33
- `print.funcml_compare (compare-methods)`, 14
- `print.funcml_dca (dca-methods)`, 17
- `print.funcml_estimand`
 - (estimate-methods), 20
- `print.funcml_eval (evaluate-methods)`, 22
- `print.funcml_fit (fit-methods)`, 24
- `print.funcml_ice`
 - (interpret-ice-methods), 34
- `print.funcml_isml_local_model`
 - (interpret-local-model-methods), 37
- `print.funcml_interaction`
 - (interpret-interaction-methods), 35
- `print.funcml_local`
 - (interpret-local-methods), 36
- `print.funcml_pdp`
 - (interpret-pdp-methods), 38
- `print.funcml_permute`
 - (interpret-permute-methods), 39
- `print.funcml_roc (roc-methods)`, 52
- `print.funcml_shap`
 - (interpret-shap-methods), 40
- `print.funcml_surrogate`
 - (interpret-surrogate-methods), 41
- `print.funcml_tune (tune-methods)`, 56
- `pROC::ci.auc()`, 5
- `pROC::roc()`, 52
-
- `recall (metrics)`, 47
- `rmse (metrics)`, 47
- `roc-methods`, 52
- `roc_curve`, 52
- `rsq (metrics)`, 47
-
- `specificity (metrics)`, 47

- summary.funcml_ale
 - (interpret-ale-methods), [32](#)
- summary.funcml_calibration
 - (interpret-calibration-methods), [33](#)
- summary.funcml_compare
 - (compare-methods), [14](#)
- summary.funcml_estimand
 - (estimate-methods), [20](#)
- summary.funcml_eval (evaluate-methods), [22](#)
- summary.funcml_fit (fit-methods), [24](#)
- summary.funcml_ice
 - (interpret-ice-methods), [34](#)
- summary.funcml_iml_local_model
 - (interpret-local-model-methods), [37](#)
- summary.funcml_interaction
 - (interpret-interaction-methods), [35](#)
- summary.funcml_local
 - (interpret-local-methods), [36](#)
- summary.funcml_pdp
 - (interpret-pdp-methods), [38](#)
- summary.funcml_permute
 - (interpret-permute-methods), [39](#)
- summary.funcml_shap
 - (interpret-shap-methods), [40](#)
- summary.funcml_surrogate
 - (interpret-surrogate-methods), [41](#)
- summary.funcml_tune (tune-methods), [56](#)
- theme_funcml, [53](#)
- time_cv, [54](#)
- tune, [54](#)
- tune-methods, [56](#)