

Package ‘shinyds’

August 22, 2026

Title 'Shiny' Bindings for Designsystemet Components

Version 0.5.0

Description Provides 'R' wrappers for the Designsystemet component library
<<https://designsystemet.no>>, enabling use of Norwegian government design system
components in 'Shiny' applications. Includes web components and CSS-based
HTML components with full 'Shiny' input binding support.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 8.0.0

Imports htmltools (>= 0.5.0), shiny (>= 1.7.0)

Suggests testthat (>= 3.0.0), shinytest2, chromote, jsonlite, withr,
bslib, quarto

VignetteBuilder quarto

Config/testthat/edition 3

Config/roxygen2/markdown TRUE

Config/roxygen2/version 8.0.0

URL <https://github.com/novica/shinyds>

BugReports <https://github.com/novica/shinyds/issues>

NeedsCompilation no

Author Novica Nakov [aut, cre, cph] (ORCID:
<<https://orcid.org/0009-0005-7773-7718>>)

Maintainer Novica Nakov <nnovica@gmail.com>

Repository CRAN

Date/Publication 2026-08-22 11:40:02 UTC

Contents

ds_alert	3
ds_avatar	4

ds_avatar_stack	4
ds_badge	5
ds_badge_position	6
ds_breadcrumbs	7
ds_button	7
ds_card	8
ds_card_block	9
ds_checkbox	10
ds_chip	10
ds_chip_group	11
ds_combobox	12
ds_dependencies	12
ds_details	13
ds_dialog	14
ds_divider	14
ds_dropdown	15
ds_error_summary	16
ds_field	16
ds_fieldset	17
ds_heading	18
ds_input	18
ds_label	19
ds_link	20
ds_list	20
ds_list_item	21
ds_pagination	21
ds_paragraph	22
ds_popover	23
ds_radio	23
ds_radio_group	24
ds_search	25
ds_select	26
ds_skeleton	27
ds_skip_link	27
ds_spinner	28
ds_suggestion	28
ds_tab	29
ds_table	30
ds_tablist	31
ds_tabpanel	31
ds_tabs	32
ds_tag	33
ds_tbody	34
ds_td	34
ds_textarea	35
ds_th	36
ds_thead	36
ds_theme	37

ds_toggle_group	38
ds_tooltip	38
ds_tr	39
ds_validation_message	40
hide_ds_dialog	40
show_ds_dialog	41
update_ds_checkbox	42
update_ds_input	42
update_ds_pagination	43
update_ds_radio_group	44
update_ds_select	45
update_ds_suggestion	45
update_ds_tabs	46
use_designsystemmet	47
Index	48

ds_alert	<i>Alert Component</i>
----------	------------------------

Description

Create an alert message using Designsystemmet styles.

Usage

```
ds_alert(  
  ...,  
  variant = c("info", "warning", "danger", "success"),  
  class = NULL  
)
```

Arguments

...	Alert content
variant	Alert variant ("info", "warning", "danger", "success")
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_alert("This is an informational message.", variant = "info")  
ds_alert("Warning: Please review before continuing.", variant = "warning")  
ds_alert("Error: Something went wrong.", variant = "danger")  
ds_alert("Success! Your changes were saved.", variant = "success")
```

ds_avatar	<i>Avatar Component</i>
-----------	-------------------------

Description

Create an avatar using Designsystemet styles.

Usage

```
ds_avatar(..., variant = NULL, size = NULL, class = NULL)
```

Arguments

...	Avatar content (typically an image or initials)
variant	Avatar variant
size	Size variant ("sm", "md", "lg")
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_avatar("AB", size = "md")
```

ds_avatar_stack	<i>Avatar Stack Component</i>
-----------------	-------------------------------

Description

Create a stack of avatars using Designsystemet styles.

Usage

```
ds_avatar_stack(..., class = NULL)
```

Arguments

...	Avatar elements
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_avatar_stack(  
  ds_avatar("AB"),  
  ds_avatar("CD"),  
  ds_avatar("EF")  
)
```

ds_badge	Badge Component
----------	-----------------

Description

Create a count-indicator badge using Designsystemet styles.

Usage

```
ds_badge(  
  count = NULL,  
  color = NULL,  
  variant = NULL,  
  size = NULL,  
  class = NULL,  
  ...  
)
```

Arguments

count	Numeric or character value shown inside the badge circle. Pass NULL for a plain dot.
color	Color context: one of "info", "success", "warning", "danger", "accent", "neutral", "brand1", "brand2". Maps to the DS data-color attribute.
variant	Structural variant: "tinted" for a muted background. Colour variants belong in color, not here.
size	Size variant ("sm", "md", "lg").
class	Additional CSS classes.
...	Additional attributes passed to the .

Details

The badge is a small circle that sits on top of another element (e.g. a button) to show a numeric count. Wrap the target element with a ds_badge_position() container and place ds_badge() inside it.

The circle text comes from count; ... is the accessible label for the element being badged (rendered as invisible span text).

Value

A Shiny tag object

Examples

```
# Standalone dot with no count
ds_badge(color = "success")

# Count badge on a button (typical use – see ds_badge_position())
## Not run:
ds_badge_position(
  ds_button("Inbox"),
  ds_badge(count = 4, color = "danger")
)

## End(Not run)
```

ds_badge_position	<i>Badge Position Wrapper</i>
-------------------	-------------------------------

Description

Wraps an element so that a `ds_badge()` can be positioned on top of it.

Usage

```
ds_badge_position(..., placement = "top-right", overlap = NULL, class = NULL)
```

Arguments

<code>...</code>	The target element followed by a <code>ds_badge()</code> .
<code>placement</code>	Badge placement: "top-right" (default), "top-left", "bottom-right", "bottom-left".
<code>overlap</code>	Set to "circle" when the target is a circular avatar.
<code>class</code>	Additional CSS classes.

Value

A Shiny tag object

Examples

```
ds_badge_position(
  ds_button("Inbox"),
  ds_badge(count = 3, color = "danger"),
  placement = "top-right"
)
```

ds_breadcrumbs	<i>Breadcrumbs Component</i>
----------------	------------------------------

Description

Create a breadcrumb navigation trail.

Usage

```
ds_breadcrumbs(..., class = NULL)
```

Arguments

...	Child elements (typically list items with links)
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_breadcrumbs(  
  htmltools::tags$ol(  
    htmltools::tags$li(ds_link("Home", href = "/")),  
    htmltools::tags$li(ds_link("Products", href = "/products")),  
    htmltools::tags$li(htmltools::tags$span("Current Page"))  
  )  
)
```

ds_button	<i>Button Component</i>
-----------	-------------------------

Description

Create a styled button using Designsystemet styles. `ds_action_button()` is a drop-in replacement for `shiny::actionButton()` with the same (`inputId`, `label`, ...) argument order.

Usage

```
ds_button(  
  label,  
  inputId = NULL,  
  variant = c("primary", "secondary", "tertiary"),  
  size = NULL,  
  icon = FALSE,
```

```

    loading = FALSE,
    disabled = FALSE,
    fullwidth = FALSE,
    type = "button",
    ...
)

ds_action_button(inputId, label, ...)

```

Arguments

label	The button label.
inputId	Input ID (first argument, matching shiny::actionButton).
variant	Button variant: "primary", "secondary", or "tertiary".
size	Size variant: "sm", "md", or "lg".
icon	If TRUE, creates an icon-only button.
loading	If TRUE, shows loading state.
disabled	If TRUE, disables the button.
fullwidth	If TRUE, makes the button full width.
type	Button type: "button", "submit", or "reset".
...	Additional attributes.

Value

A Shiny tag object.

Examples

```

ds_button("Click me", inputId = "btn")
ds_button("Submit", variant = "primary", type = "submit")
ds_button("Cancel", variant = "secondary")
ds_action_button("btn", "Click me")

```

ds_card

Card Component

Description

Create a styled card container using Designsystemet styles.

Usage

```
ds_card(..., variant = NULL, class = NULL)
```


Arguments

...	Child elements
variant	Card variant ("default", "tinted")
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_card(  
  ds_card_block(  
    ds_heading("Card Title", level = 3),  
    ds_paragraph("Card content goes here.")  
  )  
)
```

ds_card_block

Card Block

Description

A block section within a card with proper padding.

Usage

```
ds_card_block(..., class = NULL)
```

Arguments

...	Child elements
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_card_block(ds_paragraph("Card content."))
```

ds_checkbox	<i>Checkbox Component</i>
-------------	---------------------------

Description

Create a styled checkbox using Designsystemet styles.

Usage

```
ds_checkbox(inputId, label, value = FALSE, size = NULL, disabled = FALSE, ...)
```

Arguments

inputId	The input slot for Shiny reactivity
label	The checkbox label
value	Initial checked state
size	Size variant ("sm", "md", "lg")
disabled	If TRUE, disables the checkbox
...	Additional attributes

Value

A Shiny tag object

Examples

```
ds_checkbox("agree", "I agree to the terms", value = FALSE)
```

ds_chip	<i>Chip Component</i>
---------	-----------------------

Description

Create an interactive chip using Designsystemet styles.

Usage

```
ds_chip(..., variant = NULL, size = NULL, selected = FALSE, class = NULL)
```

Arguments

...	Chip content
variant	Chip variant
size	Size variant ("sm", "md", "lg")
selected	If TRUE, shows selected state
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_chip("React")
ds_chip("Vue", selected = TRUE)
```

ds_chip_group	<i>Chip Group Component</i>
---------------	-----------------------------

Description

Create a reactive group of toggle chips. Selected chip values are reported to Shiny as a character vector via `input[[inputId]]`.

Usage

```
ds_chip_group(inputId, ..., class = NULL)
```

Arguments

<code>inputId</code>	Shiny input ID
<code>...</code>	<code>ds_chip()</code> elements
<code>class</code>	Additional CSS classes

Value

A Shiny tag object

Examples

```
## Not run:
ds_chip_group(
  "languages",
  ds_chip("R", value = "r", selected = TRUE),
  ds_chip("Python", value = "python"),
  ds_chip("Julia", value = "julia")
)

## End(Not run)
```

ds_combobox

Combobox Component

Description

Create a combobox container using Designsystemet styles. Unlike ds_suggestion, this is a pure CSS component — keyboard navigation and dropdown behaviour must be implemented by the caller.

Usage

```
ds_combobox(inputId, ..., size = NULL, class = NULL)
```

Arguments

inputId	The input slot for Shiny reactivity
...	Child elements (input wrapper, options wrapper, etc.)
size	Size variant ("sm", "md", "lg")
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_combobox("mycombo",
  htmltools::tags$div(class = "ds-combobox__input__wrapper",
    htmltools::tags$input(class = "ds-combobox__input", type = "text")
  ),
  htmltools::tags$div(class = "ds-combobox__options-wrapper")
)
```

ds_dependencies

Designsystemet Dependencies

Description

Returns the HTML dependencies required for Designsystemet components.

Usage

```
ds_dependencies()
```

Value

A list of htmltools `htmlDependency` objects

Examples

```
ds_dependencies()
```

ds_details	<i>Details/Accordion Component</i>
------------	------------------------------------

Description

Create an expandable details section using Designsystemet styles.

Usage

```
ds_details(summary, ..., open = FALSE, class = NULL)
```

Arguments

summary	The summary/title text shown when collapsed
...	Content shown when expanded
open	If TRUE, the details are initially open
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_details(  
  summary = "Click to expand",  
  ds_paragraph("Hidden content goes here.")  
)
```

`ds_dialog`*Dialog Component*

Description

Create a modal dialog using Designsystemet styles. Place `ds_dialog()` in your UI and open/close it from the server with [show_ds_dialog\(\)](#) and [hide_ds_dialog\(\)](#).

Usage

```
ds_dialog(..., id = NULL, class = NULL)
```

Arguments

<code>...</code>	Dialog content
<code>id</code>	Dialog ID for opening/closing via show_ds_dialog()
<code>class</code>	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_dialog(  
  id = "my-dialog",  
  ds_heading("Dialog Title", level = 2),  
  ds_paragraph("Dialog content here."),  
  ds_button("Close", onclick = "this.closest('dialog').close()")  
)
```

`ds_divider`*Divider Component*

Description

Create a horizontal divider using Designsystemet styles.

Usage

```
ds_divider(class = NULL)
```

Arguments

<code>class</code>	Additional CSS classes
--------------------	------------------------

Value

A Shiny tag object

Examples

```
ds_divider()
```

ds_dropdown	<i>Dropdown Component</i>
-------------	---------------------------

Description

Create a dropdown menu using Designsystemet styles.

Usage

```
ds_dropdown(trigger, ..., id = NULL, class = NULL)
```

Arguments

trigger	The trigger element (usually a button)
...	Dropdown panel content
id	Optional ID for the dropdown panel. Auto-generated if omitted.
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_dropdown(  
  trigger = ds_button("Options"),  
  ds_list(ds_list_item("Edit"), ds_list_item("Delete"))  
)
```

ds_error_summary	<i>Error Summary Component</i>
------------------	--------------------------------

Description

Display a summary of form validation errors.

Usage

```
ds_error_summary(..., heading = "Feil i skjema", class = NULL)
```

Arguments

...	Error list items
heading	The heading text for the error summary
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_error_summary(  
  heading = "There were errors in the form",  
  htmltools::tags$li(ds_link("Name is required", href = "#name")),  
  htmltools::tags$li(ds_link("Email is invalid", href = "#email"))  
)
```

ds_field	<i>Field Container</i>
----------	------------------------

Description

A container for form field elements with proper spacing and layout.

Usage

```
ds_field(..., size = NULL, class = NULL)
```

Arguments

...	Child elements (label, input, validation message, etc.)
size	Size variant ("sm", "md", "lg")
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_field(  
  ds_label("Email", `for` = "email"),  
  ds_input("email", type = "email", placeholder = "your@email.com"),  
  ds_validation_message("Please enter a valid email")  
)
```

ds_fieldset

Fieldset Component

Description

Group related form fields with a legend using Designsystemet styles.

Usage

```
ds_fieldset(legend, ..., class = NULL)
```

Arguments

legend	The legend text for the fieldset group
...	Child elements (fields, inputs, etc.)
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_fieldset("Preferences",  
  ds_checkbox("opt1", "Option 1"),  
  ds_checkbox("opt2", "Option 2")  
)
```

ds_heading	Heading Component
Description	
Create a styled heading using Designsystemet styles.	
Usage	
<pre>ds_heading(..., level = 2, size = NULL, class = NULL)</pre>	
Arguments	
...	Heading content
level	Heading level (1-6)
size	Size variant ("2xs", "xs", "sm", "md", "lg", "xl", "2xl")
class	Additional CSS classes
Value	
A Shiny tag object	
Examples	
<pre>ds_heading("Page Title", level = 1) ds_heading("Section Title", level = 2, size = "lg")</pre>	
ds_input	Text Input Component

Description

Create a styled text input using Designsystemet styles.

Usage

```
ds_input(
  inputId,
  value = "",
  type = "text",
  placeholder = NULL,
  size = NULL,
  readonly = FALSE,
  disabled = FALSE,
  invalid = FALSE,
  ...
)
```

Arguments

inputId	The input slot for Shiny reactivity
value	Initial value
type	Input type ("text", "email", "password", "number", "tel", "url")
placeholder	Placeholder text
size	Size variant ("sm", "md", "lg")
readonly	If TRUE, makes the input read-only
disabled	If TRUE, disables the input
invalid	If TRUE, shows invalid state
...	Additional attributes

Value

A Shiny tag object

Examples

```
ds_input("name", placeholder = "Enter your name")
ds_input("email", type = "email", placeholder = "your@email.com")
```

ds_label	<i>Label Component</i>
----------	------------------------

Description

Create a styled form label using Designsystemet styles.

Usage

```
ds_label(..., `for` = NULL, class = NULL)
```

Arguments

...	Label content
for	The ID of the input this label is for
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_label("Email address", `for` = "email")
```

`ds_link`*Link Component*

Description

Create a styled link using Designsystemet styles.

Usage

```
ds_link(..., href = "#", class = NULL)
```

Arguments

<code>...</code>	Link content
<code>href</code>	Link URL
<code>class</code>	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_link("Visit our website", href = "https://example.com")
```

`ds_list`*List Component*

Description

Create a styled list using Designsystemet styles.

Usage

```
ds_list(..., ordered = FALSE, class = NULL)
```

Arguments

<code>...</code>	List items
<code>ordered</code>	If TRUE, creates an ordered list
<code>class</code>	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_list(  
  ds_list_item("First item"),  
  ds_list_item("Second item"),  
  ds_list_item("Third item")  
)
```

`ds_list_item`*List Item*

Description

Create a list item.

Usage

```
ds_list_item(...)
```

Arguments

... Item content

Value

A Shiny tag object

Examples

```
ds_list_item("First item")
```

`ds_pagination`*Pagination Component*

Description

Create a pagination component for navigating through pages.

Usage

```
ds_pagination(  
  inputId,  
  current = 1,  
  total,  
  label = "Sidenavigasjon",  
  href = NULL,  
  ...  
)
```

Arguments

inputId	The input slot for Shiny reactivity
current	The current page number (1-indexed)
total	The total number of pages
label	Accessibility label for the pagination nav
href	Optional URL template for page links (use <code>sprintf</code> style, e.g. "page?p=1")
...	Additional attributes

Value

A Shiny tag object

Examples

```
ds_pagination("mypage", current = 1, total = 10)
```

ds_paragraph

Paragraph Component

Description

Create a styled paragraph using Designsystemet styles.

Usage

```
ds_paragraph(..., size = NULL, class = NULL)
```

Arguments

...	Paragraph content
size	Size variant ("sm", "md", "lg")
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_paragraph("This is a paragraph of text.")
```

`ds_popover`*Popover Component*

Description

Create a popover using Designsystemet styles.

Usage

```
ds_popover(..., variant = NULL, class = NULL)
```

Arguments

<code>...</code>	Popover content
<code>variant</code>	Popover variant ("default", "tinted")
<code>class</code>	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_popover("Helpful information about this field.")
ds_popover("Highlighted note", variant = "tinted")
```

`ds_radio`*Radio Button Component*

Description

Create a single styled radio button using Designsystemet styles. This is the building block used by [ds_radio_group\(\)](#) — a standalone `ds_radio()` is not reactive on its own. To get a Shiny input value out of a group of radio buttons, use [ds_radio_group\(\)](#) instead.

Usage

```
ds_radio(
  inputId,
  label,
  value,
  name,
  checked = FALSE,
  size = NULL,
  disabled = FALSE,
  ...
)
```

Arguments

inputId	The id/for pair linking this radio to its label
label	The radio button label
value	The value for this radio button
name	The name grouping radio buttons together
checked	If TRUE, this radio is initially selected
size	Size variant ("sm", "md", "lg")
disabled	If TRUE, disables the radio button
...	Additional attributes

Value

A Shiny tag object

Examples

```
ds_radio("opt_a", label = "Option A", value = "a", name = "opts")
```

ds_radio_group	<i>Radio Group Component</i>
----------------	------------------------------

Description

Create a reactive group of radio buttons. The value of whichever `ds_radio()` is checked is reported to Shiny as a single value via `input[[inputId]]` — mirroring how Shiny's own `radioButtons()` works.

Usage

```
ds_radio_group(  
  inputId,  
  label,  
  choices,  
  selected = NULL,  
  size = NULL,  
  disabled = FALSE,  
  class = NULL  
)
```


Arguments

inputId	Shiny input ID
label	The legend text for the group
choices	Named vector of choices (names are labels, values are values)
selected	Initially selected value. Defaults to the first choice.
size	Size variant ("sm", "md", "lg")
disabled	If TRUE, disables every radio button in the group
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_radio_group("opts",
  label = "Choose one",
  choices = c("Choice A" = "a", "Choice B" = "b", "Choice C" = "c"),
  selected = "a"
)
```

ds_search

*Search Component***Description**

Create a search input using Designsystemet styles.

Usage

```
ds_search(
  inputId,
  value = "",
  placeholder = NULL,
  size = NULL,
  class = NULL,
  ...
)
```

Arguments

inputId	The input slot for Shiny reactivity
value	Initial value
placeholder	Placeholder text
size	Size variant ("sm", "md", "lg")
class	Additional CSS classes
...	Additional attributes

Value

A Shiny tag object

Examples

```
ds_search("search", placeholder = "Search. . .")
```

ds_select

Select Component

Description

Create a styled select dropdown using Designsystemet styles.

Usage

```
ds_select(
  inputId,
  choices,
  selected = NULL,
  size = NULL,
  disabled = FALSE,
  ...
)
```

Arguments

inputId	The input slot for Shiny reactivity
choices	Named vector of choices (names are labels, values are values)
selected	Initially selected value
size	Size variant ("sm", "md", "lg")
disabled	If TRUE, disables the select
...	Additional attributes

Value

A Shiny tag object

Examples

```
ds_select("country",
  choices = c("Norway" = "no", "Sweden" = "se", "Denmark" = "dk"),
  selected = "no"
)
```

ds_skeleton	<i>Skeleton Component</i>
-------------	---------------------------

Description

Create a loading skeleton placeholder using Designsystemet styles.

Usage

```
ds_skeleton(variant = "text", width = NULL, height = NULL, class = NULL)
```

Arguments

variant	Skeleton variant ("text", "circle", "rectangle")
width	Width of the skeleton
height	Height of the skeleton
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_skeleton(variant = "text", width = "200px")
ds_skeleton(variant = "circle", width = "50px", height = "50px")
```

ds_skip_link	<i>Skip Link Component</i>
--------------	----------------------------

Description

Create an accessibility skip link using Designsystemet styles.

Usage

```
ds_skip_link(..., href = "#main", class = NULL)
```

Arguments

...	Link content
href	Target anchor
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_skip_link("Skip to main content", href = "#main")
```

ds_spinner	<i>Spinner Component</i>
------------	--------------------------

Description

Create a loading spinner using Designsystemet styles.

Usage

```
ds_spinner(title = "Laster...", size = NULL, class = NULL)
```

Arguments

title	Accessibility title for the spinner
size	Size variant ("sm", "md", "lg")
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_spinner(title = "Loading...")
```

ds_suggestion	<i>Suggestion/Autocomplete Component</i>
---------------	--

Description

Create an autocomplete input with suggestions.

Usage

```
ds_suggestion(  
  inputId,  
  choices = NULL,  
  value = "",  
  placeholder = NULL,  
  size = NULL,  
  ...  
)
```

Arguments

inputId	The input slot for Shiny reactivity
choices	Character vector of suggestion choices
value	Initial value
placeholder	Placeholder text
size	Size variant ("sm", "md", "lg")
...	Additional attributes

Value

A Shiny tag object

Examples

```
ds_suggestion("city",  
  choices = c("Oslo", "Bergen", "Trondheim", "Stavanger"),  
  placeholder = "Search for a city..."  
)
```

ds_tab	<i>Tab Button</i>
--------	-------------------

Description

A single tab button within ds_tablist.

Usage

```
ds_tab(label, value, selected = FALSE, ...)
```

Arguments

label	The tab label text
value	The value to return when this tab is selected
selected	Whether this tab is initially selected
...	Additional attributes

Value

A Shiny tag object

Examples

```
ds_tab("Overview", value = "overview", selected = TRUE)
```

ds_table	<i>Table Component</i>
----------	------------------------

Description

Create a styled table using Designsystemet styles.

Usage

```
ds_table(..., size = NULL, class = NULL)
```

Arguments

- ... Table content (thead, tbody, etc.)
- size Size variant ("sm", "md", "lg")
- class Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_table(  
  ds_thead(  
    ds_tr(  
      ds_th("Name"),  
      ds_th("Email")  
    )  
  ),  
  ds_tbody(  
    ds_tr(  
      ds_td("John Doe"),  
      ds_td("john@example.com")  
    )  
  )  
)
```

ds_tablist	<i>Tab List Container</i>
------------	---------------------------

Description

Container for tab buttons within ds_tabs.

Usage

```
ds_tablist(..., class = NULL)
```

Arguments

...	Child elements (ds_tab elements)
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_tablist(  
  ds_tab("First", value = "tab1", selected = TRUE),  
  ds_tab("Second", value = "tab2")  
)
```

ds_tabpanel	<i>Tab Panel</i>
-------------	------------------

Description

Content panel for a tab.

Usage

```
ds_tabpanel(..., value, class = NULL)
```

Arguments

...	Panel content
value	The value that matches the corresponding ds_tab
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_tabpanel(value = "overview", ds_paragraph("Content here."))
```

ds_tabs	<i>Tabs Component</i>
---------	-----------------------

Description

Create a tabbed interface using Designsystemet tabs.

Usage

```
ds_tabs(inputId, ..., class = NULL)
```

Arguments

- inputId The input slot for Shiny reactivity
- ... Child elements (typically ds_tablist and ds_tabpanel elements)
- class Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_tabs("mytabs",
  ds_tablist(
    ds_tab("First", value = "tab1", selected = TRUE),
    ds_tab("Second", value = "tab2")
  ),
  ds_tabpanel(value = "tab1", "Content 1"),
  ds_tabpanel(value = "tab2", "Content 2")
)
```

ds_tag	Tag Component
--------	---------------

Description

Create a text label tag using Designsystemet styles.

Usage

```
ds_tag(..., color = NULL, variant = NULL, size = NULL, class = NULL)
```

Arguments

...	Tag content (text or child elements).
color	Color context: one of "info", "success", "warning", "danger", "accent", "neutral", "brand1", "brand2". Maps to the DS data-color attribute.
variant	Structural variant: "outline" adds a subtle border.
size	Size variant ("sm", "md", "lg").
class	Additional CSS classes.

Details

Tags are the right component for standalone text status labels such as "New", "Beta" or "Active". For numeric count indicators, use [ds_badge](#).

Value

A Shiny tag object

Examples

```
ds_tag("New")
ds_tag("Active", color = "success")
ds_tag("Warning", color = "warning", variant = "outline")
```

`ds_tbody`*Table Body*

Description

Create a table body section.

Usage

```
ds_tbody(...)
```

Arguments

... Body rows

Value

A Shiny tag object

Examples

```
ds_tbody(ds_tr(ds_td("John"), ds_td("john@example.com")))
```

`ds_td`*Table Data Cell*

Description

Create a table data cell.

Usage

```
ds_td(...)
```

Arguments

... Cell content

Value

A Shiny tag object

Examples

```
ds_td("Cell content")
```

ds_textarea*Textarea Component*

Description

Create a styled textarea using Designsystemet styles.

Usage

```
ds_textarea(  
  inputId,  
  value = "",  
  placeholder = NULL,  
  rows = 3,  
  size = NULL,  
  readonly = FALSE,  
  disabled = FALSE,  
  invalid = FALSE,  
  ...  
)
```

Arguments

inputId	The input slot for Shiny reactivity
value	Initial value
placeholder	Placeholder text
rows	Number of visible rows
size	Size variant ("sm", "md", "lg")
readonly	If TRUE, makes the textarea read-only
disabled	If TRUE, disables the textarea
invalid	If TRUE, shows invalid state
...	Additional attributes

Value

A Shiny tag object

Examples

```
ds_textarea("msg", placeholder = "Type here...", rows = 4)
```

ds_th	<i>Table Header Cell</i>
-------	--------------------------

Description

Create a table header cell.

Usage

```
ds_th(..., scope = "col")
```

Arguments

- ... Cell content
- scope Cell scope ("col", "row")

Value

A Shiny tag object

Examples

```
ds_th("Column header")
```

ds_thead	<i>Table Header</i>
----------	---------------------

Description

Create a table header section.

Usage

```
ds_thead(...)
```

Arguments

- ... Header rows

Value

A Shiny tag object

Examples

```
ds_thead(ds_tr(ds_th("Name"), ds_th("Email")))
```

ds_theme

*Designsystemet Theme***Description**

Override Designsystemet CSS tokens for color, typography, and spacing. Call inside your UI alongside `use_designsystemet()`.

Usage

```
ds_theme(
  color = NULL,
  font_size = NULL,
  border_radius = NULL,
  button_padding = NULL,
  ...
)
```

Arguments

color	Global color context. One of "default", "brand1", "brand2", "neutral", "success", "warning", "danger", "info". Sets data-color on <html>.
font_size	Base font size as a CSS value (e.g. "16px", "1rem"). Overrides --ds-font-size-base on :root.
border_radius	Border radius as a CSS value (e.g. "4px", "0"). Overrides --ds-border-radius-md on :root.
button_padding	Padding for buttons as a CSS shorthand (e.g. "0.4rem 0.9rem"). Overrides --dsc-button-padding on :root.
...	Named CSS custom property overrides in the form "--ds-token-name" = "value". Applied to :root.

Details

Color palette tokens follow the Designsystemet naming convention. Use data-color="brand2" on a container to switch its color context, or set color here to change the global default.

Value

A <style> tag applied to :root and optionally a JS snippet to set data-color on <html>.

Examples

```
ui <- bslib::page_fluid(
  use_designsystemet(),
  ds_theme(color = "brand1", border_radius = "2px", button_padding = "0.3rem 0.8rem"),
  ds_button("Click me", inputId = "btn")
)
```

ds_toggle_group	<i>Toggle Group Component</i>
-----------------	-------------------------------

Description

Create a toggle button group using Designsystemet styles.

Usage

```
ds_toggle_group(inputId, ..., size = NULL, class = NULL)
```

Arguments

inputId	The input slot for Shiny reactivity
...	Toggle buttons
size	Size variant ("sm", "md", "lg")
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
## Not run:
ds_toggle_group(
  "view_mode",
  tags$button(class = "ds-button", `data-variant` = "secondary",
    `aria-pressed` = "true", value = "list", "List"),
  tags$button(class = "ds-button", `data-variant` = "secondary",
    `aria-pressed` = "false", value = "grid", "Grid")
)

## End(Not run)
```

ds_tooltip	<i>Tooltip</i>
------------	----------------

Description

Add a tooltip to an element by attaching data-tooltip attributes.

Usage

```
ds_tooltip(tag, text, placement = "top")
```

Arguments

- tag The element to attach the tooltip to.
- text The tooltip text.
- placement Tooltip placement: "top", "bottom", "left", or "right".

Value

The element with tooltip attributes added.

Examples

```
ds_tooltip(  
  ds_button("Hover me"),  
  text = "This is helpful information"  
)
```

ds_tr	<i>Table Row</i>
-------	------------------

Description

Create a table row.

Usage

```
ds_tr(...)
```

Arguments

- ... Row cells

Value

A Shiny tag object

Examples

```
ds_tr(ds_td("Cell 1"), ds_td("Cell 2"))
```

ds_validation_message	<i>Validation Message Component</i>
-----------------------	-------------------------------------

Description

Create a validation message using Designsystemet styles.

Usage

```
ds_validation_message(..., variant = "error", class = NULL)
```

Arguments

...	Message content
variant	Message variant ("error", "warning")
class	Additional CSS classes

Value

A Shiny tag object

Examples

```
ds_validation_message("This field is required")
```

hide_ds_dialog	<i>Close a dialog from the server</i>
----------------	---------------------------------------

Description

Sends a message to the browser to call close() on a ds_dialog() element.

Usage

```
hide_ds_dialog(id, session = shiny::getDefaultReactiveDomain())
```

Arguments

id	The id of the ds_dialog() to close.
session	Shiny session object.

Value

Called for side effects.

Examples

```
## Not run:
observeEvent(input$cancel_btn, {
  hide_ds_dialog("confirm-dialog")
})

## End(Not run)
```

show_ds_dialog	<i>Open a dialog from the server</i>
----------------	--------------------------------------

Description

Sends a message to the browser to call `showModal()` on a `ds_dialog()` element already present in the UI.

Usage

```
show_ds_dialog(id, session = shiny::getDefaultReactiveDomain())
```

Arguments

<code>id</code>	The id of the <code>ds_dialog()</code> to open.
<code>session</code>	Shiny session object.

Value

Called for side effects.

Examples

```
## Not run:
observeEvent(input$open_btn, {
  show_ds_dialog("confirm-dialog")
})

## End(Not run)
```

update_ds_checkbox	<i>Update Checkbox</i>
--------------------	------------------------

Description

Change the checked state from the server.

Usage

```
update_ds_checkbox(  
  session = shiny::getDefaultReactiveDomain(),  
  inputId,  
  value = NULL  
)
```

Arguments

session	The Shiny session object
inputId	The input ID
value	The new checked state (TRUE/FALSE)

Value

Called for its side effect. Returns NULL invisibly.

Examples

```
## Not run:  
update_ds_checkbox(session, "agree", value = FALSE)  
  
## End(Not run)
```

update_ds_input	<i>Update Text Input</i>
-----------------	--------------------------

Description

Change the value from the server.

Usage

```
update_ds_input(  
  session = shiny::getDefaultReactiveDomain(),  
  inputId,  
  value = NULL  
)
```

Arguments

session	The Shiny session object
inputId	The input ID
value	The new value

Value

Called for its side effect. Returns NULL invisibly.

Examples

```
## Not run:
update_ds_input(session, "name", value = "")

## End(Not run)
```

update_ds_pagination	<i>Update Pagination Input</i>
----------------------	--------------------------------

Description

Change the current page or total pages from the server.

Usage

```
update_ds_pagination(
  session = shiny::getDefaultReactiveDomain(),
  inputId,
  current = NULL,
  total = NULL
)
```

Arguments

session	The Shiny session object
inputId	The input ID of the pagination component
current	The new current page number
total	The new total number of pages

Value

Called for its side effect. Returns NULL invisibly.

Examples

```
## Not run:
update_ds_pagination(session, "pager", current = 1)

## End(Not run)
```

update_ds_radio_group *Update Radio Group*

Description

Change the selected value of a `ds_radio_group()` from the server.

Usage

```
update_ds_radio_group(
  session = shiny::getDefaultReactiveDomain(),
  inputId,
  value = NULL
)
```

Arguments

session	The Shiny session object
inputId	The input ID
value	The new selected value

Value

Called for its side effect. Returns NULL invisibly.

Examples

```
## Not run:
update_ds_radio_group(session, "opts", value = "b")

## End(Not run)
```

update_ds_select	<i>Update Select</i>
------------------	----------------------

Description

Change the selected value or choices from the server.

Usage

```
update_ds_select(  
  session = shiny::getDefaultReactiveDomain(),  
  inputId,  
  value = NULL,  
  choices = NULL  
)
```

Arguments

session	The Shiny session object
inputId	The input ID
value	The new selected value
choices	New named vector of choices

Value

Called for its side effect. Returns NULL invisibly.

Examples

```
## Not run:  
update_ds_select(session, "country", value = "no")  
  
## End(Not run)
```

update_ds_suggestion	<i>Update Suggestion Input</i>
----------------------	--------------------------------

Description

Change the value or choices from the server.

Usage

```
update_ds_suggestion(  
  session = shiny::getDefaultReactiveDomain(),  
  inputId,  
  value = NULL,  
  choices = NULL  
)
```

Arguments

session	The Shiny session object
inputId	The input ID of the suggestion component
value	The new value
choices	New character vector of choices

Value

Called for its side effect. Returns NULL invisibly.

Examples

```
## Not run:  
update_ds_suggestion(session, "fruit", value = "Apple")  
  
## End(Not run)
```

update_ds_tabs	<i>Update Tabs Input</i>
----------------	--------------------------

Description

Change the selected tab from the server.

Usage

```
update_ds_tabs(  
  session = shiny::getDefaultReactiveDomain(),  
  inputId,  
  selected = NULL  
)
```

Arguments

session	The Shiny session object
inputId	The input ID of the tabs component
selected	The value of the tab to select

Value

Called for its side effect. Returns NULL invisibly.

Examples

```
## Not run:
update_ds_tabs(session, "my_tabs", selected = "overview")

## End(Not run)
```

use_designsystemet	<i>Use Designsystemet in a Shiny App</i>
--------------------	--

Description

Include this function in your UI to load all necessary Designsystemet CSS and JavaScript dependencies.

Usage

```
use_designsystemet(color_scheme = "light")
```

Arguments

color_scheme	Color scheme to apply to the page. One of "light" or "dark". Sets the data-color-scheme attribute on <html>, which activates Designsystemet's CSS custom property tokens.
--------------	---

Value

A tagList containing the dependencies

Examples

```
ui <- bslib::page_fluid(
  use_designsystemet(),
  ds_button("Click me", inputId = "btn")
)
```

Index

`ds_action_button(ds_button)`, 7
`ds_alert`, 3
`ds_avatar`, 4
`ds_avatar_stack`, 4
`ds_badge`, 5, 33
`ds_badge_position`, 6
`ds_breadcrumbs`, 7
`ds_button`, 7
`ds_card`, 8
`ds_card_block`, 9
`ds_checkbox`, 10
`ds_chip`, 10
`ds_chip_group`, 11
`ds_combobox`, 12
`ds_dependencies`, 12
`ds_details`, 13
`ds_dialog`, 14
`ds_divider`, 14
`ds_dropdown`, 15
`ds_error_summary`, 16
`ds_field`, 16
`ds_fieldset`, 17
`ds_heading`, 18
`ds_input`, 18
`ds_label`, 19
`ds_link`, 20
`ds_list`, 20
`ds_list_item`, 21
`ds_pagination`, 21
`ds_paragraph`, 22
`ds_popover`, 23
`ds_radio`, 23
`ds_radio()`, 24
`ds_radio_group`, 24
`ds_radio_group()`, 23, 44
`ds_search`, 25
`ds_select`, 26
`ds_skeleton`, 27
`ds_skip_link`, 27
`ds_spinner`, 28
`ds_suggestion`, 28
`ds_tab`, 29
`ds_table`, 30
`ds_tablist`, 31
`ds_tabpanel`, 31
`ds_tabs`, 32
`ds_tag`, 33
`ds_tbody`, 34
`ds_td`, 34
`ds_textarea`, 35
`ds_th`, 36
`ds_thead`, 36
`ds_theme`, 37
`ds_toggle_group`, 38
`ds_tooltip`, 38
`ds_tr`, 39
`ds_validation_message`, 40

`hide_ds_dialog`, 40
`hide_ds_dialog()`, 14

`show_ds_dialog`, 41
`show_ds_dialog()`, 14

`update_ds_checkbox`, 42
`update_ds_input`, 42
`update_ds_pagination`, 43
`update_ds_radio_group`, 44
`update_ds_select`, 45
`update_ds_suggestion`, 45
`update_ds_tabs`, 46
`use_designsystemet`, 47
`use_designsystemet()`, 37