

Package ‘tidydelta’

July 19, 2024

Title Estimation of Standard Errors using Delta Method

Version 0.1.0

Description Delta Method implementation to estimate standard errors with known asymptotic properties within the ‘tidyverse’ workflow. The Delta Method is a statistical tool that approximates an estimator’s behaviour using a Taylor Expansion. For a comprehensive explanation, please refer to Chapter 3 of van der Vaart (1998, ISBN: 9780511802256).

License MIT + file LICENSE

Imports dplyr, numDeriv, purrr, rlang, tibble, cli

Suggests testthat (>= 3.0.0), tidyverse

Encoding UTF-8

RoxygenNote 7.3.2

Config/testthat/edition 3

URL <https://github.com/JavierMtzRdz/tidydelta>

BugReports <https://github.com/JavierMtzRdz/tidydelta/issues>

NeedsCompilation no

Author Javier Martinez-Rodriguez [aut, cre, cph]

Maintainer Javier Martinez-Rodriguez <javier.matz.rdz@gmail.com>

Repository CRAN

Date/Publication 2024-07-18 23:20:02 UTC

Contents

cases_ext	2
ext_bd_var	2
for_to_exp	3
tidydelta	3
where_env	4

Index

5

cases_ext

Extract variables and their names from the formula

Description

Extract variables and their names from the formula

Usage

```
cases_ext(formula, mean_dta = NULL, cov_dta = NULL)
```

Arguments

- | | |
|----------|--|
| formula | A formula object specifying the variables of interest. |
| mean_dta | Vector containing the means of the variables. |
| cov_dta | Covariance matrix of the variables. |

Value

list containing objects with variables and formula

ext_bd_var

Extract variables from a formula

Description

Extracts variables from a formula string.

Usage

```
ext_bd_var(formula)
```

Arguments

- | | |
|---------|--|
| formula | A formula object or a character string representing a formula. |
|---------|--|

Value

A named character vector of extracted variables.

for_to_exp	<i>Convert a formula to an expression</i>
------------	---

Description

Converts a formula to an expression for further evaluation.

Usage

```
for_to_exp(formula)
```

Arguments

formula A formula object or a character string representing a formula.

Value

The evaluated expression.

tidydelta	<i>Delta Method implementation</i>
-----------	------------------------------------

Description

Estimates standard errors for transformations of random variables using Delta method.

Usage

```
tidydelta(  
  formula,  
  normality_eval = TRUE,  
  formula_vars = mean,  
  mean_dta = NULL,  
  cov_dta = NULL,  
  n = NULL,  
  conf_lev = 0.95  
)
```

Arguments

formula A formula object specifying the variables of interest.

normality_eval Logical value to run normality test in case of being possible.

formula_vars The function(s) to apply to the variables in the formula.

mean_dta Vector containing the means of the variables.

cov_dta Covariance matrix of the variables.

n	Sample size evaluation (in case that we can evaluate the confidence intervals with different hypnotic sample sizes).
conf_lev	Confidence level for confidence intervals.

Value

A tibble with columns for means, standard errors, and optionally, confidence intervals.

Examples

```
# Equivalent ways to use tidydelta()
library(tidyverse)

x <- rnorm(1000, mean = 5, sd = 2)
y <- rnorm(1000, mean = 15, sd = 3)

bd <- tibble(x, y)

tidydelta(~ y / x,
          conf_lev = .95
        )

tidydelta(~ bd$y / bd$x,
          conf_lev = .95
        )
bd %>%
  summarise(tidydelta(~ y / x,
                      conf_lev = .95
                    ))
```

Description

Recursive search of environment containing object.

Usage

```
where_env(name, env = rlang::caller_env())
```

Arguments

name	Object searched
env	Initial environment to search

Value

A named character vector of extracted variables.

Index

`cases_ext`, [2](#)

`ext_bd_var`, [2](#)

`for_to_exp`, [3](#)

`tidydelta`, [3](#)

`where_env`, [4](#)