

---

Stream: Internet Engineering Task Force (IETF)  
RFC: [9755](#)  
Obsoletes: [6855](#)  
Category: Standards Track  
Published: February 2025  
ISSN: 2070-1721  
Authors: P. Resnick J. Yao A. Gulbrandsen  
*Episteme CNNIC ICANN*

# RFC 9755

## IMAP Support for UTF-8

---

### Abstract

This specification extends the Internet Message Access Protocol, specifically IMAP4rev1 (RFC 3501), to support UTF-8 encoded international characters in user names, mail addresses, and message headers. This specification replaces RFC 6855. This specification does not extend IMAP4rev2 (RFC 9051), since that protocol includes everything in this extension.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <https://www.rfc-editor.org/info/rfc9755>.

### Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

## Table of Contents

1. Introduction	2
2. Requirements Language	3
3. "UTF8=ACCEPT" IMAP Capability and UTF-8 in IMAP Quoted-Strings	3
4. "APPEND" Command	4
5. "LOGIN" Command and UTF-8	5
6. FETCH BODYSTRUCTURE and message/global	5
7. "UTF8=ONLY" Capability	5
8. Dealing with Legacy Clients	6
9. Issues with UTF-8 Header Mailstore	7
10. IANA Considerations	7
11. Security Considerations	7
12. References	8
12.1. Normative References	8
12.2. Informative References	9
Appendix A. Design Rationale	9
Appendix B. Changes since RFC 6855	10
B.1. APPEND UTF8	10
B.2. FETCH BODYSTRUCTURE	10
Acknowledgments	11
Authors' Addresses	11

## 1. Introduction

This specification forms part of the Email Address Internationalization protocols described in the Email Address Internationalization Framework document [RFC6530]. It extends IMAP [RFC3501] to permit UTF-8 [RFC3629] in headers, as described in "Internationalized Email Headers" [RFC6532]. It also adds a mechanism to support mailbox names using the UTF-8 charset. This specification creates two new IMAP capabilities to allow servers to advertise these new extensions.

This specification assumes that the IMAP server will be operating in a fully internationalized environment, i.e., one in which all clients accessing the server will be able to accept non-ASCII message header fields and other information, as specified in [Section 3](#). At least during a transition period, that assumption will not be realistic for many environments; the issues involved are discussed in [Section 7](#) below.

This specification replaces an earlier, experimental approach to the same problem; see [\[RFC5738\]](#) as well as [\[RFC6855\]](#).

## 2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [\[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

## 3. "UTF8=ACCEPT" IMAP Capability and UTF-8 in IMAP Quoted-Strings

The "UTF8=ACCEPT" capability indicates that the server supports the ability to open mailboxes containing internationalized messages with the "SELECT" and "EXAMINE" commands, and the server can provide UTF-8 responses to the "LIST" and "LSUB" commands. This capability also affects other IMAP extensions that can return mailbox names or their prefixes, such as NAMESPACE [\[RFC2342\]](#) and ACL [\[RFC4314\]](#).

The "UTF8=ONLY" capability, described in [Section 7](#), implies the "UTF8=ACCEPT" capability. A server is said to support "UTF8=ACCEPT" if it advertises either "UTF8=ACCEPT" or "UTF8=ONLY".

A client **MUST** use the "ENABLE" command [\[RFC5161\]](#) with the "UTF8=ACCEPT" option (defined in [Section 4](#) below) to indicate to the server that the client accepts UTF-8 in quoted-strings and supports the "UTF8=ACCEPT" extension. The "ENABLE UTF8=ACCEPT" command is only valid in the authenticated state.

The IMAP base specification [\[RFC3501\]](#) forbids the use of 8-bit characters in atoms or quoted-strings. Thus, a UTF-8 string can only be sent as a literal. This can be inconvenient from a coding standpoint, and unless the server offers IMAP non-synchronizing literals [\[RFC2088\]](#), this requires an extra round trip for each UTF-8 string sent by the client. When the IMAP server supports "UTF8=ACCEPT", it supports UTF-8 in quoted-strings with the following ABNF syntax [\[RFC5234\]](#):

```
quoted          =/ DQUOTE *uQUOTED-CHAR DQUOTE
                ; QUOTED-CHAR is not modified, as it will affect
                ; other RFC 3501 ABNF non-terminals.

uQUOTED-CHAR    = QUOTED-CHAR / UTF8-2 / UTF8-3 / UTF8-4

UTF8-2          = <Defined in Section 4 of RFC 3629>

UTF8-3          = <Defined in Section 4 of RFC 3629>

UTF8-4          = <Defined in Section 4 of RFC 3629>
```

When this extended quoting mechanism is used by the client, the server **MUST** reject, with a "BAD" response, any octet sequences with the high bit set that fail to comply with the formal syntax requirements of UTF-8 [[RFC3629](#)]. The IMAP server **MUST NOT** send UTF-8 in quoted-strings to the client unless the client has indicated support for that syntax by using the "ENABLE UTF8=ACCEPT" command.

If the server supports "UTF8=ACCEPT", the client **MAY** use extended quoted syntax with any IMAP argument that permits a string (including astring and nstring). However, if characters outside the US-ASCII repertoire are used in an inappropriate place, the results would be the same as if other syntactically valid but semantically invalid characters were used. Specific cases where UTF-8 characters are permitted or not permitted are described in the following paragraphs.

All IMAP servers that support "UTF8=ACCEPT" **SHOULD** accept UTF-8 in mailbox names, and those that also support the Mailbox International Naming Convention described in [[RFC3501](#)], [Section 5.1.3](#), **MUST** accept UTF-8 in mailbox names and convert them to the appropriate internal format. Mailbox names **MUST** comply with the Net-Unicode Definition ([RFC5198](#), [Section 2](#)) with the specific exception that they **MUST NOT** contain control characters (U+0000 - U+001F and U+0080 - U+009F), a delete character (U+007F), a line separator (U+2028), or a paragraph separator (U+2029).

Once an IMAP client has enabled UTF-8 support with the "ENABLE UTF8=ACCEPT" command, it **MUST NOT** issue a "SEARCH" command that contains a charset specification. If an IMAP server receives such a "SEARCH" command in that situation, it **SHOULD** reject the command with a "BAD" response (due to the conflicting charset labels). This also applies to any IMAP command or extension that includes an optional charset label and associated strings in the command arguments, including the MULTISEARCH extension. For commands with a mandatory charset field, such as SORT and THREAD, servers **SHOULD** reject charset values other than UTF-8 with a "BAD" response (due to the conflicting charset labels).

## 4. "APPEND" Command

If the server supports "UTF8=ACCEPT", then the server accepts UTF-8 headers in the "APPEND" command message argument.

If an IMAP server supports "UTF8=ACCEPT" and the IMAP client has not issued the "ENABLE UTF8=ACCEPT" command, the server **MUST** reject, with a "NO" response, an "APPEND" command that includes any 8-bit character in message header fields.

## 5. "LOGIN" Command and UTF-8

This specification does not extend the IMAP "LOGIN" command [RFC3501] to support UTF-8 usernames and passwords. Whenever a client needs to use UTF-8 usernames or passwords, it **MUST** use the IMAP "AUTHENTICATE" command, which is already capable of passing UTF-8 usernames and credentials.

Although using the IMAP "AUTHENTICATE" command in this way makes it syntactically legal to have a UTF-8 username or password, there is no guarantee that the user provisioning system utilized by the IMAP server will allow such identities. This is an implementation decision and may depend on what identity system the IMAP server is configured to use.

## 6. FETCH BODYSTRUCTURE and message/global

[RFC9051], Section 7.5.2 treats message/global like message/rfc, which means that for some messages, the response to FETCH BODYSTRUCTURE varies depending on whether IMAP4rev1 or IMAP4rev2 is in use.

[RFC6855] does not extend [RFC3501] in this respect. This document extends the media-message ABNF production to match [RFC9051].

```
media-message = DQUOTE "MESSAGE" DQUOTE SP
               DQUOTE ("RFC822" / "GLOBAL") DQUOTE
```

When IMAP4rev1 and UTF8=ACCEPT has been enabled, the server **MAY** treat message/global like message/rfc822 when computing the body structure, but **MAY** also treat it as described in [RFC3501]. Clients **MUST** accept both cases.

When IMAP4rev2 and UTF8=ACCEPT are in use, the server **MUST** behave as described in [RFC9051].

## 7. "UTF8=ONLY" Capability

The "UTF8=ONLY" capability indicates that the server supports "UTF8=ACCEPT" (see Section 3) and that it requires support for UTF-8 from clients. In particular, this means that the server will send UTF-8 in quoted-strings, and it will not accept the older international mailbox name convention (modified UTF-7 [RFC3501]). Because these are incompatible changes to IMAP, explicit server announcement and client confirmation are necessary: clients **MUST** use the "ENABLE UTF8=ACCEPT" command before using this server. A server that advertises "UTF8=ONLY" will reject, with a "NO [CANNOT]" response [RFC5530], any command that might require UTF-8 support and is not preceded by an "ENABLE UTF8=ACCEPT" command.

IMAP clients that find support for a server that announces "UTF8=ONLY" problematic are encouraged to at least detect the announcement and provide an informative error message to the end user.

Because the "UTF8=ONLY" server capability includes support for "UTF8=ACCEPT", the capability string will include, at most, one of those and never both. For the client, "ENABLE UTF8=ACCEPT" is always used -- never "ENABLE UTF8=ONLY".

## 8. Dealing with Legacy Clients

In most situations, it will be difficult or impossible for the implementer or operator of an IMAP (or POP) server to know whether all of the clients that might access it, or the associated mail store more generally, will be able to support the facilities defined in this document. In almost all cases, servers that conform to this specification will have to be prepared to deal with clients that do not enable the relevant capabilities. Unfortunately, there is no completely satisfactory way to do so other than for systems that wish to receive email that requires SMTPUTF8 capabilities to be sure that all components of those systems -- including IMAP and other clients selected by users -- are upgraded appropriately.

When a message that requires SMTPUTF8 is encountered and the client does not enable UTF-8 capability, choices available to the server include hiding the problematic message(s), creating in-band or out-of-band notifications or error messages, or somehow trying to create a surrogate of the message with the intention of providing useful information to that client about what has occurred. Such surrogate messages cannot be actual substitutes for the original message: they will almost always be impossible to reply to (either at all or without loss of information) and the new header fields or specialized constructs for server-client communications may go beyond the requirements of current email specifications (e.g., [RFC5322]). Consequently, such messages may confuse some legacy mail user agents (including IMAP clients) or not provide expected information to users. There are also trade-offs in constructing surrogates of the original message between accepting complexity and additional computation costs in order to try to preserve as much information as possible (for example, in "Post-Delivery Message Downgrading for Internationalized Email Messages" [RFC6857]) and trying to minimize those costs while still providing useful information (for example, in "Simplified POP and IMAP Downgrading for Internationalized Email" [RFC6858]).

Implementations that choose to perform downgrading **SHOULD** use one of the standardized algorithms provided in [RFC6857] or [RFC6858]. Getting downgrade algorithms right, and minimizing the risk of operational problems and harm to the email system, is tricky and requires careful engineering. These two algorithms are well understood and carefully designed.

Because such messages are really surrogates of the original ones, not really "downgraded" ones (although that terminology is often used for convenience), they inevitably have relationships to the originals that the IMAP specification [RFC3501] did not anticipate. This brings up two concerns in particular: First, digital signatures computed over and intended for the original message will often not be applicable to the surrogate message, and will often fail signature verification. (It will be possible for some digital signatures to be verified, if they cover only parts

of the original message that are not affected in the creation of the surrogate.) Second, servers that may be accessed by the same user with different clients or methods (e.g., POP or webmail systems in addition to IMAP or IMAP clients with different capabilities) will need to exert extreme care to be sure that UIDVALIDITY [RFC3501] behaves as the user would expect. Those issues may be especially sensitive if the server caches the surrogate message or computes and stores it when the message arrives with the intent of making either form available depending on client capabilities. Additionally, in order to cope with the case when a server compliant with this extension returns the same UIDVALIDITY to both legacy and "UTF8=ACCEPT"-aware clients, a client upgraded from being non-"UTF8=ACCEPT"-aware **MUST** discard its cache of messages downloaded from the server.

The best (or "least bad") approach for any given environment will depend on local conditions, local assumptions about user behavior, the degree of control the server operator has over client usage and upgrading, the options that are actually available, and so on. It is impossible, at least at the time of publication of this specification, to give good advice that will apply to all situations, or even particular profiles of situations, other than "upgrade legacy clients as soon as possible".

## 9. Issues with UTF-8 Header Mailstore

When an IMAP server uses a mailbox format that supports UTF-8 headers and it permits selection or examination of that mailbox without issuing "ENABLE UTF8=ACCEPT" first, it is the responsibility of the server to comply with the IMAP base specification [RFC3501] and the Internet Message Format [RFC5322] with respect to all header information transmitted over the wire. The issue of handling messages containing non-ASCII characters in legacy environments is discussed in [Section 8](#).

## 10. IANA Considerations

the "IMAP Capabilities" registry contained a number of references to [RFC6855]. IANA has updated them point to this document instead. The affected references are:

- UTF8=ACCEPT
- UTF8=ALL (OBSOLETE)
- UTF8=APPEND (OBSOLETE)
- UTF8=ONLY
- UTF8=USER (OBSOLETE)

## 11. Security Considerations

The security considerations of UTF-8 [RFC3629] and SASLprep [RFC4013] apply to this specification, particularly with respect to use of UTF-8 in usernames and passwords. Otherwise, this is not believed to alter the security considerations of IMAP.

Special considerations, some of them with security implications, occur if a server that conforms to this specification is accessed by a client that does not, as well as in some more complex situations in which a given message is accessed by multiple clients that might use different protocols and/or support different capabilities. Those issues are discussed in [Section 8](#).

## 12. References

### 12.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3501] Crispin, M., "INTERNET MESSAGE ACCESS PROTOCOL - VERSION 4rev1", RFC 3501, DOI 10.17487/RFC3501, March 2003, <<https://www.rfc-editor.org/info/rfc3501>>.
- [RFC3629] Yergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, RFC 3629, DOI 10.17487/RFC3629, November 2003, <<https://www.rfc-editor.org/info/rfc3629>>.
- [RFC4013] Zeilenga, K., "SASLprep: Stringprep Profile for User Names and Passwords", RFC 4013, DOI 10.17487/RFC4013, February 2005, <<https://www.rfc-editor.org/info/rfc4013>>.
- [RFC5161] Gulbrandsen, A., Ed. and A. Melnikov, Ed., "The IMAP ENABLE Extension", RFC 5161, DOI 10.17487/RFC5161, March 2008, <<https://www.rfc-editor.org/info/rfc5161>>.
- [RFC5198] Klensin, J. and M. Padlipsky, "Unicode Format for Network Interchange", RFC 5198, DOI 10.17487/RFC5198, March 2008, <<https://www.rfc-editor.org/info/rfc5198>>.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, DOI 10.17487/RFC5234, January 2008, <<https://www.rfc-editor.org/info/rfc5234>>.
- [RFC5322] Resnick, P., Ed., "Internet Message Format", RFC 5322, DOI 10.17487/RFC5322, October 2008, <<https://www.rfc-editor.org/info/rfc5322>>.
- [RFC6530] Klensin, J. and Y. Ko, "Overview and Framework for Internationalized Email", RFC 6530, DOI 10.17487/RFC6530, February 2012, <<https://www.rfc-editor.org/info/rfc6530>>.
- [RFC6532] Yang, A., Steele, S., and N. Freed, "Internationalized Email Headers", RFC 6532, DOI 10.17487/RFC6532, February 2012, <<https://www.rfc-editor.org/info/rfc6532>>.



- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

## 12.2. Informative References

- [RFC2088] Myers, J., "IMAP4 non-synchronizing literals", RFC 2088, DOI 10.17487/RFC2088, January 1997, <<https://www.rfc-editor.org/info/rfc2088>>.
- [RFC2342] Gahrns, M. and C. Newman, "IMAP4 Namespace", RFC 2342, DOI 10.17487/RFC2342, May 1998, <<https://www.rfc-editor.org/info/rfc2342>>.
- [RFC4314] Melnikov, A., "IMAP4 Access Control List (ACL) Extension", RFC 4314, DOI 10.17487/RFC4314, December 2005, <<https://www.rfc-editor.org/info/rfc4314>>.
- [RFC5530] Gulbrandsen, A., "IMAP Response Codes", RFC 5530, DOI 10.17487/RFC5530, May 2009, <<https://www.rfc-editor.org/info/rfc5530>>.
- [RFC5738] Resnick, P. and C. Newman, "IMAP Support for UTF-8", RFC 5738, DOI 10.17487/RFC5738, March 2010, <<https://www.rfc-editor.org/info/rfc5738>>.
- [RFC6855] Resnick, P., Ed., Newman, C., Ed., and S. Shen, Ed., "IMAP Support for UTF-8", RFC 6855, DOI 10.17487/RFC6855, March 2013, <<https://www.rfc-editor.org/info/rfc6855>>.
- [RFC6857] Fujiwara, K., "Post-Delivery Message Downgrading for Internationalized Email Messages", RFC 6857, DOI 10.17487/RFC6857, March 2013, <<https://www.rfc-editor.org/info/rfc6857>>.
- [RFC6858] Gulbrandsen, A., "Simplified POP and IMAP Downgrading for Internationalized Email", RFC 6858, DOI 10.17487/RFC6858, March 2013, <<https://www.rfc-editor.org/info/rfc6858>>.
- [RFC8620] Jenkins, N. and C. Newman, "The JSON Meta Application Protocol (JMAP)", RFC 8620, DOI 10.17487/RFC8620, July 2019, <<https://www.rfc-editor.org/info/rfc8620>>.
- [RFC9051] Melnikov, A., Ed. and B. Leiba, Ed., "Internet Message Access Protocol (IMAP) - Version 4rev2", RFC 9051, DOI 10.17487/RFC9051, August 2021, <<https://www.rfc-editor.org/info/rfc9051>>.

## Appendix A. Design Rationale

This non-normative section discusses the reasons behind some of the design choices in this specification.

The "UTF8=ONLY" mechanism simplifies diagnosis of interoperability problems when legacy support goes away. In the situation where backwards compatibility is not working anyway, the non-conforming "just-send-UTF-8 IMAP" has the advantage that it might work with some legacy clients. However, the difficulty of diagnosing interoperability problems caused by a "just-send-UTF-8 IMAP" mechanism is the reason the "UTF8=ONLY" capability mechanism was chosen.

## Appendix B. Changes since RFC 6855

This non-normative section describes the changes made since [\[RFC6855\]](#).

### B.1. APPEND UTF8

This document removes APPEND's UTF8 data item, making the UTF8-related syntax compatible with IMAP4rev2 as defined by [\[RFC9051\]](#) and making it simpler for clients to support IMAP4rev1 and IMAP4rev2 with the same code.

IMAP4rev2 [\[RFC9051\]](#) provides roughly the same abilities as [\[RFC6855\]](#) but does not include APPEND's UTF8 item. None of [\[RFC6855\]](#), IMAP4rev2, or JMAP [\[RFC8620\]](#) specify any way to learn whether a particular message was stored using the UTF8 data item. As of today, an IMAP client cannot learn whether a particular message was stored using the UTF8 data item, nor would it be able to trust that information even if IMAP4rev1 and 2 were extended to provide that information.

In July 2023, one of the authors found only one IMAP client that uses the UTF8 data item, and that client uses it incorrectly (it sends the data item for all messages if the server supports UTF8=ACCEPT, without regard to whether a particular message includes any UTF8 at all).

For these reasons, it was judged best to revise [\[RFC6855\]](#) and adopt the same syntax as IMAP4rev2.

### B.2. FETCH BODYSTRUCTURE

[\[RFC6532\]](#) defines a new media type, message/global, which is substantially like message/rfc822 except that the submessage may (also) use the syntax defined in [\[RFC6532\]](#). [\[RFC3501\]](#) and [\[RFC9051\]](#) define a FETCH item to return the media type of the body of a message, which servers usually compute once and store.

None of the RFCs point out to implementers that IMAP4rev1 and IMAP4rev2 are slightly different, so storing the BODYSTRUCTURE in the way servers and clients often do can easily lead to problems.

This document makes the syntax optional, making it simple for server authors to implement this extension correctly. This implies that clients need to parse and handle both varieties, which they need to do anyway if they want to support both IMAP4rev1 and IMAP4rev2.

## Acknowledgments

This document is an almost unchanged copy of [RFC6855], which was written by Pete Resnick, Chris Newman, and Sean Shen. Sean has since changed jobs and the current authors do not have a new email address for him. We cannot be sure that he would approve of the changes in this document, so we did not list him as author, but do gratefully acknowledge his work on [RFC6855]. Jiankang Yao replaces him.

The next paragraph is a straight copy of the acknowledgments in [RFC6855]:

The authors wish to thank the participants of the EAI working group for their contributions to this document, with particular thanks to Harald Alvestrand, David Black, Randall Gellens, Arnt Gulbrandsen, Kari Hurtta, John Klensin, Xiaodong Lee, Charles Lindsey, Alexey Melnikov, Subramanian Moonesamy, Shawn Steele, Daniel Taharlev, and Joseph Yee for their specific contributions to the discussion.

Many of them also reread the document during this revision.

## Authors' Addresses

### **Pete Resnick**

Episteme Technology Consulting LLC  
503 West Indiana Avenue  
Urbana, IL 61801-4941  
United States of America  
Email: [resnick@episteme.net](mailto:resnick@episteme.net)

### **Jiankang Yao**

CNNIC  
No.4 South 4th Zhongguancun Street  
Beijing  
100190  
China  
Email: [yaojk@cnnic.cn](mailto:yaojk@cnnic.cn)

### **Arnt Gulbrandsen**

ICANN  
6 Rond Point Schumann, Bd. 1  
1040 Brussels  
Belgium  
Email: [arnt@gulbrandsen.priv.no](mailto:arnt@gulbrandsen.priv.no)