Internet Engineering Task Force

Internet-Draft H. Watanabe

Intended status: Standards Track H. Takagi

Expires: November 19, 2012 RISEC, AIST

B. Kihara

Y. Oiwa

T. Hayashi

Lepidum

Y. Ioku

Yahoo! Japan

May 18, 2012

Mutual Authentication Protocol for HTTP: KAM3-based Cryptographic Algorithms draft-oiwa-http-mutualauth-algo-02

Abstract

This document specifies some cryptographic algorithms which will be used for the Mutual user authentication method for the Hyper-text Transport Protocol (HTTP).

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 19, 2012.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- 1. Introduction
 - 1.1. Terminology
- 2. Authentication Algorithms
 - 2.1. Support Functions and Notations
 - 2.2. Functions for Discrete-Logarithm Settings
 - 2.3. Functions for Elliptic-Curve Settings
- 3. IANA Considerations
- 4. Security Considerations
- 5. Notice on intellectual properties
- 6. References
 - 6.1. Normative References
 - 6.2. Informative References

Appendix A. (Informative) Group Parameters for Discrete-Logarithm Based Algorithms

Appendix B. (Informative) Derived Numerical Values

Appendix C. (Informative) Draft Change Log

- C.1. Changes in revision 02
- C.2. Changes in revision 01
- C.3. Changes in revision 00
- § Authors' Addresses

1. Introduction

This document specifies some algorithms for <u>Mutual authentication protocol for Hyper-Text Transport Protocol (HTTP)</u> [I-D.oiwa-http-mutualauth].

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

The terms "encouraged" and "advised" are used for suggestions that do not constitute "SHOULD"-level requirements. People MAY freely choose not to include the suggested items regarding [RFC2119], but complying with those suggestions would be a best practice; it will improve the security, interoperability, and/or operational performance.

The term "natural numbers" refers to the non-negative integers (including zero) throughout this document.

This document treats target (codomain) of hash functions to be natural numbers. The notation OCTETS(H(s)) gives a usual octet-string output of hash function H applied to string s.

2. Authentication Algorithms

This document specifies only one family of the authentication algorithm. The family consists of four authentication algorithms, which only differ in their underlying mathematical groups and security parameters. The algorithms do not add any additional parameters. The tokens for these algorithms are

- iso-kam3-dl-2048-sha256: for the 2048-bit discrete-logarithm setting with the SHA-256 hash function.
- iso-kam3-dl-4096-sha512: for the 4096-bit discrete-logarithm setting with the SHA-512 hash function.
- iso-kam3-ec-p256-sha256: for the 256-bit prime-field elliptic-curve setting with the SHA-256 hash function.
- iso-kam3-ec-p521-sha512: for the 521-bit prime-field elliptic-curve setting with the SHA-512 hash function.

For discrete-logarithm settings, the underlying groups are the 2048-bit and 4096-bit MODP groups defined in [RFC3526], respectively. See Appendix A for the exact specifications of the groups and associated parameters. The hash functions H are SHA-256 for the 2048-bit group and SHA-512 for the 4096-bit group, respectively, defined in FIPS PUB 180-2 [FIPS.180-2.2002]. The representation of the parameters kc1, ks1, vkc, and vks is base64-fixed-number.

For the elliptic-curve settings, the underlying groups are the elliptic curves over the prime fields P-256 and P-521, respectively, specified in the appendix D.1.2 of <u>FIPS PUB 186-3</u> [FIPS.186-3.2009] specification. The hash functions H, which are referenced by the core document, are SHA-256 for the P-256 curve and SHA-512 for the P-521 curve, respectively. The representation of the parameters kc1, ks1, vkc, and vks is hex-fixed-number.

Note: This algorithm is based on the Key Agreement Mechanism 3 (KAM3) defined in Section 6.3 of <u>ISO/IEC 11770-4</u> [ISO.11770-4.2006] with a few modifications/improvements. However, implementers should use this document as the normative reference, because the algorithm has been changed in several minor details as well as major improvements.

2.1. Support Functions and Notations

The algorithm definitions use several support functions and notations defined below:

The integers in the specification are in decimal, or in hexadecimal when prefixed with "0x".

The two functions named octet() and OCTETS() are those defined in the <u>core specification</u> [I-D.oiwa-http-mutualauth].

Note: The definition of OCTETS() is different from the function GE2OS_x in the original ISO specification, which takes the shortest representation without preceding zeros.

All of the algorithms defined in this specification use the default functions defined in the core specification for computing the values pi, VK_c and VK_s .

2.2. Functions for Discrete-Logarithm Settings

In this section, an equation $(x / y \mod z)$ denotes a natural number w less than z that satisfies $(w * y) \mod z = x \mod z$.

For the discrete-logarithm, we refer to some of the domain parameters by using the following symbols:

- q: for "the prime" defining the MODP group.
- g: for "the generator" associated with the group.
- r: for the order of the subgroup generated by g.

The function J is defined as

$$J(pi) = g^{(pi)} \mod q$$
.

The value of K_{c1} is derived as

$$K_{c1} = g^{\wedge}(S_{c1}) \bmod q,$$

where S_{c1} is a random integer within range [1, r-1] and r is the size of the subgroup generated by g. In addition, S_{c1} MUST be larger than log(q)/log(g) (so that $g^{(s)} > q$).

The value of K_{c1} SHALL satisfy $1 < K_{c1} < q-1$. The server MUST check this condition upon reception.

Let an intermediate value t₁ be

$$t_1 = H(octet(1) | OCTETS(K_{c1})),$$

the value of K_{s1} is derived from J(pi) and K_{c1} as:

$$K_{s1} = (J(pi) * K_{c1}^{(t_1)})^{(S_{s1})} \mod q$$

where S_{s1} is a random number within range [1, r-1]. The value of K_{s1} MUST satisfy $1 < K_{s1} < q$ -1. If this condition is not held, the server MUST retry using another value for S_{s1} . The client MUST check this condition upon reception.

Let an intermediate value t₂ be

$$t_2 = H(\text{octet}(2) \mid \text{OCTETS}(K_{c1}) \mid \text{OCTETS}(K_{s1})),$$

the value z on the client side is derived by the following equation:

$$z = K_{s1}^{((S_{c1} + t_2) / (S_{c1} * t_1 + pi) \mod r) \mod q}$$
.

The value z on the server side is derived by the following equation:

$$z = (K_{c1} * g^{(t_2)})^{(S_{s1})} \mod q$$
.

2.3. Functions for Elliptic-Curve Settings

For the elliptic-curve setting, we refer to some of the domain parameters by the following symbols:

- q: for the prime used to define the group.
- G: for the defined point called the generator.
- r: for the order of the subgroup generated by G.

The function P(p) converts a curve point p into an integer representing point p, by computing $x * 2 + (y \mod 2)$, where (x, y) are the coordinates of point p. P'(z) is the inverse of function P, that is, it converts an integer z to a point p that satisfies P(p) = z. If such p exists, it is uniquely defined. Otherwise, z does not represent a valid curve point. The operator + indicates the elliptic-curve group operation, and the operation [x] * p denotes an integer-multiplication of point p: it calculates p + p + ...

(x times) ... + p. See the literatures on elliptic-curve cryptography for the exact algorithms used for those functions (e.g. Section 3 of [RFC6090], which uses different notations, though.) 0_E represents the infinity point. The equation (x / y mod z) denotes a natural number w less than z that satisfies (w * y) mod z = x mod z.

The function J is defined as

$$J(pi) = [pi] * G.$$

The value of K_{c1} is derived as

$$K_{c1} = P(K_{c1}')$$
, where $K_{c1}' = [S_{c1}] * G$,

where S_{c1} is a random number within range [1, r-1]. The value of K_{c1} MUST represent a valid curve point, and K_{c1} ' SHALL NOT be 0_E . The server MUST check this condition upon reception.

Let an intermediate integer t₁ be

$$t_1 = H(octet(1) | OCTETS(K_{c1})),$$

the value of K_{s1} is derived from J(pi) and $K_{c1}' = P'(K_{c1})$ as:

$$K_{s1} = P([S_{s1}] * (J(pi) + [t_1] * K_{c1}')),$$

where S_{s1} is a random number within range [1, r-1]. The value of K_{s1} MUST represent a valid curve point and satisfy [4] * P'(K_{s1}) <> 0_E . If this condition is not satisfied, the server MUST retry using another value for S_{s1} . The client MUST check this condition upon reception.

Let an intermediate integer t₂ be

$$t_2 = H(\text{octet}(2) \mid \text{OCTETS}(K_{c1}) \mid \text{OCTETS}(K_{s1})),$$

the value z on the client side is derived by the following equation:

$$z = P([(S_{c1} + t_2) / (S_{c1} * t_1 + pi) \text{ mod } r] * P'(K_{s1})).$$

The value z on the server side is derived by the following equation:

$$z = P([S_{s1}] * (P'(K_{c1}) + [t_2] * G)).$$

3. IANA Considerations

Four tokens iso-kam3-dl-2048-sha256, iso-kam3-dl-4096-sha512, iso-kam3-ec-p256-sha256 and iso-kam3-ec-p521-sha512 shall be allocated and registered according to the provision of the core documentation when this document is promoted to an RFC.

Note: More formal declarations will be added in the future drafts to meet the RFC 5226 requirements.

4. Security Considerations

Refer the corresponding section of the core specification for algorithm-independent, generic considerations.

- All random numbers used in these algorithms MUST be at least cryptographically computationally secure against forward and backward guessing attacks.
- Computation times of all numerical operations on discrete-logarithm group elements and elliptic-curve points MUST be normalized and made independent of the exact values, to prevent timing-based side-channel attacks.

5. Notice on intellectual properties

The National Institute of Advanced Industrial Science and Technology (AIST) and Yahoo! Japan, Inc. has jointly submitted a patent application on the protocol proposed in this documentation to the Patent Office of Japan. The patent is intended to be open to any implementors of this protocol and its variants under non-exclusive royalty-free manner. For the details of the patent application and its status, please contact the author of this document.

The elliptic-curve based authentication algorithms might involve several existing third-party patents. The authors of the document take no position regarding the validity or scope of such patents, and other patents as well.

6. References

6.1. Normative References

[FIPS.180-2.2002]	National Institute of Standards and Technology, "Secure Hash Standard," FIPS PUB 180-2, August 2002.
[FIPS.186-3.2009]	National Institute of Standards and Technology, " <u>Digital Signature Standard (DSS)</u> ," FIPS PUB 186-3, June 2009.
[I-D.oiwa-http-mutualauth]	Oiwa, Y., Watanabe, H., Takagi, H., Kihara, B., Hayashi, T., and Y. Ioku, " <u>Mutual Authentication Protocol for HTTP</u> ," draft-oiwa-http-mutualauth-11 (work in progress), May 2012.
[RFC2119]	Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," BCP 14, RFC 2119, March 1997 (TXT, HTML, XML).
[RFC3526]	Kivinen, T. and M. Kojo, "More Modular Exponential (MODP) <u>Diffie-Hellman groups for Internet Key Exchange (IKE)</u> ," RFC 3526, May 2003 (<u>TXT</u>).

6.2. Informative References

[ISO.11770-4.2006] International Organization for Standardization, "Information technology – Security techniques – Key management – Part 4: Mechanisms based on weak secrets," ISO Standard 11770-4, May 2006.

Appendix A. (Informative) Group Parameters for Discrete-Logarithm Based Algorithms

The MODP group used for the iso-kam3-dl-2048-sha256 algorithm is defined by the following parameters.

The prime is:

```
      q =
      0xFFFFFFFF
      FFFFFFFF
      C90FDAA2
      2168C234
      C4C6628B
      80DC1CD1

      29024E08
      8A67CC74
      020BBEA6
      3B139B22
      514A0879
      8E3404DD

      EF9519B3
      CD3A431B
      302B0A6D
      F25F1437
      4FE1356D
      6D51C245

      E485B576
      625E7EC6
      F44C42E9
      A637ED6B
      0BFF5CB6
      F406B7ED

      EE386BFB
      5A899FA5
      AE9F2411
      7C4B1FE6
      49286651
      ECE45B3D

      C2007CB8
      A163BF05
      98DA4836
      1C55D39A
      69163FA8
      FD24CF5F

      83655D23
      DCA3AD96
      1C62F356
      208552BB
      9ED52907
      7096966D

      670C354E
      4ABC9804
      F1746C08
      CA18217C
      32905E46
      2E36CE3B

      E39E772C
      180E8603
      9B2783A2
      EC07A28F
      B5C55DF0
      6F4C52C9

      DE2BCBF6
      95581718
      3995497C
      EA956AE5
      15D22618
      98FA0510

      15728E5A
      8AACAA68
      FFFFFFFF
      FFFFFFFF
```

The generator is:

g = 2.

The size of the subgroup generated by g is:

```
r = (q - 1) / 2 =

0x7FFFFFFF FFFFFFFF E487ED51 10B4611A 62633145 C06E0E68
94812704 4533E63A 0105DF53 1D89CD91 28A5043C C71A026E
F7CA8CD9 E69D218D 98158536 F92F8A1B A7F09AB6 B6A8E122
F242DABB 312F3F63 7A262174 D31BF6B5 85FFAE5B 7A035BF6
F71C35FD AD44CFD2 D74F9208 BE258FF3 24943328 F6722D9E
E1003E5C 50B1DF82 CC6D241B 0E2AE9CD 348B1FD4 7E9267AF
C1B2AE91 EE51D6CB 0E3179AB 1042A95D CF6A9483 B84B4B36
B3861AA7 255E4C02 78BA3604 650C10BE 19482F23 171B671D
F1CF3B96 0C074301 CD93C1D1 7603D147 DAE2AEF8 37A62964
EF15E5FB 4AAC0B8C 1CCAA4BE 754AB572 8AE9130C 4C7D0288
0AB9472D 45565534 7FFFFFFF FFFFFFFF.
```

The MODP group used for the iso-kam3-dl-4096-sha512 algorithm is defined by the following parameters.

The prime is:

```
      q =
      0xFFFFFFFF
      FFFFFFFF
      C90FDAA2
      2168C234
      C4C6628B
      80DC1CD1

      29024E08
      8A67CC74
      020BBEA6
      3B139B22
      514A0879
      8E3404DD

      EF9519B3
      CD3A431B
      302B0A6D
      F25F1437
      4FE1356D
      6D51C245

      E485B576
      625E7EC6
      F44C42E9
      A637ED6B
      0BFF5CB6
      F406B7ED

      EE386BFB
      5A899FA5
      AE9F2411
      7C4B1FE6
      49286651
      ECE45B3D

      C2007CB8
      A163BF05
      98DA4836
      1C55D39A
      69163FA8
      FD24CF5F

      83655D23
      DCA3AD96
      1C62F356
      208552BB
      9ED52907
      7096966D

      670C354E
      4ABC9804
      F1746C08
      CA18217C
      32905E46
      2E36CE3B

      E39E772C
      180E8603
      9B2783A2
      EC07A28F
      B5C55DF0
      6F4C52C9

      DE2BCBF6
      95581718
      3995497C
      EA956AE5
      15D22618
      98FA0510
```

```
      15728E5A
      8AAAC42D
      AD33170D
      04507A33
      A85521AB
      DF1CBA64

      ECFB8504
      58DBEF0A
      8AEA7157
      5D060C7D
      B3970F85
      A6E1E4C7

      ABF5AE8C
      DB0933D7
      1E8C94E0
      4A25619D
      CEE3D226
      1AD2EE6B

      F12FFA06
      D98A0864
      D8760273
      3EC86A64
      521F2B18
      177B200C

      BBE11757
      7A615D6C
      770988C0
      BAD946E2
      08E24FA0
      74E5AB31

      43DB5BFC
      E0FD108E
      4B82D120
      A9210801
      1A723C12
      A787E6D7

      88719A10
      BDBA5B26
      99C32718
      6AF4E23C
      1A946834
      B6150BDA

      2583E9CA
      2AD44CE8
      DBBBC2DB
      04DE8EF9
      2E8EFC14
      1FBECAA6

      287C5947
      4E6BC05D
      99B2964F
      A090C3A2
      233BA186
      515BE7ED

      1F612970
      CEE2D7AF
      B81BDD76
      2170481C
      D0069127
      D5B05AA9

      93B4EA98
      8D8FDDC1
      86FFB7DC
      90A6C08F
      4DF435C9
      34063199

      FFFFFFFF
      FFFFFFFFF
```

The generator is:

g = 2.

The size of the subgroup generated by g is:

```
r = (q - 1) / 2 =
    0x7FFFFFF FFFFFFF E487ED51 10B4611A 62633145 C06E0E68
      94812704 4533E63A 0105DF53 1D89CD91 28A5043C C71A026E
      F7CA8CD9 E69D218D 98158536 F92F8A1B A7F09AB6 B6A8E122
      F242DABB 312F3F63 7A262174 D31BF6B5 85FFAE5B 7A035BF6
      F71C35FD AD44CFD2 D74F9208 BE258FF3 24943328 F6722D9E
      E1003E5C 50B1DF82 CC6D241B 0E2AE9CD 348B1FD4 7E9267AF
      C1B2AE91 EE51D6CB 0E3179AB 1042A95D CF6A9483 B84B4B36
      B3861AA7 255E4C02 78BA3604 650C10BE 19482F23 171B671D
      F1CF3B96 0C074301 CD93C1D1 7603D147 DAE2AEF8 37A62964
      EF15E5FB 4AAC0B8C 1CCAA4BE 754AB572 8AE9130C 4C7D0288
      0AB9472D 45556216 D6998B86 82283D19 D42A90D5 EF8E5D32
      767DC282 2C6DF785 457538AB AE83063E D9CB87C2 D370F263
      D5FAD746 6D8499EB 8F464A70 2512B0CE E771E913 0D697735
      F897FD03 6CC50432 6C3B0139 9F643532 290F958C 0BBD9006
      5DF08BAB BD30AEB6 3B84C460 5D6CA371 047127D0 3A72D598
      AleDADFE 707E8847 25C16890 54908400 8D391E09 53C3F36B
      C438CD08 5EDD2D93 4CE1938C 357A711E 0D4A341A 5B0A85ED
      12C1F4E5 156A2674 6DDDE16D 826F477C 97477E0A 0FDF6553
      143E2CA3 A735E02E CCD94B27 D04861D1 119DD0C3 28ADF3F6
      8FB094B8 67716BD7 DC0DEEBB 10B8240E 68034893 EAD82D54
      C9DA754C 46C7EEE0 C37FDBEE 48536047 A6FA1AE4 9A0318CC
      FFFFFFFF FFFFFFFF.
```

Appendix B. (Informative) Derived Numerical Values

This section provides several numerical values for implementing this protocol, derived from the above specifications. The values shown in this section are for informative purposes only.

	dl-2048	dl-4096	ec-p256	ec-p521	
Size of K _{c1} etc.	2048	4096	257	522	(bits)
Size of H()	256	512	256	512	(bits)
length of OCTETS(K_{c1}) etc.	256	512	33	66	(octets)
length of kc1, ks1 param. values.	344 *	684 *	66	132	(octets)
length of vkc, vks param. values.	44 *	88 *	64	128	(octets)

(The numbers marked with an * do not include any enclosing quotation marks.)

Appendix C. (Informative) Draft Change Log

C.1. Changes in revision 02

• Implementation hints in appendix changed (number of characters for base64-fixed-number does not contain double-quotes).

C.2. Changes in revision 01

- Parameter names renamed.
- Some expressions clarified without changing the value.

C.3. Changes in revision 00

The document is separated from the revision 08 of the core documentation.

Authors' Addresses

Yutaka Oiwa

National Institute of Advanced Industrial Science and Technology

Research Institute for Secure Systems

Tsukuba Central 2

1-1-1 Umezono

Tsukuba-shi, Ibaraki

ΙP

Email: mutual-auth-contact-ml@aist.go.jp

Hajime Watanabe

National Institute of Advanced Industrial Science and Technology

Hiromitsu Takagi

National Institute of Advanced Industrial Science and Technology

Boku Kihara

Lepidum Co. Ltd.

#602, Village Sasazuka 3

1-30-3 Sasazuka

Shibuya-ku, Tokyo

JP

Tatsuya Hayashi

Lepidum Co. Ltd.

Yuichi Ioku

Yahoo! Japan, Inc. Midtown Tower 9-7-1 Akasaka Minato-ku, Tokyo JP