

repththeorem*

Jesse Straat

2024-10-07

Abstract

When writing a large manuscript, it is sometimes beneficial to repeat a theorem (or lemma or ...) at an earlier or later point for didactical purposes. However, `thmtools`'s built-in `restatable` only allows replicating theorems *after* they have been stated, and only in the same document. `repththeorem` solves the issue by making use of the `.aux` file, and also introduces its own file extension, `.thm`, to replicate theorems in other files.

Contents

1 Repeating theorems	1
2 Replicating theorems between files	3
2.1 Replicating theorems to subfiles	3
3 Source code	3

1 Repeating theorems

Let's say we define a theorem as follows:

```
\begin{theorem}[Yoneda Lemma]
  For  $(F\colon \mathcal{C}\to \mathbf{Set})$  a functor,
   $([\mathcal{C}^{\mathrm{op}}, \mathbf{Set}](YA, F) \cong F(A))\%$ 
  for all objects  $A$  in  $\mathcal{C}$ .
\end{theorem}
```

Its output is of course

Theorem 1 (Yoneda Lemma). *For $F\colon \mathcal{C} \rightarrow \mathbf{Set}$ a functor, $[\mathcal{C}^{\mathrm{op}}, \mathbf{Set}](YA, F) \cong F(A)$ for all objects A in \mathcal{C} .*

Now let's say we want to replicate the theorem within the same document. `makethm` (*env.*) That is what the new environment `makethm` is used for.

```
\begin{makethm}{theorem}{thm:Yoneda}[Yoneda Lemma]
  For  $(F\colon \mathcal{C}\to \mathbf{Set})$  a functor,
```

*Version v1.3, last revised 2024-10-07.

```

\([\mathcal{C}^{\mathrm{op}}, \mathbf{Set}](YA, F) \cong F(A)\)
for all objects  $A$  in  $\mathcal{C}$ .
\end{makethm}

```

Its output is the same (in fact, we’ve secretly used `makethm` in the previous example), but the important difference is that we have saved the theorem for later use.

The `makethm` environment takes two mandatory arguments and one optional one. The first mandatory argument is the type of theorem environment as defined in `amsthm`, like `theorem`, `lemma`, `definition`, etc. The second is the theorem’s label. The label is mandatory since, to replicate the theorem, we need to have a “name” attached to it. `makethm` automatically attaches a `\label`, as well, so `\ref{thm:Yoneda}` becomes `1`. The optional argument is passed right to the optional argument of the theorem environment, giving the theorem a name.

Now let’s say we want to replicate the theorem later or earlier in the text. This may be done if, for example, the theorem is proven at a later point, or we want to “tease” the reader with a powerful theorem that will be proven later in the chapter. To do this, we use the `\repthm` command: `\repthm{thm:Yoneda}`. This outputs the theorem again.

Theorem 1 (Yoneda Lemma). *For $F: \mathcal{C} \rightarrow \mathbf{Set}$ a functor, $[\mathcal{C}^{\mathrm{op}}, \mathbf{Set}](YA, F) \cong F(A)$ for all objects A in \mathcal{C} .*

The label of this theorem is a `\ref`, and automatically links to the original theorem statement.

If the original theorem statement exists in a different file, or has not been created yet, we can add a placeholder alt text to the `\repthm` as an optional argument, which only displays if the theorem is undefined. For example, `\repthm{thm:foo}[bar]` returns

Theorem ??. *bar*

If we do the same without providing an alt text, we get

Theorem ??.

together with a warning: “Package repttheorem: Theorem `thm:foo` not defined; rebuild your project. If the issue persists, create the theorem using `\begin{makethm}{theorem}{thm:foo}` or consider adding alt text to `\repthm` using the optional parameter.”

Since we’re using the `.aux` file, it is possible to replicate a theorem before it is stated. For example,

```

\repthm{thm:later}
\begin{makethm}{theorem}{thm:later}
Alligator!
\end{makethm}

```

returns

Theorem 2. *Alligator*

Theorem 2. *Alligator*

Note that it is necessary to run a `.tex` file twice to replicate theorems ahead of time, similarly to how one has to run a file twice to make sure the references are correct.

2 Replicating theorems between files

Let's say we have the following files for our project:

```
foo.tex
bar.tex
```

Let's say that we have defined a theorem `thm:baz` in `bar.tex`, and we want to replicate it in `foo.tex`. To achieve this, we first use the `\theoremfile` command in the preamble of `bar.tex`. This compiles all theorems defined in `bar.tex` and outputs them into a file `bar.thm`. To then import these into `foo.tex`, we use `\loadtheorems` `\loadtheorems{bar.thm}` in the preamble, which loads all theorems saved in `bar.thm`. One can then use `\repthm` as usual.

Since the `.aux` file is loaded at `\begin{document}`, putting `\loadtheorems` in the preamble of a file will guarantee that the loaded theorem file will be overwritten by the theorems in the `.aux` file, i.e., theorems defined in the same document. In our example, if we also defined a `thm:baz` in `foo.tex`, loading `bar.thm` into `foo.tex` will not overwrite the local `thm:baz`.

2.1 Replicating theorems to subfiles

Replicating theorems to different files is particularly useful when working in big documents with multiple subfiles. For example, let's say we have the files

```
main.tex
foo.tex
bar.tex
```

Here, `main.tex` is generated by including `foo.tex` and `bar.tex` as chapters, creating a single large document. It is now possible to replicate theorems within the subfiles by running `\theoremfile` in `main.tex`, and then using `\loadtheorems{main.thm}` in `foo.tex` and `bar.tex`. This will allow us to use all theorems in the final `main.tex` in each of the subfiles.

3 Source code

```
1 (*package)
2 \ProvidesPackage{repththeorem}[2024-10-07 v1.3 Reptheorem package]
\theoremfile Using \theoremfile will output all saved theorems into an output file. By default,
if your LATEX file is foo.tex, the output file is foo.thm.
3 \def\repththeorem@theoremfile{\relax}
4 \NewDocumentCommand{\theoremfile}{ 0{\jobname.thm} }{
5 % 0: the path of the file to which we should save theorems
6 %
7 \def\repththeorem@theoremfile{#1}
```

```

8 \newwrite\@thmlist
9 \immediate\openout\@thmlist=#1
10 }

```

`\loadtheorems` If you have exported saved theorems to a file, you can load them into another file using the macro `\loadtheorems`.

```

11 \NewDocumentCommand{\loadtheorems}{m}{
12 \IfFileExists{#1}{
13 \input{#1}
14 }{
15 \PackageWarning{repththeorem}{%
16 File #1 not found. I will not import any theorems.%
17 }
18 }
19 }

```

`makethm` (*env.*) On to defining the actual theorems to be saved.

```

20 \NewDocumentEnvironment{makethm}{m m o +b }
21 % m: the type of theorem environment
22 % m: the name of the theorem
23 % o: optional parameter for environment
24 % b: the content of the theorem
25 %
26 {%
27 \IfValueTF{#3}{% Check if theorem has optional arguments
28 \begin{#1}[#3]\label{#2}
29 }{
30 \begin{#1}\label{#2}
31 }
32 % \begin{theorem}
33 #4
34 \expandafter\gdef\csname thmtype@#2\endcsname{#1}%
35 \expandafter\long\expandafter\gdef\csname thm@#2\endcsname{#4}%
36 \IfValueT{#3}{% Only save theorem name if it exists
37 \expandafter\gdef\csname thmdesc@#2\endcsname{#3}%
38 }
39 % Saving parameters to aux file
40 \expandafter\long\expandafter\gdef\csname thmoutput@#2\endcsname{%
41 \string\expandafter\string\gdef\noexpand%
42 \csname thmtype@#2\string\endcsname{#1}%
43 ^^J%
44 \string\expandafter\string\long\string\expandafter%
45 \string\gdef\noexpand\csname thm@#2\string\endcsname{#4}%
46 \IfValueT{#3}{
47 ^^J%
48 \string\expandafter\string\gdef\noexpand%
49 \csname thmdesc@#2\string\endcsname{#3}%
50 }
51 }
52 \write@auxout{\csname thmoutput@#2\endcsname}
53 \if\repththeorem@theoremfile\relax
54 % No file has been set
55 \else
56 % We have a theorem file

```

```

57   % Saving parameters to theorem file
58   \write\thmlist{\csname thmoutput@#2\endcsname}
59   \fi
60   \end{#1}
61 }{}

```

`\repthm` To repeat a theorem, use the `\repthm` command.

```

62 \newcounter{old@counter}
63 \NewDocumentCommand{\repthm}{ m +o }{
64   % m: the name of the theorem
65   % o: alt text
66   \begingroup
67   % Check if thmtype is given
68   \ifcsname thmtype@#1\endcsname%
69   \expandafter\let\expandafter\@@thmtype\csname thmtype@#1\endcsname%
70   \else%
71   \def\@@thmtype{theorem}%
72   \fi%
73   %
74   % Save theorem counter so we don't increase it
75   \setcounter{old@counter}{\value{\@@thmtype}}
76   \setcounter{\@@thmtype}{-900}
77   \expandafter\def\csname the\@@thmtype\endcsname{\ref{#1}}
78   \let\@@theoremnotdefined\relax
79   %
80   \ifcsname thm@#1\endcsname% Check if theorem is even defined
81   % Theorem is defined
82   \expandafter\let\expandafter\@thm\csname thm@#1\endcsname
83   % Output theorem
84   \ifcsname thmdesc@#1\endcsname % Check if theorem has name
85   \begin{\@@thmtype}[\csname thmdesc@#1\endcsname]
86     \@thm
87   \end{\@@thmtype}
88   \else % No optionals
89   \begin{\@@thmtype}
90     \@thm
91   \end{\@@thmtype}
92   \fi
93   \else
94   % Theorem undefined
95   \IfValueTF{#2}{
96     \begin{\@@thmtype}
97       #2
98     \end{\@@thmtype}
99   }{% No theorem or alt text provided: throw warning
100     \begin{\@@thmtype}
101     \end{\@@thmtype}
102     \PackageWarning{repthm}{%
103       Theorem #1 not defined; rebuild your project.
104       If the issue persists, create the theorem using
105       \begin{makethm} or consider adding alt text to \repthm
106       using the optional parameter%
107     }
108   }

```

```

109 \fi
110 \setcounter{\@thmtype}{\value{old@counter}}
111 % Reset theorem counter back to original
112 \endgroup
113 }
114 </package>

```

Change History

v1.0		Theorem name is only saved if it exists.	4
General: First public release	1		
v1.1		<code>\repthm</code> : Fixed bug where theorems got a name even if undefined.	5
<code>makethm</code> : Now saves theorem environment type, breaking backwards compatibility.	4		
<code>\repthm</code> : Now saves theorem environment type, breaking backwards compatibility.	5	v1.3	
		<code>\repthm</code> : Added hyperref named destination compatibility by setting counter to very low value	5
v1.2		Changed <code>thetheorem</code> to <code>csname</code> to fix compatibility with theorem types not called “theorem”.	5
<code>makethm</code> : Environment end moved to fix vertical spacing.	4		
Renamed theorem output variable to be unique for each theorem.	4		

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in **roman** refer to the code lines where the entry is used.

Symbols	I	P
<code>\@theoremnotdefined</code> <i>78</i>	<code>\IfValueT</code> <i>36, 46</i>	<code>\PackageWarning</code> <i>15, 102</i>
<code>\@thm</code> <i>82, 86, 90</i>	L	
<code>\@thmtype</code> <i>69,</i>	<code>\loadtheorems</code> <i>3, 11</i>	R
<i>71, 75, 76, 77,</i>	M	<code>\reptheorem@theoremfile</code>
<i>85, 87, 89, 91,</i>	<code>makethm</code> (env.) <i>1, 20</i> <i>3, 7, 53</i>
<i>96, 98, 100, 101, 110</i>	N	<code>\repthm</code> <i>2, 62</i>
<code>\@auxout</code> <i>52</i>	<code>\newwrite</code> <i>8</i>	
<code>\@thmlist</code> <i>8, 9, 58</i>	O	T
E	<code>\openout</code> <i>9</i>	<code>\theoremfile</code> <i>3, 3</i>
environments:		
<code>makethm</code> <i>1, 20</i>		